



### FEATURES:

- Composed of no asphalt, Hawk-Seal provides a special High-Tack feature only found in butyl
- Use Hawk-Seal on joints in: Box culverts, manholes, concrete pipe, septic tanks, utility boxes, and vaults
- No special tools needed
- Designed for flexibility in temperature extremes
- Excellent chemical resistance
- Hawk-Seal tolerates joint deflection
- Indefinite Service Life

### DIRECTIONS:

- Joint surface should be clean and dry. Unroll the sealant onto the joint. Light pressure on the release paper side of the sealant will help to keep the sealant in place. After the entire joint has sealant in place leave the release paper intact until the joint is about to be sealed.
- When joining two ends of Hawk-Seal avoid overlapping sealant. Use the splicing method.
- Splicing Method: Butt the two ends together without overlapping. The two ends then will fuse together after light pressure.

Note: To find annular space to be filled subtract the outside diameter of the tongue from the inside diameter of the groove and divide by two.

SIZE	ROLL LENGTH	ROLLS/CARTON	CARTONS/PALLET
1/2"	26"	12	27
3/4"	14' 6"	10	36
1"	14' 6"	8	36
1 1/4"	14' 6"	6	36
1 1/2"	10'	6	36
3/4" x 2 1/4"	14' 6"	4	36

Meets ASTM C-990-01A and AASHTOM-198 and SS-S-210

### ORDERING INFORMATION

For additional information, prices, or to place an order, please contact your ErgonArmor sales representative. If you do not know the name of your sales representative, call 877-98ARMOR.

Data Sheet Revised July 2009

All statements, technical information, and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, express or implied. Sellers and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and user assumes all risk and liability whatsoever therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.