

**DESCRIPTION:**

Hawk-Wrap is a high-tack butyl rubber compound laminated with a tough poly backing for added strength. Hawk-Wrap comes in roll form and is unrolled over concrete joints externally and functions as a seal against infiltration and exfiltration.

**USES:**

Hawk-Wrap can be used virtually anywhere there is an external concrete joint including:

- Manhole Joints
- Septic Tank Joints
- Pipe Joints (both elliptical and round)
- Box Culverts
- Arches
- Burial Vaults
- Grade Ring Joints
- Concrete Bridge Spans
- Vacuum Test Leaks

Hawk-Wrap can be used on new and rehabilitation jobs.

**SURFACE PREPARATION:**

Surface must be free from all release agents, dirt, dust and debris to ensure that the Wrap is bonding with the concrete only. Surface may be primed in difficult situations and rehabilitation jobs. Primer is not typically necessary. If conditions exist where a primer is being considered, please consult ErgonArmor.

**APPLICATION:**

- 1.) Center the Hawk-Wrap over the joint, sticky black side down and apply in an unrolling fashion.
- 2.) Ensure full adhesion by running a hand across the Hawk-Wrap with full pressure to promote the adhesion to the concrete.
- 3.) Be sure to eliminate all air bubbles and wrinkles.
- 4.) When the roll is unwrapped far enough to overlap on the beginning of the roll by 6 inches cut the wrap with scissors or knife and adhere to itself.

**SIZES:**

6" X 33'

9" x 33'

12" x 33'

Other sizes and lengths available through special order.

**PHYSICAL PROPERTIES:**

Meets or exceeds the following:

ASTM C-877

ASTM C-990



## ORDERING INFORMATION

For additional information, prices, or to place an order, please contact your ErgonArmor sales representative. If you do not know the name of your sales representative, call 877-98ARMOR.

Data Sheet Revised July 2009

All statements, technical information, and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, express or implied. Sellers and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and user assumes all risk and liability whatsoever therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.



A Division of Ergon Asphalt & Emulsions, Inc. | P.O. Box 1639, Jackson, MS 39215-1639  
913-371-1354 Fax | 877-98ARMOR | [ergonarmor.com](http://ergonarmor.com)