

UNDER BODY COATING**DESCRIPTION:**

Ertech 2010 undercoating is a non-fibered asphalt emulsion designed for use on underbodies of trucks, trailers, buses, and RV's. This product is formulated using selected mineral fillers and emulsified asphalts that yield low VOC and provide excellent protection to guard against corrosion on steel surfaces and other substrates. Being water based, Ertech 2010 is non-flammable and presents no hazards from open flame or welding in the work area.

USES:

The primary application of Ertech 2010 is for protection of transportation equipment underbodies. It is also used as a general corrosion protection coating over many different surfaces, metal parts, or where a moisture barrier is needed.

APPLICATION:

Ertech 2010 is designed for spray application using airless equipment. A 15:1 or higher ratio pump with a minimum .023 orifice size is recommended. This product displays excellent mechanical stability when exposed to high shear pumps.

SURFACE PREPARATION:

Prior to application of the coating, surfaces should be cleaned of dirt or loose material; oils and greases must be removed with proper solvents. Powdery or flaked corrosion should be sandblasted or mechanically removed.

CLEAN UP:

Tools and hands should be cleaned with soap and water before emulsion sets. Dried material can be cleaned with kerosene or petroleum naphtha. Use care in handling solvents.

TYPICAL PROPERTIES

Density, lbs/gal	9.7
Solids Content, % by Weight	50
Dry Time, Hours @ 77° F., to touch	2-4
Consistency	Semi paste-like
Color	Black
Water Resistance (ASTM D 2939-94)	
Blistering	None
Re-emulsification	Nil
Resistance to Oils, Greases, & Solvents	Poor
Volatile Organic Content (EPA Method 24)	0.2 lbs/gal
Flash Point Pensky Martens Closed Cup, Deg. F., Min.	NA
Application Ambient Temperature Range, Deg F.	50-120
Storage Stability	Must be protected from freezing

ORDERING INFORMATION

For additional information, prices, or to place an order, please contact your ErgonArmor sales representative. If you do not know the name of your sales representative, call 877-98ARMOR.

Data Sheet Revised July 2009

All statements, technical information, and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, express or implied. Sellers and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and user assumes all risk and liability whatsoever therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.