SAFETY DATA SHEET



1. Identification

Product identifier BH5330 Other means of identification None

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

1-800-222-7122

Normal work hours

telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3 **Health hazards** Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Germ cell mutagenicity Category 1

> Carcinogenicity Category 1 Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

exposure

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer. Causes damage to organs through prolonged or repeated exposure. May cause

genetic defects. Causes serious eve irritation. Flammable liquid and vapor. May cause drowsiness

Category 1

or dizziness. Causes skin irritation.

Precautionary statement

Prevention Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or

smoke when using this product. Keep container tightly closed. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces, - No smoking, Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and

understood.

Material name: BH5330 SDS US Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs, seek medical advice/attention. If eye irritation persists: Get medical advice/attention. Specific treatment see Section 4 of this SDS. IF ON

SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower. In case of fire: Use appropriate media for extinction. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. IF exposed or concerned: Get medical

advice/attention. Get medical advice/attention if you feel unwell.

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

See section 13 of this SDS for disposal instructions.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	30 - 40
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY		64742-48-9	20 - 30
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.		64742-95-6	1 - 10
1,2,4-TRIMETHYLBENZENE		95-63-6	0 - 5
BENZENE		71-43-2	<1
QUARTZ		14808-60-7	< 1
Other components below reportable	e levels		35.54

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing

difficulties, oxygen may be necessary. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if

needed.

Skin contact For hot product, immediately immerse in or flush the affected area with large amounts of cold

water to dissipate heat. For minor skin contact, avoid spreading material on unaffected skin. Wash

off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO Eye contact

NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and

persists.

Ingestion Rinse mouth thoroughly. Call a POISON CENTER or doctor/physician. Do not induce vomiting

without advice from poison control center. If vomiting occurs, keep head low so that stomach

content doesn't get into the lungs.

Most important

delayed

symptoms/effects, acute and

Not available.

Indication of immediate

medical attention and special treatment needed

In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

Foam. Carbon dioxide (CO2). Water fog. Dry chemical powder.

media

Do not use water jet.

Material name: BH5330 SDS US Specific hazards arising from the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Do not get water inside container. Some of these materials, if spilled, may evaporate leaving a flammable residue.

Specific methods

In the event of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

7. Handling and storage

Precautions for safe handling

Avoid heat, sparks, open flames and other ignition sources. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Do not use in areas without adequate ventilation. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container closed. Keep container dry. Keep away from food, drink and animal feedingstuffs. Keep out of reach of children. Use care in handling/storage.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Components	Substances (29 CFR 1910.10 Type	01-1050) Value	
BENZENE (CAS 71-43-2)	STEL	5 ppm	
	TWA	1 ppm	
US. OSHA Table Z-1 Limits for Air Components	Contaminants (29 CFR 1910 Type	0.1000) Value	Form
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-2 (29 CFR 191) Components	0.1000) Type	Value	
BENZENE (CAS 71-43-2)	Ceiling	25 ppm	
	TWA	10 ppm	
US. OSHA Table Z-3 (29 CFR 191	0.1000)		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Value	s		
Components	Туре	Value	Form
1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)	TWA	25 ppm	
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.

Material name: BH5330 SDS US

e fraction.
e dust.
e

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
BENZENE (CAS 71-43-2)	25 μg/g	S-Phenylmerca pturic acid	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

BENZENE (CAS 71-43-2)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

BENZENE (CAS 71-43-2)

Can be absorbed through the skin.

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other It is a good industrial hygiene practice to minimize skin contact. Wear appropriate clothing to

prevent any possibility of liquid contact and repeated or prolonged vapor contact.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Not available.

General hygiene considerations

When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Handle in accordance with good

4 / 10

industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance

boiling range

Physical state Liquid.
Form Liquid.
Color Not available.
Odor Not available.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.
Initial boiling point and 212 °F (100 °C)

Material name: BH5330 SDS US

Flash point 100.0 - 140.0 °F (37.8 - 60.0 °C) Cleveland Open Cup

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit upper (%)

Explosive limit - lower

(%)

Not available.

Not available.

Not available.

Explosive limit - upper

(%)

Not available.

Not available. Vapor pressure Vapor density Not available. Not available. Relative density

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** (n-octanol/water)

Not available.

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Not available. **Viscosity**

Other information

Specific gravity 1.08 - 1.20 VOC < 250 g/l

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Stable at normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. **Incompatible materials** Strong oxidizing agents.

Hazardous decomposition

products

Irritants. Carbon oxides. Sulphur oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

Acute toxicity Not classified.

Material name: BH5330 SDS US

Test Results Components **Species**

1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)

Acute

Dermal

LD50 Rabbit > 3160 mg/kg

Oral

LD50 Rat 6 g/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Not a skin sensitizer. Skin sensitization Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

BENZENE (CAS 71-43-2) 1 Carcinogenic to humans. QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

BENZENE (CAS 71-43-2) Cancer QUARTZ (CAS 14808-60-7) **US. National Toxicology Program (NTP) Report on Carcinogens**

BENZENE (CAS 71-43-2) Known To Be Human Carcinogen. QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Not classified. Reproductive toxicity

Specific target organ toxicity Central nervous system. May cause drowsiness and dizziness.

- single exposure

May cause damage to organs through prolonged or repeated exposure by inhalation.

Specific target organ toxicity - repeated exposure

Aspiration hazard Not classified.

Chronic effects Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

	Species	Test Results
EC50	Daphnia	4980.9971 mg/l, 48 hours estimated
LC50	Fish	373.2411 mg/l, 96 hours estimated
	Species	Test Results
(CAS 95-63-6)		
LC50	Fathead minnow (Pimephales promelas)	7.19 - 8.28 mg/l, 96 hours
EC50	Water flea (Daphnia magna)	8.76 - 15.6 mg/l, 48 hours
LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	7.2 - 11.7 mg/l, 96 hours
	LC50 (CAS 95-63-6) LC50 EC50	LC50 Fish Species (CAS 95-63-6) LC50 Fathead minnow (Pimephales promelas) EC50 Water flea (Daphnia magna) LC50 Rainbow trout,donaldson trout

^{*} Estimates for product may be based on additional component data not shown.

Material name: BH5330 SDS US 6 / 10

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability Not available.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

BENZENE 2.13

Mobility in soilNot available.Other adverse effectsNot available.

13. Disposal considerations

Disposal instructionsDispose of contents/container in accordance with local/regional/national/international regulations.

If discarded, this product is considered a RCRA ignitable waste, D001.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Waste from residues /

unused products

Dispose of in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number UN1999 **UN proper shipping name** Tars, liquid

Transport hazard class(es)

Class Combustible Liquid

Subsidiary risk Label(s) 3
Packing group III
Environmental hazards

Marine mellutant

Marine pollutant No

Special precautions for If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous

user material.

Special provisions B1, B13, IB3, T1, TP3

Packaging exceptions 150
Packaging non bulk 203
Packaging bulk 242

IATA

UN number UN1999 UN proper shipping name Tars, liquid

Transport hazard class(es)
Class 3
Subsidiary risk Packing group III
Environmental hazards No.
ERG Code 3L

Special precautions for

user

Not available.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1999 **UN proper shipping name** Tars, liquid

Transport hazard class(es)
Class 3
Subsidiary risk Packing group III

Environmental hazards

Marine pollutant No.

EmS F-E, S-E

Special precautions for Not available.

user

Material name: BH5330 SDS US

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

IATA; IMDG



Further information

If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous material. If shipped by vessel in individual containers that are less than 7.9 gallons (30 L) each, then IMDG 2.3.2.5 exception applies: Not regulated as a hazardous material.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BENZENE (CAS 71-43-2)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

BENZENE (CAS 71-43-2) Cancer QUARTZ (CAS 14808-60-7) Cancer

BENZENE (CAS 71-43-2) Central nervous system

QUARTZ (CAS 14808-60-7) lung effects BENZENE (CAS 71-43-2) Blood

QUARTZ (CAS 14808-60-7) immune system effects

BENZENE (CAS 71-43-2) Aspiration
QUARTZ (CAS 14808-60-7) kidney effects

BENZENE (CAS 71-43-2) Skin Eye

respiratory tract irritation

Flammability

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Yes

Hazardous chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

categories Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

Germ cell mutagenicity Carcinogenicity Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2,4-TRIMETHYLBENZENE	95-63-6	0 - 5

Material name: BH5330 SDS US

SARA 313 (TRI reporting)

Chemical nameCAS number% by wt.BENZENE71-43-2<1</td>

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE (CAS 71-43-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65

California Proposition 65 - CRT: Listed date/Carcinogenic substance

BENZENE (CAS 71-43-2) Listed: February 27, 1987 QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

California Proposition 65 - CRT: Listed date/Developmental toxin

BENZENE (CAS 71-43-2) Listed: December 26, 1997

California Proposition 65 - CRT: Listed date/Male reproductive toxin

BENZENE (CAS 71-43-2) Listed: December 26, 1997

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)

ASPHALT (CAS 8052-42-4) BENZENE (CAS 71-43-2)

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS 64742-48-9)

QUARTZ (CAS 14808-60-7)

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. (CAS 64742-95-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 12-17-2014

 Revision date
 01-27-2020

Version # 07

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Health: 2 Flammability: 2 Instability: 0

Material name: BH5330 SDS US

ACGIH References

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names

Hazard(s) identification: Prevention Hazard(s) identification: Hazard statement

Composition / Information on Ingredients: Disclosure Overrides

Physical & Chemical Properties: Multiple Properties

Regulatory Information: United States

GHS: Classification

Material name: BH5330 SDS US 10 / 10