# SAFETY DATA SHEET



# 1. Identification

**BLACKHAWK™ 5300 ROOFING ADHESIVE Product identifier** 

Other means of identification None

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

**Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

**Address** 2829 Lakeland Drive Jackson, MS 39232

**USA** 

After hours telephone

number

1-800-222-7122

**Normal work hours** 

telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

**Emergency 24-hour** telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Specific target organ toxicity, single exposure Category 3 narcotic effects

Information on operation

hours

8:00 a.m. to 5:00 p.m.

# 2. Hazard(s) identification

**Physical hazards** Flammable liquids Category 3 **Health hazards** Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Germ cell mutagenicity Category 1

Carcinogenicity Category 1

**Environmental hazards** Not classified. **OSHA** defined hazards Not classified.

**Label elements** 



Signal word

**Hazard statement** Flammable liquid and vapor. Causes eye irritation. Causes skin irritation. May cause genetic

defects. May cause cancer. May cause drowsiness or dizziness.

**Precautionary statement Prevention** 

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Wear protective gloves/eye protection/face protection. Ground/bond container and receiving equipment. Wash thoroughly after handling. Avoid breathing mist/vapors/spray. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Material name: BLACKHAWK™ 5300 ROOFING ADHESIVE SDS US 5033 Version #: 02 Revision date: 11-23-2021 Issue date: 11-23-2020 1/9 **Response** Specific treatment see Section 4 of this SDS. In case of fire: Use appropriate media for extinction.

IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. If skin irritation occurs, seek medical advice/attention. Take off contaminated clothing and wash before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

**Storage** Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

See section 13 of this SDS for disposal instructions.

Hazard(s) not otherwise classified (HNOC)

None known.

water/shower.

Supplemental information

None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	30 - 50
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY		64742-48-9	20 - 40
BENZENE		71-43-2	< 1
QUARTZ		14808-60-7	< 1
Other components below reporta	ble levels		34.3

## 4. First-aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing

difficulties, oxygen may be necessary. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if

needed.

**Skin contact** For hot product, immediately immerse in or flush the affected area with large amounts of cold

water to dissipate heat. For minor skin contact, avoid spreading material on unaffected skin. Wash

off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO

NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and

persists.

Not available.

**Ingestion** Rinse mouth thoroughly. Call a POISON CENTER or doctor/physician. Do not induce vomiting

without advice from poison control center. If vomiting occurs, keep head low so that stomach

content doesn't get into the lungs.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation.

Symptoms may be delayed.

**General information** IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give

oxygen. Keep victim warm. Keep victim under observation. Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media

Foam. Carbon dioxide (CO2). Water fog. Dry chemical powder.

Unsuitable extinguishing media

Do not use water jet.

Specific hazards arising from

the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Material name: BLACKHAWK™ 5300 ROOFING ADHESIVE

5033 Version #: 02 Revision date: 11-23-2021 Issue date: 11-23-2020 2 /

Special protective equipment and precautions for firefighters

equipment/instructions

Fire fighting

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Do not get water inside container. Some of these materials, if spilled, may evaporate leaving a flammable residue.

**Specific methods** 

In the event of fire and/or explosion do not breathe fumes.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Never return spills in original containers for re-use.

**Environmental precautions** 

Prevent further leakage or spillage if safe to do so. Do not contaminate water. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

# 7. Handling and storage

**Precautions for safe handling** 

Avoid heat, sparks, open flames and other ignition sources. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Do not use in areas without adequate ventilation. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container closed. Keep container dry. Keep away from food, drink and animal feedingstuffs. Keep out of reach of children. Use care in handling/storage.

# 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Specifically Regulated Components	Туре	Value	
BENZENE (CAS 71-43-2)	STEL	5 ppm	
	TWA	1 ppm	
US. OSHA Table Z-1 Limits for Ai Components	r Contaminants (29 CFR 191 Type	0.1000) Value	Form
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-2 (29 CFR 191 Components	0.1000) Type	Value	
BENZENE (CAS 71-43-2)	Ceiling	25 ppm	
	TWA	10 ppm	
US. OSHA Table Z-3 (29 CFR 191 Components	0.1000) Type	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Value Components	es Type	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.
BENZENE (CAS 71-43-2)	STEL	2.5 ppm	
	TWA	0.5 ppm	
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

Material name: BLACKHAWK™ 5300 ROOFING ADHESIVE

SDS US

US. NIOSH: Pocket Guide to Chemical Hazards				
Components	Туре	Value	Form	
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.	
BENZENE (CAS 71-43-2)	STEL	1 ppm		
	TWA	0.1 ppm		
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.	

## **Biological limit values**

**ACGIH Biological Exposure Indices** 

Components	Value	Determinant	Specimen	Sampling Time
BENZENE (CAS 71-43-2)	25 μg/g	S-Phenylmerca pturic acid	Creatinine in urine	*

<sup>\* -</sup> For sampling details, please see the source document.

## **Exposure guidelines**

**US - California OELs: Skin designation** 

BENZENE (CAS 71-43-2) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation** 

BENZENE (CAS 71-43-2) Can be absorbed through the skin.

Appropriate engineering Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. controls

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection

**Hand protection** Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other It is a good industrial hygiene practice to minimize skin contact. Wear appropriate clothing to

prevent any possibility of liquid contact and repeated or prolonged vapor contact.

**Respiratory protection** When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Not available.

General hygiene When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Wash considerations hands before breaks and immediately after handling the product. Handle in accordance with good

industrial hygiene and safety practice.

## 9. Physical and chemical properties

**Appearance** 

**Physical state** Liquid. **Form** Liquid. Color Not available. Odor Not available. **Odor threshold** Not available. Not available. Melting point/freezing point Not available. Initial boiling point and 212 °F (100 °C)

boiling range

Flash point 100.0 - 120.0 °F (37.8 - 48.9 °C) Cleveland Open Cup

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower Not available.

(%)

Flammability limit -

Not available.

upper (%)

**Explosive limit - lower** 

Not available.

(%)

**Explosive limit - upper** 

(%)

Not available.

Not available. Vapor pressure Vapor density > 1 estimated Relative density Not available.

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

**Auto-ignition temperature** Not available. **Decomposition temperature** Not available. Not available. **Viscosity** 

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

**Chemical stability** Stable at normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

**Conditions to avoid** Heat, flames and sparks. **Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition** 

products

Irritants. Carbon oxides. Sulphur oxides.

# 11. Toxicological information

## Information on likely routes of exposure

Inhalation Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea

Skin contact Causes skin irritation. Causes eye irritation. **Eye contact** 

**Ingestion** May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Not available.

## Information on toxicological effects

Not classified. **Acute toxicity** 

Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye Causes eye irritation.

irritation

## Respiratory or skin sensitization

Respiratory sensitization Not available. Skin sensitization Not a skin sensitizer. Germ cell mutagenicity May cause genetic defects.

Carcinogenicity This product contains crystalline silica. Silica is a known carcinogen; however in this encapsulated

form the normal routes of exposure are unavailable.

## IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

BENZENE (CAS 71-43-2) 1 Carcinogenic to humans. QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

**BENZENE (CAS 71-43-2)** Cancer QUARTZ (CAS 14808-60-7) Cancer

## **US. National Toxicology Program (NTP) Report on Carcinogens**

BENZENE (CAS 71-43-2) Known To Be Human Carcinogen. QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

**Reproductive toxicity** Not classified.

**Specific target organ toxicity** 

- single exposure

Central nervous system.

Specific target organ toxicity

- repeated exposure

May cause damage to organs through prolonged or repeated exposure by inhalation.

**Aspiration hazard** Not classified.

**Chronic effects** Prolonged exposure may cause chronic effects.

# 12. Ecological information

**Ecotoxicity** Components of this product are hazardous to aquatic life. Accumulation in aquatic organisms is

expected. Not expected to be harmful to aquatic organisms.

Product		Species	Test Results
BLACKHAWK™ 5300 I	ROOFING ADHESIV	Ε	
Aquatic			
Crustacea	EC50	Daphnia	10888.3594 mg/l, 48 hours estimated
Fish	LC50	Fish	45166.0742 mg/l, 96 hours estimated
Components		Species	Test Results
BENZENE (CAS 71-43	-2)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	8.76 - 15.6 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	7.2 - 11.7 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Persistence and degradability** Not available. **Bioaccumulative potential** Not available.

Partition coefficient n-octanol / water (log Kow)

BENZENE 2.13

Mobility in soilNot available.Other adverse effectsNot available.

## 13. Disposal considerations

**Disposal instructions**Contract with a disposal operator licensed by the Law on Disposal and Cleaning. Dispose of this

material and its container to hazardous or special waste collection point. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose in accordance with all applicable

regulations.

**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F

Waste from residues / unused products

Dispose of in accordance with local regulations.

**Contaminated packaging** Offer rinsed packaging material to local recycling facilities.

## 14. Transport information

DOT

**UN number** UN1999 **UN proper shipping name** Tars, liquid

Transport hazard class(es)

Class Combustible Liquid

Subsidiary risk Label(s) 3
Packing group III
Environmental hazards

invironmental nazarus

Marine pollutant No

Material name: BLACKHAWK™ 5300 ROOFING ADHESIVE

**Special precautions for** If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous

**user** material.

Special provisions B1, B13, IB3, T1, TP3

Packaging exceptions150Packaging non bulk203Packaging bulk242

**IATA** 

UN number UN1993

**UN proper shipping name** Flammable liquid, n.o.s. (ASPHALT)

Transport hazard class(es)

Class 3
Subsidiary risk Packing group III
Environmental hazards Yes
ERG Code 3L

**Special precautions for** Not available.

user

Other information

**Passenger and cargo** Allowed with restrictions.

aircraft

**Cargo aircraft only** Allowed with restrictions.

**IMDG** 

**UN number** UN1993

UN proper shipping name FLAMMABLE LIQUID, N.O.S. (ASPHALT), MARINE POLLUTANT

Transport hazard class(es)

Class 3 Subsidiary risk -Packing group III

**Environmental hazards** 

user

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

IATA; IMDG



## **Marine pollutant**



**Further information** If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous material.

# 15. Regulatory information

**US federal regulations** 

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

## TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

## **CERCLA Hazardous Substance List (40 CFR 302.4)**

ASPHALT (CAS 8052-42-4) Listed. BENZENE (CAS 71-43-2) Listed.

## SARA 304 Emergency release notification

Not regulated.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

BENZENE (CAS 71-43-2) Cancer QUARTZ (CAS 14808-60-7) Cancer

BENZENE (CAS 71-43-2) Central nervous system

QUARTZ (CAS 14808-60-7) lung effects BENZENE (CAS 71-43-2) Blood

QUARTZ (CAS 14808-60-7) immune system effects

BENZENE (CAS 71-43-2) Aspiration
QUARTZ (CAS 14808-60-7) kidney effects

BENZENE (CAS 71-43-2) Skin Eye

respiratory tract irritation

Flammability

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312** Yes

**Hazardous chemical** 

**Classified hazard** Flammable (gases, aerosols, liquids, or solids)

**categories** Skin corrosion or irritation

Serious eye damage or eye irritation

Germ cell mutagenicity

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

#### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
BENZENE	71-43-2	< 1	

## Other federal regulations

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE (CAS 71-43-2)

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

**US state regulations** WARNING: This product contains a chemical known to the State of California to cause cancer.

## **California Proposition 65**

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

BENZENE (CAS 71-43-2) Listed: February 27, 1987 QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

## California Proposition 65 - CRT: Listed date/Developmental toxin

BENZENE (CAS 71-43-2) Listed: December 26, 1997

## California Proposition 65 - CRT: Listed date/Male reproductive toxin

BENZENE (CAS 71-43-2) Listed: December 26, 1997

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

BENZENE (CAS 71-43-2)

**Inventory name** 

## **International Inventories**

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

 Issue date
 11-23-2020

 Revision date
 11-23-2021

Version # 02

**Further information** HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Health: 2 Flammability: 3

Flammability: 3 Instability: 0

**References** ACGIH

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

**Revision information** Physical & Chemical Properties: Multiple Properties

Material name: BLACKHAWK™ 5300 ROOFING ADHESIVE

5033 Version #: 02 Revision date: 11-23-2021 Issue date: 11-23-2020 9 / 9

On inventory (yes/no)\*