SAFETY DATA SHEET



1. Identification

Product identifier BLACKHAWK™ 5350 ROOFING ADHESIVE

Other means of identification None.

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

1-800-222-7122

Normal work hours

telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3 **Health hazards** Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Germ cell mutagenicity Category 1

Carcinogenicity Category 1 Reproductive toxicity Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Category 1

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

exposure

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause respiratory irritation. May cause drowsiness or dizziness. Causes serious eye irritation.

Causes skin irritation. Causes damage to organs through prolonged or repeated exposure. May cause cancer. Suspected of damaging fertility or the unborn child. Flammable liquid and vapor.

May cause genetic defects.

Precautionary statement

Prevention Use only non-sparking tools. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed. Ground/bond container and receiving equipment. Use

explosion-proof electrical/ventilating/lighting equipment. Use only outdoors or in a well-ventilated area. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eve protection/face protection. Wash thoroughly after handling. Obtain special

instructions before use. Do not handle until all safety precautions have been read and understood.

Do not eat, drink or smoke when using this product. Avoid breathing

dust/fume/gas/mist/vapors/spray.

Specific treatment see Section 4 of this SDS. If skin irritation occurs: Get medical advice/attention. Response

Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical

advice/attention. Call a poison center/doctor if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of fire: Use appropriate media for extinction. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF ON SKIN: Wash with plenty of soap and water.

Storage Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

See section 13 of this SDS for disposal instructions.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Eye contact

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	50 - 70
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.		64742-95-6	10 - 20
1,2,4-TRIMETHYLBENZENE		95-63-6	5 - 15
QUARTZ		14808-60-7	< 1
Other components below reportable I	evels		0 - 40

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing

difficulties, oxygen may be necessary. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if

needed.

For hot product, immediately immerse in or flush the affected area with large amounts of cold Skin contact

water to dissipate heat. For minor skin contact, avoid spreading material on unaffected skin. Wash

off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and

Ingestion Rinse mouth thoroughly. Call a POISON CENTER or doctor/physician. Do not induce vomiting

without advice from poison control center. If vomiting occurs, keep head low so that stomach

content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Not available.

Indication of immediate medical attention and special treatment needed

In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

Material name: BLACKHAWK™ 5350 ROOFING ADHESIVE

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Foam. Carbon dioxide (CO2). Water fog. Dry chemical powder.

Do not use water jet.

Specific hazards arising from

the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Do not get water inside container. Some of these materials, if spilled, may evaporate leaving a flammable

Specific methods

In the event of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

7. Handling and storage

Precautions for safe handling

Avoid heat, sparks, open flames and other ignition sources. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Do not use in areas without adequate ventilation. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container closed. Keep container dry. Keep away from food, drink and animal feedingstuffs. Keep out of reach of children. Use care in handling/storage.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Value Form				
dust.				
ume.				
fraction.				

Material name: BLACKHAWK™ 5350 ROOFING ADHESIVE 5554 Version #: 01 Issue date: 12-02-2021

US. NIOSH: Pocket Guide to Chemical Hazards				
Components	Туре	Value	Form	
1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)	TWA	125 mg/m3		
		25 ppm		
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.	
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.	

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear quuntlet style

gloves.

Other It is a good industrial hygiene practice to minimize skin contact. Wear appropriate clothing to

prevent any possibility of liquid contact and repeated or prolonged vapor contact.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Not available.

General hygiene considerations

When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Handle in accordance with good

industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance

Physical state
Form
Color
Not available.

Odor threshold
PH
Not available.

Not available.

Not available.

Not available.

Not available.

Not available.

Initial boiling point and

boiling range

212 °F (100 °C)

Flash point 100.0 - 120.0 °F (37.8 - 48.9 °C) Cleveland Open Cup

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits
Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

-

Explosive limit - lower

•

Not available.

Explosive limit - upper

(%)

(%)

Not available.

Vapor pressureNot available.Vapor density> 1 estimatedRelative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Not available. **Decomposition temperature**

Not available. Not available.

Viscosity Other information

> Specific gravity 1.08 - 1.2VOC < 250 g/l

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Stable at normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. **Incompatible materials** Strong oxidizing agents.

Hazardous decomposition

products

Irritants. Carbon oxides. Sulphur oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Causes skin irritation.

Eve contact Causes serious eve irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

Acute toxicity Not classified.

Components **Species Test Results**

1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)

Acute Dermal

LD50 Rabbit > 3160 mg/kg

Oral

LD50 Rat 6 g/kg

Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization Not a skin sensitizer. Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans. QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cancer

Material name: BLACKHAWK™ 5350 ROOFING ADHESIVE 5554 Version #: 01 Issue date: 12-02-2021

^{*} Estimates for product may be based on additional component data not shown.

US. National Toxicology Program (NTP) Report on Carcinogens

QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity

- single exposure

Central nervous system. May cause respiratory irritation. May cause drowsiness and dizziness.

Specific target organ toxicity

Causes damage to organs through prolonged or repeated exposure.

- repeated exposure

Aspiration hazard Not classified.

Chronic effects Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

2014.6666 mg/l, 48 hours estimated
91.4859 mg/l, 96 hours estimated
Test Results
_

Aquatic

LC50 Fathead minnow (Pimephales promelas) 7.19 - 8.28 mg/l, 96 hours Fish

Persistence and degradability Not available. **Bioaccumulative potential** Not available. Mobility in soil Not available. Not available. Other adverse effects

13. Disposal considerations

Disposal instructions Dispose of contents/container in accordance with local/regional/national/international regulations.

If discarded, this product is considered a RCRA ignitable waste, D001.

If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Waste from residues /

unused products

Dispose of in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number UN1999

UN proper shipping name Tars, liquid including road oils and cut back bitumens

Transport hazard class(es) 3 Class

Subsidiary risk Label(s) 3 **Packing group** III

Special precautions for

material.

Special provisions B1, B13, IB3, T1, TP3

Packaging exceptions 150 Packaging non bulk 203 242 **Packaging bulk**

IATA

UN number

UN1999

UN proper shipping name Tars, liquid including road asphalt and oils, bitumen and cut backs

Transport hazard class(es)

Class 3

^{*} Estimates for product may be based on additional component data not shown.

Subsidiary risk Packing group III**Environmental hazards** No. **ERG Code** 3L

Special precautions for

user

Not available.

Other information Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN number UN1999

UN proper shipping name Transport hazard class(es)

TARS, LIQUID including road oils, and cutback bitumens

Class 3 **Subsidiary risk Packing group** III**Environmental hazards**

Marine pollutant No. **EmS** F-E, S-E Special precautions for Not available.

Transport in bulk according to Not available. Annex II of MARPOL 73/78

and the IBC Code

DOT



IATA; IMDG



Further information

If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous material. If shipped by vessel in individual containers that are less than 7.9 gallons (30 L) each, then IMDG 2.3.2.5 exception applies: Not regulated as a hazardous material.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ASPHALT (CAS 8052-42-4) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7)

Cancer lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Yes

Hazardous chemical

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation

Serious eye damage or eye irritation

Germ cell mutagenicity Carcinogenicity Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1.2.4-TRIMETHYLBENZENE	95-63-6	5 - 15

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65

California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990 QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)

ASPHALT (CAS 8052-42-4) QUARTZ (CAS 14808-60-7)

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. (CAS 64742-95-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Material name: BLACKHAWK™ 5350 ROOFING ADHESIVE

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 12-02-2021

Version # 01

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Health: 2

Flammability: 2 Instability: 0

References ACGIH

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

DisclaimerThe information in the sheet was written based on the best knowledge and experience currently

available. The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any

other materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names

Hazard(s) identification: Response

Composition / Information on Ingredients: Disclosure Overrides

Physical & Chemical Properties: Multiple Properties

Transport Information: Proper Shipping Name/Packing Group

GHS: Classification

Material name: BLACKHAWK™ 5350 ROOFING ADHESIVE 5554 Version #: 01 Issue date: 12-02-2021