SAFETY DATA SHEET



1. Identification

Product identifier NOVOCOAT™ DTM EPOXY PART B

Other means of identification None.

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive

Jackson, MS 39232

USA

After hours telephone

number

Normal work hours

telephone number

1-877-982-7667

1-800-222-7122

Website www.ergonarmor.com E-mail sds@ergon.com

Emergency 24-hour

telephone number Information on operation hours

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Category 1 Skin corrosion/irritation

> Category 1 Serious eye damage/eye irritation Sensitization, skin Category 1

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious

eye damage.

Precautionary statement

Prevention Avoid breathing dust/fume/gas/mist/vapors. Wash thoroughly after handling. Contaminated

work clothing must not be allowed out of the workplace. Wear protective gloves/protective

clothing/eye protection/face protection.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Specific treatment see Section 4 of Response

this SDS. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international

regulations.

Version #: 04 Revision date: 05-20-2025 Issue date: 06-12-2020

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
BENZYL ALCOHOL		100-51-6	35 - 45
3-AMINOMETHYL-3,5,5-TRIMETHY LCYCLOHEXYLAMINE	,	2855-13-2	15 - 35
1,3-BENZENEDIMETHANAMINE		1477-55-0	1 - 10
3-AMINOPROPYLTRIETHOXYSILAN E	I	919-30-2	1 - 10
TRIMETHYLHEXAMETHYLENE DIAMINE		25620-58-0	1 - 10

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the

substance. Get medical attention immediately.

Immediately flush skin with plenty of water. Remove and isolate contaminated clothing and Skin contact

shoes. Chemical burns must be treated by a physician. Wash contaminated clothing before

reuse. Wash clothing separately before reuse. Get medical attention immediately.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention immediately.

Rinse mouth thoroughly. Do not induce vomiting. If vomiting occurs, keep head low so that **Ingestion**

stomach content doesn't get into the lungs. Never give anything by mouth to a victim who is

unconscious or is having convulsions. Get medical attention immediately.

Most important symptoms/effects, acute

and delayed

Indication of immediate medical attention and special treatment needed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Fire may produce irritating, corrosive and/or toxic gases.

Special protective equipment

and precautions for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure

demand breathing apparatus, protective clothing and face mask.

Fire fighting

equipment/instructions

In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers. Cool containers exposed to flames with water until well after the fire is out. Water runoff can

cause environmental damage.

Specific methods Move containers from fire area if you can do so without risk.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: NOVOCOAT™ DTM EPOXY PART B 4858 Version #: 04 Revision date: 05-20-2025 Issue date: 06-12-2020 Methods and materials for containment and cleaning up

Extinguish all flames in the vicinity. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not taste or swallow. When using do not eat or drink. Do not get this material in contact with eyes. Do not get this material in contact with skin. Do not get this material on clothing. Avoid prolonged exposure. Use personal protective equipment as required. Observe good industrial hygiene practices. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from food, drink and animal feedingstuffs.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values (TLV)

ComponentsTypeValue1,3-BENZENEDIMETHANAMCeiling0.018 ppmINE (CAS 1477-55-0)

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)
Components Type Value

1,3-BENZENEDIMETHANAM Ceiling 0.1 mg/m3
INE (CAS 1477-55-0)

US. OARS. Workplace Environmental Exposure Level (WEEL) Guide

ComponentsTypeValueBENZYL ALCOHOL (CASTWA44.2 mg/m3100-51-6)10 ppm

10 ρρι

No biological exposure limits noted for the ingredient(s).

Biological limit values Exposure guidelines

US - California OELs: Skin designation

1,3-BENZENEDIMETHANAMINE (CAS 1477-55-0) Can be absorbed through the skin.

US - Tennessee OELs: Skin designation

1,3-BENZENEDIMETHANAMINE (CAS 1477-55-0) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

1,3-BENZENEDIMETHANAMINE (CAS 1477-55-0) Danger of cutaneous absorption

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

1,3-BENZENEDIMETHANAMINE (CAS 1477-55-0) Can be absorbed through the skin.

Appropriate engineering Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

controls occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical goggles are recommended. Use face shield in case of splash risk.

Skin protection

Hand protection Wear protective gloves. Nitrile, butyl rubber or neoprene gloves are recommended.

Other Wear appropriate chemical resistant clothing.

Material name: NOVOCOAT™ DTM EPOXY PART B
4858 Version #: 04 Revision date: 05-20-2025 Issue date: 06-12-2020

Respiratory protection Do not breathe dust/fume/gas/mist/vapors/spray. When workers are facing concentrations

above the exposure limit they must use appropriate certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Do not get in eyes, on skin, on clothing. Contaminated

work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid. Color Not available.

Odor Not available. **Odor threshold** Not available. Not available. nН Melting point/freezing point Not available.

Initial boiling point and

boiling range

212 °F (100 °C) estimated

>200.0 °F (>93.3 °C) Flash point

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure Not available. Vapor density Not available. Relative density Not available.

Solubility(ies)

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature 816.8 °F (436 °C) estimated

Decomposition temperature Not available. Viscosity Not available.

Other information

Density 8.53 lb/gal estimated Specific gravity 1.0242 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Stable under normal temperature conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point.

Incompatible materials Peroxides. Phenols.

Hazardous decomposition

products

Irritating and/or toxic fumes and gases may be emitted upon the products decomposition.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Material name: NOVOCOAT™ DTM EPOXY PART B 4858 Version #: 04 Revision date: 05-20-2025 Issue date: 06-12-2020 **Skin contact** Causes severe skin burns and eye damage. May cause an allergic skin reaction.

Eye contact Causes serious eye damage.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Irritation of eyes and mucous membranes. May cause mild irritation including stinging, watering,

and redness. Repeated exposure may cause skin dryness and cracking. Rash. Dermatitis.

Information on toxicological effects

Acute toxicity

Product Species Test Results

NOVOCOAT™ DTM EPOXY PART B

<u>Acute</u> Dermal

LD50 Rabbit 5149 mg/kg

Components Species Test Results

3-AMINOPROPYLTRIETHOXYSILANE (CAS 919-30-2)

Acute Oral

Point estimate* 500 mg/kg bw

BENZYL ALCOHOL (CAS 100-51-6)

<u>Acute</u> Dermal

LD50 Rabbit 2000 mg/kg

Inhalation

LC50 Rat > 4.178 mg/l, 4 Hours

Oral

LD50 Rat 1230 - 3100 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes severe eye burns.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization Corrosive to skin and eyes.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity

gan toxicity Not classified.

single exposure

Specific target organ toxicity

Not classified.

- repeated exposure

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

Material name: NOVOCOAT™ DTM EPOXY PART B

SDS US

5 / 9

^{*} Point estimate = Converted acute toxicity point estimate

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the

environment.

Product Species Test Results

NOVOCOAT™ DTM EPOXY PART B

Aquatic

Crustacea EC50 Daphnia 57.2773 mg/l, 48 hours 416.2358 mg/l, 96 hours Fish LC50 Fish

Components **Species Test Results**

BENZYL ALCOHOL (CAS 100-51-6)

Aquatic

Acute

Fish LC50 Bluegill (Lepomis macrochirus) 10 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

1.1 BENZYL ALCOHOL

Mobility in soil Not available. Other adverse effects Not available.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the

waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions). Avoid discharge into water courses or onto the ground.

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container

is emptied.

14. Transport information

DOT

UN2735 **UN number**

UN proper shipping name Amines, liquid, corrosive, n.o.s, or Polyamines, liquid, corrosive, n.o.s.

(1,3-BENZENEDIMETHANAMINE)

Transport hazard class(es)

Class 8 **Subsidiary hazard** 8 Label(s) **Packing group** TTT

Environmental hazards

Marine pollutant No. Not assigned.

Special precautions for

user

IB3, T7, TP1, TP28 Special provisions

Packaging exceptions 154 203 Packaging non bulk Packaging bulk 241

IATA

UN number UN2735

UN proper shipping name Amines, liquid, corrosive, n.o.s. (1,3-BENZENEDIMETHANAMINE)

Transport hazard class(es) Class 8

Subsidiary hazard

^{*} Estimates for product may be based on additional component data not shown.

Packing group III Environmental hazards YES ERG Code 8L

Special precautions for

user

Other information

Passenger and cargo Allowed with restrictions.

Not assigned.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN2735

UN proper shipping name AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(1,3-BENZENEDIMETHANAMINE), MARINE POLLUTANT

Transport hazard class(es)

Class 8
Subsidiary hazard Packing group III
Environmental hazards

Marine pollutantYESEmSF-A, S-BSpecial precautions forNot assigned.

user

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

DOT



IATA; IMDG



Marine pollutant



Material name: NOVOCOAT™ DTM EPOXY PART B

4858 Version #: 04 Revision date: 05-20-2025 Issue date: 06-12-2020

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Yes

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312

Hazardous chemical

Classified hazard Skin corrosion or irritation

categories Serious eye damage or eye irritation

Respiratory or skin sensitization

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Clean Water Act (CWA)

Section 112(r) (40 CFR

68.130)

Safe Drinking Water Act

(SDWA)

Not regulated.

Hazardous substance

US state regulationsCalifornia Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This

material is not known to contain any chemicals currently listed as carcinogens or reproductive

toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Material name: NOVOCOAT™ DTM EPOXY PART B

SDS US

8/9

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the

16. Other information, including date of preparation or last revision

06-12-2020 **Issue date** 05-20-2025 **Revision date**

Version # 04

governing country(s).

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings

Flammability: 1 Instability: 0

The information provided in this Safety Data Sheet is correct to the best of our knowledge, **Disclaimer**

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any

other materials or in any process, unless specified in the text.

SDS US

4858 Version #: 04 Revision date: 05-20-2025 Issue date: 06-12-2020

Yes