SAFETY DATA SHEET



1. Identification

Product identifier NOVOCOAT™ SC3300 NOVOLAC EPOXY LINING PART A

Other means of identification None. Recommended use Lining **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

1-800-222-7122

Normal work hours

telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

> Serious eye damage/eye irritation Category 2B Sensitization, skin Category 1B Carcinogenicity Category 2

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Suspected of causing cancer by ingestion. Causes skin irritation. Causes serious eye irritation. May

cause an allergic skin reaction.

Precautionary statement

Prevention Wear protective gloves. Wear eye/face protection. Wash thoroughly after handling. Avoid

breathing mist or vapor. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Do not handle until all safety precautions have been read and

understood. Obtain special instructions before use.

Response Specific treatment see Section 4 of this SDS. Wash contaminated clothing before reuse. IF exposed

or concerned: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye

irritation persists: Get medical advice/attention.

Storage Store in accordance with local/regional/national regulations.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: NOVOCOAT™ SC3300 NOVOLAC EPOXY LINING PART A

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
PHENOL-FORMALDEHYDE POLYI GLYCIDYL ETHER	MER	28064-14-4	30 - 50
TALC (Mg3Si4O10(OH)2)		14807-96-6	20 - 40
QUARTZ		14808-60-7	5 - 15
TITANIUM DIOXIDE		13463-67-7	5 - 15
1,3-DIGLYCIDYLOXYBENZENE		101-90-6	1 - 10
Other components below reporta	able levels		20 - 40

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

> Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve

or other proper respiratory medical device. Get medical attention, if needed.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a POISON

CENTER or doctor/physician if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. For minor skin contact, avoid spreading

material on unaffected skin. Take off contaminated clothing and wash before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO **Eye contact**

NOT delay irrigation or attempt to remove the lens. Continue rinsing. Get medical attention

immediately.

Call a physician or poison control center immediately. Rinse mouth thoroughly. Never give anything **Ingestion**

by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device.

Most important

symptoms/effects, acute and delayed

Skin irritation. May cause an allergic skin reaction. Dermatitis. Rash. Irritant effects. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Take off contaminated clothing and shoes immediately. In case of shortness of breath, give oxygen IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Alcohol foam. Carbon dioxide (CO2).

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Special protective equipment and precautions for firefighters

Wear suitable protective equipment. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers. Cool containers exposed to flames with

water until well after the fire is out. Water runoff can cause environmental damage.

Specific methods General fire hazards In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

No unusual fire or explosion hazards noted.

Material name: NOVOCOAT™ SC3300 NOVOLAC EPOXY LINING PART A 4856 Version #: 01 Issue date: 11-01-2021

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Immediately evacuate personnel to safe areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid skin contact and inhalation of vapors during disposal of spills. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Extinguish all flames in the vicinity.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not breathe mist or vapor. Do not get this material in contact with eyes. Do not taste or swallow. Avoid contact with skin. Avoid prolonged exposure. Avoid contact with clothing. Do not use in areas without adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash thoroughly after handling. Avoid release to the environment. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

CAUTION Store locked up. Keep away from heat, sparks and open flame. Store in a closed container away from incompatible materials. Store in a well-ventilated place. Keep away from food, drink and animal feedingstuffs. Keep out of the reach of children. Store in accordance with local/regional/national/international regulation.

Value

Form

8. Exposure controls/personal protection

Occupational exposure limits

Components

US. OSHA Table Z-1 Limits fo	r Air C	ontaminant	s (29	CFR 1910.1000)
------------------------------	---------	------------	-------	----------------

Type

QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
TITANIUM DIOXIDE (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 19 :	(0.1000)		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
TALC (Mg3Si4O10(OH)2) (CAS 14807-96-6)	TWA	0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

SDS US

US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
TALC (Mg3Si4O10(OH)2) (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

(CAS 14807-96-6)

TALC (Mg3Si4O10(OH)2)

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

2 mg/m3

Respirable.

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses. If risk of splashing, wear safety goggles or face shield.

TWA

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Wear appropriate clothing to prevent any possibility of skin contact.

When workers are facing concentrations above the exposure limit they must use appropriate **Respiratory protection**

certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid.

Color Not available. Odor Not available. Not available. **Odor threshold** 7 estimated Not available. Melting point/freezing point

Initial boiling point and

boiling range

> 392 °F (> 200 °C)

> 302.0 °F (> 150.0 °C) Flash point

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -

Not available.

upper (%)

Explosive limit - lower

Not available.

(%)

Explosive limit - upper

(%)

Not available.

82.00 Pa at 20°C Vapor pressure Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient

> 3

(n-octanol/water)

Auto-ignition temperature572 °F (300 °C)Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 12.39 lb/gal estimated

Specific gravity 1.48 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Stable.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials Peroxides. Chlorine. Strong acids, alkalies and oxidizing agents.

Hazardous decomposition

products

If product is burned hazardous gases such as oxides of carbon and nitrogen and various

hydrocarbons may be produced.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contactCauses skin irritation. **Eye contact**Causes eye irritation.

Ingestion Suspected of causing cancer by ingestion. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not available.

Skin corrosion/irritation Corrosive to skin and eyes.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Possible cancer hazard based on tests with laboratory animals. This product contains crystalline

silica. Silica is a known carcinogen; however in this encapsulated form the normal routes of

exposure are unavailable.

IARC Monographs. Overall Evaluation of Carcinogenicity

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6) 2B Possibly carcinogenic to humans.

QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

TALC (Mg3Si4O10(OH)2) (CAS 14807-96-6) 2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

SDS US

TITANIUM DIOXIDE (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cancer

Material name: NOVOCOAT™ SC3300 NOVOLAC EPOXY LINING PART A

US. National Toxicology Program (NTP) Report on Carcinogens

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6)

Reasonably Anticipated to be a Human Carcinogen.

QUARTZ (CAS 14808-60-7)

Known To Be Human Carcinogen.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not classified.

Aspiration hazard

Not available.

Chronic effects

Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

The product components are not classified as environmentally hazardous. However, this does no exclude the possibility that large or frequent spills can have a harmful or damaging effect on the

environment.

Product Species Test Results NOVOCOAT™ SC3300 NOVOLAC EPOXY LINING PART A Aquatic Crustacea EC50 10810.8105 mg/l, 48 hours estimated Daphnia Fish LC50 10810.8105 mg/l, 96 hours estimated Fish Components **Test Results** Species

> 3

PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER (CAS 28064-14-4)

Aquatic

Acute

Fish LC50

Fish

1 - 10 mg/l

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

NOVOCOAT™ SC3300 NOVOLAC EPOXY LINING PART A

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Dispose in accordance with all applicable regulations. When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Material name: NOVOCOAT™ SC3300 NOVOLAC EPOXY LINING PART A

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cancer

lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312

Yes

Hazardous chemical

Classified hazard categories

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

Carcinogenicity

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,3-DIGLYCIDYLOXYBENZENE	101-90-6	1 - 10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

(SDIIA)

US state regulations

California Proposition 65



WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6) Listed: July 1, 1989
QUARTZ (CAS 14808-60-7) Listed: October 1, 1988
TITANIUM DIOXIDE (CAS 13463-67-7) Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6)

QUARTZ (CAS 14808-60-7)

TALC (Mg3Si4O10(OH)2) (CAS 14807-96-6) TITANIUM DIOXIDE (CAS 13463-67-7)

Material name: NOVOCOAT™ SC3300 NOVOLAC EPOXY LINING PART A 4856 Version #: 01 Issue date: 11-01-2021

International Inventories

New Zealand

Philippines

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes

(PICCS)

Inventory name

TaiwanTaiwan Chemical Substance Inventory (TCSI)YesUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

Philippine Inventory of Chemicals and Chemical Substances

16. Other information, including date of preparation or last revision

New Zealand Inventory

Issue date 11-01-2021

Version # 01

NFPA ratings Health: 2

Flammability: 0 Instability: 0

References EPA: AQUIRE database

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names

Hazard(s) identification: Supplemental information

GHS: Classification

Material name: NOVOCOAT™ SC3300 NOVOLAC EPOXY LINING PART A 4856 Version #: 01 Issue date: 11-01-2021

On inventory (yes/no)*

Yes

Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).