



### **Why Choose Novolite?**

- Easy to Use
- Lightweight (3.5 lbs. per gallon)
- Stronger than Concrete
- Long-Term Protection
- Excellent Chemical Resistance
- No Sagging or Slumping
- 100% Solids, VOC-Free

ErgonArmor  
P.O. Box 1639  
Jackson MS 39215-1639



# **Novolite**

PERMANENT CONCRETE REPAIR

**STRONGER THAN CONCRETE. LIGHTWEIGHT. EXCELLENT CHEMICAL RESISTANCE.**



ErgonArmor™

# Novolite

PERMANENT CONCRETE REPAIR

*Have you ever used a concrete repair product that failed after application?*

We have. And we know many others who have done the same. That's why we created Novocoat's Novolite, a three-component, easy to use compound for vertical and overhead areas. This leading edge technology was developed at ErgonArmor's world-class technical laboratory, and its simplicity significantly reduces the chance of user error.

Novolite is much stronger than concrete. When used with NovoPrime 1100, it can penetrate into the substrate and provide a remarkable level of adhesion.

Contact your Novocoat sales representative today to learn more.



## How to Apply Novolite



**1** BRUSH LOOSE MATERIALS FROM SURFACE

Note: maximum thickness is 4"



**2** APPLY THE MIXTURE USING A FLOAT OR TROWEL



**3** SMOOTH MATERIAL WITH A STEEL TROWEL OR FLOAT

## Ordering Information

For additional information, prices, or to place an order, please contact your ErgonArmor sales representative. If you do not know the name of your sales representative, call **877-98ARMOR**.

Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using. While all statements, technical information, and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. Please contact ErgonArmor for further information at **877-982-7667** or FAX **601-933-3381**. For all Terms and Conditions of Sale see [ergonarmor.com](http://ergonarmor.com).

CALL 877-98ARMOR | VISIT [ERGONARMOR.COM](http://ERGONARMOR.COM)