# **SAFETY DATA SHEET**



# 1. Identification

Product identifier	R-17-A-73 ASPHALT COATING		
Other means of identification	None.		
Recommended use	Coatings		
<b>Recommended restrictions</b>	None known.		
Manufacturer/Importer/Suppl	ier/Distributor information		
Company Name	ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.		
Address	2829 Lakeland Drive		
	Jackson, MS 39232		
	USA		
After hours telephone number	1-800-222-7122		
Normal work hours telephone number	1-877-982-7667		
Website	www.ergonarmor.com		
E-mail	sds@ergon.com		
Emergency 24-hour telephone number	CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887		
Information on operation hours	8:00 a.m. to 5:00 p.m.		

# 2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Skin corrosion/irritation	Category 2
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1B
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	

Signal word	Daligei
Hazard statement	Highly flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May cause cancer. May cause genetic defects.
Precautionary statement	
Prevention	Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Wear protective gloves/protective clothing/eye protection/face protection.
Response	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. IF ON SKIN: Gently wash with plenty of soap and water. Specific treatment see Section 4 of this SDS. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media for extinction. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell.

Storage	Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

# 3. Composition/information on ingredients

## Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT, OXIDIZED		64742-93-4	55 - 65
SOLVENT NAPHTHA (PETROLEUM) LIGHT ALIPH.	1	64742-89-8	35 - 45

## 4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention if symptoms occur.
Skin contact	Wash off with soap and plenty of water. For minor skin contact, avoid spreading material on unaffected skin. If skin irritation occurs: Get medical advice/attention.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Aspiration may cause pulmonary edema and pneumonitis. If ingestion of a large amount does occur, call a poison control center immediately.
Most important symptoms/effects, acute and delayed	Not available.
Indication of immediate medical attention and special treatment needed	In case of shortness of breath, give oxygen. Symptoms may be delayed.

# **General information** IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide (CO2). Extinguish with water fog.		
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.		
Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases.		
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.		
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue. Water runoff can cause environmental damage.		
Specific methods	In the event of fire, cool tanks with water spray. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.		
6. Accidental release measures			

# Personal precautions,<br/>protective equipment and<br/>emergency proceduresRemove sources of ignition. Keep unnecessary personnel away. Keep people away from and upwind<br/>of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate<br/>protective clothing. Do not touch or walk through spilled material.

Methods and materials for containment and cleaning up	Dike far ahead of spill for later disposal. Cover with DRY earth, DRY sand, or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain. Collect spillage. Prevent product from entering drains.	
	Never return spills in original containers for re-use.	
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water.	
7. Handling and storage		
Precautions for safe handling	DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. All equipment used when handling the product must be grounded. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Do not use in areas without adequate ventilation. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash thoroughly after handling. Do not empty into drains.	
Conditions for safe storage, including any incompatibilities	The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place. Keep container tightly closed. Use care in handling/storage.	

## 8. Exposure controls/personal protection

**Occupational exposure limits** 

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Туре Value SOLVENT NAPHTHA PEL 400 mg/m3 (PETROLEUM), LIGHT ALIPH. (CAS 64742-89-8) 100 ppm **U.S. - NIOSH** Components Туре Value ASPHALT, OXIDIZED (CAS REL 5 mg/m3 64742-93-4) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value SOLVENT NAPHTHA TWA 400 mg/m3 (PETROLEUM), LIGHT ALIPH. (CAS 64742-89-8) 100 ppm **Biological limit values** No biological exposure limits noted for the ingredient(s). Appropriate engineering Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. controls Individual protection measures, such as personal protective equipment Eye/face protection Chemical goggles are recommended. Skin protection Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style aloves. Other Wear appropriate chemical resistant clothing. Chemical resistant gloves. **Respiratory protection** When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. **Thermal hazards** Not available. **General hygiene** When using do not smoke. When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid considerations contact with skin. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

## Appearance

**Physical state** 

Solid.

Form	Liquid.
Color	Dark brown Black.
Odor	Hydrocarbon-like.
Odor threshold	Not available.
pН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	240 - 315 °F (115.56 - 157.22 °C)
Flash point	65.0 °F (18.3 °C) Tag Open Cup
Evaporation rate	0.2
Flammability (solid, gas)	Not available.
Upper/lower flammability or ex	xplosive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	21.00 mm Hg at 100F
Vapor density	> 4
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	550 °F (287.78 °C) estimated
Decomposition temperature	Not available.
Viscosity	320 cSt
Viscosity temperature	77 °F (25 °C)
Other information	
Percent volatile	51 %
Specific gravity	0.85 - 0.95
VOC	3.2 lb/gal
10 Stability and reactivit	

# 10. Stability and reactivity

Reactivity	Not available.
Chemical stability	Stable under normal temperature conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Irritants. Toxic gas.

# **11.** Toxicological information

# Information on likely routes of exposure

Inhalation	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis
Eye contact	Causes eye irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

#### Symptoms related to the Not available. physical, chemical and toxicological characteristics

toxicological characteristics			
Information on toxicological effects			
Acute toxicity	Not classified.		
Components	Species	Test Results	
SOLVENT NAPHTHA (PETROLEUM)	), LIGHT ALIPH. (CAS 64742-89	9-8)	
<u>Acute</u>			
Inhalation			
LC50	Rat	61 mg/l, 4 Hours	
* Estimates for product may b	e based on additional compone	ent data not shown.	
Skin corrosion/irritation	May cause defatting of the sl	(in, but is neither an irritant nor a sensitizer.	
Serious eye damage/eye irritation	Not classified. May be irritating to eyes.		
Respiratory or skin sensitization	on		
Respiratory sensitization	Not available.		
Skin sensitization	Irritating to skin.		
Germ cell mutagenicity	May cause genetic defects.		
Carcinogenicity	May cause cancer.		
IARC Monographs. Overall	<b>Evaluation of Carcinogenic</b>	ity	
ASPHALT, OXIDIZED (CAS 64742-93-4) 2A Probably carcinogenic to humans. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)			
Not regulated.	eu Substances (25 CFR 151	0.1001-1052)	
-	ogram (NTP) Report on Ca	rcinogens	
Not listed.	<b>.</b>		
Reproductive toxicity	Suspected of damaging fertility or the unborn child.		
Specific target organ toxicity - single exposure	Not available.		
Specific target organ toxicity - repeated exposure	Not available.		
Aspiration hazard	Not classified.		
Further information	Symptoms may be delayed.		

# **12. Ecological information**

Ecotoxicity

Components of this product are hazardous to aquatic life. Accumulation in aquatic organisms is expected. Not expected to be harmful to aquatic organisms.

Product		Species	Test Results
R-17-A-73 ASPHALT C	OATING		
Aquatic			
Crustacea	EC50	Daphnia	9.375 mg/l, 48 hours estimated
Fish	LC50	Fish	22.5 mg/l, 96 hours estimated
Components		Species	Test Results
SOLVENT NAPHTHA (	PETROLEUM), LIGH	IT ALIPH. (CAS 64742-89-8)	
· · · · · ·			
Aquatic			
•	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Aquatic	EC50 LC50	Water flea (Daphnia pulex) Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.7 - 5.1 mg/l, 48 hours 8.8 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

Mobility in soil	Not available.
Other adverse effects	Not available.

# 13. Disposal considerations

Disposal instructions	Contract with a disposal operator licensed by the Law on Disposal and Cleaning. Dispose of this material and its container to hazardous or special waste collection point. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose in accordance with all applicable regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Offer rinsed packaging material to local recycling facilities.

# 14. Transport information

	^	-
D	U	

DOT	
UN number	UN1999
UN proper shipping name	Tars, liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	
Marine pollutant	No
Special precautions for	Not available.
user	
Special provisions	B1, B13, IB3, T1, TP3
Packaging exceptions	150
Packaging non bulk	203
Packaging bulk	242
IATA	
UN number	UN1999
UN proper shipping name	Tars, liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	31
Special precautions for	Not available.
user	
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1999
UN proper shipping name	Tars, liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-A, S-G
Special precautions for	Not available.
user	
Transport in bulk according to	Not available.
Annex II of MARPOL 73/78	
and the IBC Code	
Material name: R-17-A-73 ASPHALT CC	DATING





# 15. Regulatory information

US federal	regulations
------------	-------------

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

## TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

## SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

## SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical	Yes
Classified hazard categories	Flammable (gases, aerosols, liquids, or solids) Skin corrosion or irritation Germ cell mutagenicity Carcinogenicity Specific target organ toxicity (single or repeated exposure)

# SARA 313 (TRI reporting)

Not regulated.

# Other federal regulations

 

 Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

 Not regulated.

 Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

 Not regulated.

 Safe Drinking Water Act (SDWA)
 Not regulated.

 US state regulations
 WARNING: This product contains a chemical known to the State of California to cause cancer.

 California Proposition 65
 California Proposition 65 - CRT: Listed date/Carcinogenic substance

 ASPHALT, OXIDIZED (CAS 64742-93-4)
 Listed: January 1, 1990

## US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. (CAS 64742-89-8)

### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

•	5
Issue date	12-06-2021
Version #	01
Further information	HMIS® is a registered trade and service mark of the NPCA.
NFPA ratings	Health: 2 Flammability: 3 Instability: 0
References	ACGIH EPA: AQUIRE database NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents HSDB® - Hazardous Substances Data Bank IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Product and Company Identification: Alternate Trade Names Composition / Information on Ingredients: Ingredients Transport Information: Material Transportation Information HazReg Data: North America GHS: Classification