



SELECTION & SPECIFICATION DATA

| | |
|----------------------------------|---|
| Type | Cold Adhesive |
| Description | Blackhawk 5360 is our high performance cold adhesive. It is a single component, asbestos-free, asphaltic commercial roofing adhesive used to adhere modified bitumen roofing membranes. |
| Features | <ul style="list-style-type: none"> • Single-component • Low odor • Cold-applied • Elastomeric |
| Uses | Adhesive for single- and multi-ply SBS and select APP roofing membranes. |
| Color | Black |
| Primer | Self-priming |
| Solids Content | 78% by weight |
| Theoretical Coverage Rate | 1.5 – 2 gallons per square, depending on substrate |
| VOC Value(s) | <250 g/L (2.09 lbs/gal) |
| Limitations | Not all APP membranes are alike, and adhesion to these modified membranes should be tested. Do not use with membranes containing a burn-off film. |

SUBSTRATES & SURFACE PREPARATION

| | |
|------------|--|
| All | All surfaces must be clean and free from debris and loose scale material or anything that may interfere with adhesion or act as a bond breaker with the desired substrate. |
|------------|--|

MIXING & THINNING

| | |
|-----------------|---------------------|
| Mixing | No mixing necessary |
| Thinning | Do not thin |

APPLICATION GUIDANCE

| | |
|----------------------|--|
| Airless Spray | Pump Size - 45:1 or greater Spray Hose - 200 ft x 3/4 in ID Whip - 15 ft x 1/2 in ID |
| Squeegee | 1/4 in serrated squeegee |

CLEANUP & SAFETY

| | |
|--------------------|--|
| Cleanup | Mineral spirits or similar solvent |
| Safety | Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using. |
| Ventilation | Use in well ventilated areas |

PACKAGING, HANDLING & STORAGE

| | |
|---|--|
| Shelf Life | 12 months at 75°F (24°C) When kept at recommended storage conditions and in original unopened containers. |
| Storage Temperature & Humidity | 0°F – 110°F (4°C – 43°C) 0 – 100% relative humidity |
| Package Sizes & Shipping Weights | 5 gallon pail - 50 lbs (22.6 kg) 55 gallon drum - 550 lbs (249.4 kg) 275 gallon tote - 2800 lbs (1270 kg) 350 gallon returnable tote - 3800 lbs (1724 kg) |
| Storage | Storage indoors is recommended. Always inspect the product prior to use. |

PERFORMANCE DATA

Lap shear testing after 24 hours has shown that Blackhawk 5360 meets or exceeds the performance attributes of ASTM D3019.

Rev 12/19

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see ergonarmor.com.

