

Blackhawk™ 5501 Roofing Adhesive

SELECTION & SPECIFICATION DATA

Type	Modified Bitumen Membrane Adhesive
Description	Blackhawk 5501 Roofing Adhesive is an asphaltic adhesive specially designed to adhere modified bitumen membranes. Blackhawk 5501 Roofing Adhesive is formulated to be used as a squeegee- or spray-grade modified bitumen roofing membrane adhesive.
Features	<ul style="list-style-type: none">• Cold-applied• Quick drying• Low odor• Single-component• Strong cold-weather bond• Excellent wind uplift resistance
Uses	Adhesive for single and multi-ply SBS roofing membranes.
Color	Black
Primer	Self-priming
Solids Content	80 ± 2% by weight
VOC Value(s)	<250 g/l (2.09 lb/gal)

SUBSTRATES & SURFACE PREPARATION

All	All surfaces must be clean and free from debris and loose scale material or anything that may interfere with adhesion or act as a bond breaker with the desired substrate.
------------	--

MIXING & THINNING

Mixing	No mixing required
Thinning	Do not thin
Cleanup	Mineral spirits or equivalent solvent

APPLICATION GUIDANCE

Airless Spray Single Leg	Pump size: 45:1 or greater Hose length: 200 ft x 3/4-inch ID Whip length: 15 ft x 1/2-inch ID
---------------------------------	---

Squeegee	Serrated, 1/4-inch
-----------------	--------------------

PACKAGING, ESTIMATING & HANDLING

ITEM#	PACKAGING
K-5501-005-001	Pail - 4.7 gallons
Theoretical Coverage Rate	1.5 - 2 gallons per square depending on substrate.

Storage & Shelf Life	Estimated shelf life is 12 months when stored in a dry area at 75°F (24°C). Actual shelf life may vary with storage conditions. Do not store below 40°F (4°C) or above 110°F (43°C). Store indoors. This product is not affected by excursions below published storage temperatures. Always inspect the product prior to use to make sure it is smooth and homogeneous.
---------------------------------	---

SAFETY

Safety	Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.
---------------	--

Rev. 08/2025



TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see ergonarmor.com.