# SAFETY DATA SHEET



# 1. Identification

**Product identifier** Penncoat 310 (All Colors)

Other means of identification None.

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

**Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

**Address** 2829 Lakeland Drive Jackson, MS 39232

**USA** 

After hours telephone

number

1-800-222-7122

**Normal work hours** 

telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

**Emergency 24-hour** telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

8:00 a.m. to 5:00 p.m.

hours

# 2. Hazard(s) identification

**Physical hazards** Flammable liquids Category 3 **Health hazards** Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Sensitization, respiratory Category 1 Sensitization, skin Category 1 Reproductive toxicity Category 2

> Specific target organ toxicity, repeated exposure

Category 1

Not classified.

**Environmental hazards OSHA** defined hazards Not classified.

**Label elements** 



Signal word Danger

**Hazard statement** May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties

if inhaled. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Flammable liquid and vapor. Causes skin irritation. Causes serious

eye irritation.

## **Precautionary statement**

**Prevention** 

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Keep away from heat/sparks/open flames and hot surfaces. No smoking. In case of inadequate ventilation wear

respiratory protection. Contaminated work clothing must not be allowed out of the workplace.

Response

Specific treatment see Section 4 of this SDS. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If skin irritation or rash occurs: Get medical advice/attention. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. IF exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical

advice/attention. In case of fire: Use appropriate media for extinction.

**Storage** Store in a well-ventilated place. Keep cool. Keep container tightly closed. Keep locked-up. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Disposal** Hazard(s) not otherwise classified (HNOC)

None known.

Not available.

**Supplemental information** 

None.

# 3. Composition/information on ingredients

### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
STYRENE		100-42-5	20 - 40
QUARTZ		14808-60-7	1 - 10
Other components below re	eportable levels		58.02

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

Inhalation

Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.

Skin contact

Wash off with soap and water. For minor skin contact, avoid spreading material on unaffected skin. Get medical attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

**Ingestion** 

If swallowed, do NOT induce vomiting. Give a glass of water. Never give liquid to an unconscious person. If ingestion of a large amount does occur, call a poison control center immediately. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and

delaved

**Indication of immediate** 

medical attention and special treatment needed

In case of shortness of breath, give oxygen. Oxygen, if needed. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**General information** 

Keep victim warm. Keep victim under observation. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

SDS US

# 5. Fire-fighting measures

Suitable extinguishing media

Water fog. Carbon dioxide (CO2). Foam. Dry chemical.

**Unsuitable extinguishing** media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Material name: Penncoat 310 (All Colors)

Special protective equipment and precautions for firefighters

face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. Cool containers exposed to flames with water until well after the fire is out. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Firefighters must use standard protective equipment including flame retardant coat, helmet with

**Specific methods** 

In the event of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Use water spray to cool unopened containers.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Methods and materials for Keep unnecessary personnel away. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

containment and cleaning up

Contain spillages with sand, earth or any suitable adsorbent material.

Not available.

**Environmental precautions** 7. Handling and storage

Precautions for safe handling

All equipment used when handling the product must be grounded. Avoid contact with eyes, skin, and clothing. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid prolonged exposure. Wear personal protective equipment. Use only with adequate ventilation. Wash thoroughly after handling. Keep away from sources of ignition - No smoking.

Conditions for safe storage, including any incompatibilities

Store in cool place. The pressure in sealed containers can increase under the influence of heat. Keep away from heat and sources of ignition. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place. Keep container tightly closed. Use care in handling/storage.

# 8. Exposure controls/personal protection

### Occupational exposure limits

Components	ir Contaminants (29 CFR 1910 Type	Value	Form
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
<b>US. OSHA Table Z-2 (29 CFR 19</b> 1	10.1000)		
Components	Туре	Value	
STYRENE (CAS 100-42-5)	Ceiling	200 ppm	
	TWA	100 ppm	
<b>US. OSHA Table Z-3 (29 CFR 19</b>	10.1000)		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
<b>US. ACGIH Threshold Limit Value</b>	es		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
STYRENE (CAS 100-42-5)	STEL	40 ppm	
	TWA	20 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
STYRENE (CAS 100-42-5)	STEL	425 mg/m3	
		100 ppm	
	TWA	215 mg/m3	

Material name: Penncoat 310 (All Colors)

7005 Version #: 01 Issue date: 09-29-2020 3/9 **US. NIOSH: Pocket Guide to Chemical Hazards** Components **Type** 

Value

**Form** 

50 ppm

## **Biological limit values**

Components	Value	Determinant	Specimen	Sampling Time
STYRENE (CAS 100-42-5)	40 μg/l	Styrene	Urine	*
	400 mg/g	Mandelic acid plus phenylglyoxylic	Creatinine in urine	*

<sup>\* -</sup> For sampling details, please see the source document.

## **Exposure guidelines**

**US - California OELs: Skin designation** 

STYRENE (CAS 100-42-5) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

STYRENE (CAS 100-42-5) Skin designation applies.

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Goggles/face shield are recommended.

**Skin protection** 

**Hand protection** Wear protective gloves.

Other Wear appropriate clothing to prevent any possibility of skin contact with solutions containing 10%

or more of this chemical.

**Respiratory protection** When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Not available.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

## 9. Physical and chemical properties

**Appearance** Viscous liquid

**Physical state** Liquid.

**Form** Viscous Liquid.

Color Grey. Odor Styrene Not available. Odor threshold Not available. pН Melting point/freezing point Not available. Initial boiling point and 294 °F (145.56 °C)

boiling range

89.6 - 95.0 °F (32.0 - 35.0 °C) Flash point

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower 1.1

(%)

Flammability limit -6.1

upper (%)

**Explosive limit - lower** 

Not available.

(%)

**Explosive limit - upper** 

(%)

Not available.

Vapor pressure 7 hPa Vapor density 3.6

Relative density 1.07 - 1.08

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** 914 °F (490 °C) estimated

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**VOC** 30 - 40 %

# 10. Stability and reactivity

**Reactivity** Not available.

**Chemical stability** Material is stable under normal conditions. However, this material can undergo hazardous

polymerization.

Possibility of hazardous

reactions

Hazardous polymerization can occur. Heat will speed polymerization.

**Conditions to avoid**Contact with acids. Avoid contact with oxidizing agents. Heat, flames and sparks.

**Incompatible materials** Acids. Aluminum chlorides. Halogens.. Metal salts. Peroxides. Strong bases. Strong oxidizing agents.

**Hazardous decomposition** 

products

Carbon oxides.

# 11. Toxicological information

## Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful. May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

**Skin contact** Causes skin irritation.

**Eye contact** Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Not available.

#### Information on toxicological effects

**Acute toxicity** 

Components Species Test Results

STYRENE (CAS 100-42-5)

**Acute** 

Inhalation

LC50 Rat 24 mg/l, 4 Hours

Oral

LD50 Rat 1 g/kg

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

# Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization Not available.

Germ cell mutagenicity Not available.

SDS US

### Carcinogenicity

This product contains crystalline silica. Silica is a known carcinogen; however in this encapsulated

form the normal routes of exposure are unavailable.

### IARC Monographs. Overall Evaluation of Carcinogenicity

QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

STYRENE (CAS 100-42-5) 2A Probably carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cance

# **US. National Toxicology Program (NTP) Report on Carcinogens**

QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

STYRENE (CAS 100-42-5) Reasonably Anticipated to be a Human Carcinogen.

**Reproductive toxicity** Suspected of damaging fertility or the unborn child.

Specific target organ toxicity

- single exposure

Not available.

Specific target organ toxicity

Causes damage to the following organs through prolonged or repeated exposure: Central nervous

- repeated exposure

system. Respiratory system.

**Aspiration hazard** Not available.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects

# 12. Ecological information

**Ecotoxicity** Harmful to aquatic life.

Components		Species	Test Results	
STYRENE (CAS 100-42-	5)			
Aquatic				
Crustacea	EC50	Water flea (Daphnia)	42 g/ml, 24 hours	
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)	5.1 - 16 mg/l, 96 hours	

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Persistence and degradability Not available.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

STYRENE 2.95

Mobility in soilNot available.Other adverse effectsNot available.

# 13. Disposal considerations

**Disposal instructions**Dispose in accordance with all applicable regulations. **Hazardous waste code**Dispose in accordance with all applicable regulations.

Double Flammable material with a flash point <140 F

Waste from residues / unused products

Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the

ground.

Contaminated packaging

Since emptied containers retain product residue, follow label warnings even after container is

emptied.

# 14. Transport information

#### DOT

**UN number** UN1866 **UN proper shipping name** Resin solution

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group III

Special precautions for

Not available.

user

**Special provisions** B1, B52, IB3, T2, TP1

Packaging exceptions 150

Packaging non bulk 173 **Packaging bulk** 242

**IATA** 

**UN number** UN1866 **UN proper shipping name** Resin solution

Transport hazard class(es) Class 3 **Subsidiary risk Packing group** III**Environmental hazards** No. **ERG Code** 3L

Special precautions for

user

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Not available.

Cargo aircraft only Allowed with restrictions.

**IMDG** 

**UN number** UN1866

**UN** proper shipping name **RESIN SOLUTION** 

Transport hazard class(es)

Class 3 **Subsidiary risk Packing group** III**Environmental hazards** 

Marine pollutant No **EmS** F-E, <u>S-E</u> Special precautions for Not available.

Transport in bulk according to Not available. Annex II of MARPOL 73/78

and the IBC Code

### DOT



# IATA; IMDG



# 15. Regulatory information

**US federal regulations** All components are on the U.S. EPA TSCA Inventory List.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

# TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

STYRENE (CAS 100-42-5) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cancer

lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312** Yes

**Hazardous chemical** 

**Classified hazard** 

Flammable (gases, aerosols, liquids, or solids)

**categories** Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

 Chemical name
 CAS number
 % by wt.

 STYRENE
 100-42-5
 20 - 40

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

STYRENE (CAS 100-42-5)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

STYRENE (CAS 100-42-5) Other Flavoring Substances with OSHA PEL's

**US state regulations** WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65

California Proposition 65 - CRT: Listed date/Carcinogenic substance

QUARTZ (CAS 14808-60-7) Listed: October 1, 1988 STYRENE (CAS 100-42-5) Listed: April 22, 2016

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

QUARTZ (CAS 14808-60-7) STYRENE (CAS 100-42-5)

### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes

Country(s) or region Inventory name On inventory (yes/no)\*

New Zealand New Zealand Inventory Yes

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

**Issue date** 09-29-2020

Version # 01

**Further information** HMIS® is a registered trade and service mark of the NPCA.

**NFPA ratings** Health: 2

Flammability: 3 Instability: 0

References HSDB

IARC Monographs. Overall Evaluation of Carcinogenicity

**Disclaimer** The information in the sheet was written based on the best knowledge and experience currently

available. The information given is based on data available for the material, the components of the

material, and similar materials.

**Revision information** Product and Company Identification: Alternate Trade Names

**GHS:** Classification

Material name: Penncoat 310 (All Colors)
7005 Version #: 01 Issue date: 09-29-2020

Yes