SAFETY DATA SHEET



1. Identification

Product identifier TUFCHEM SILICATE CONCRETE FOUNDATION GRADE POWDER W/PP FIBERS

Other means of identification None.

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

1-800-222-7122

Normal work hours telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

Emergency 24-hour

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

telephone number

Information on operation 8:00 a.m. to 5:00 p.m.

hours

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

> Carcinogenicity Category 1 Specific target organ toxicity, repeated Category 1

exposure

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

No hazards resulting from the material as supplied.

Label elements



Signal word Danger

Hazard statement Harmful if swallowed. Causes damage to organs through prolonged or repeated exposure. May

cause cancer.

Precautionary statement

Prevention Do not breathe dust/fume/gas/mist/vapors/spray. Observe good industrial hygiene practices. Wash

> thoroughly after handling. Do not eat, drink, or smoke when using this product. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. IF Response

exposed or concerned: Get medical advice/attention.

Store locked up. Storage

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Material name: TUFCHEM SILICATE CONCRETE FOUNDATION GRADE POWDER W/PP FIBERS 5891 Version #: 03 Revision date: 03-13-2020 Issue date: 04-10-2015

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
QUARTZ		14808-60-7	70 - 90
DISODIUM HEXAFLUOROSILICATE		16893-85-9	1 - 10
Glass, oxide, chemicals		65997-17-3	1 - 10
Other components below reportable	e levels		4.8

4. First-aid measures

Inhalation Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration or

give oxygen by trained personnel. Call a physician if symptoms develop or persist. Get medical

attention.

Skin contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Get medical attention if symptoms occur. Wash contaminated clothing before reuse. Destroy or thoroughly clean contaminated shoes.

Eye contactDo not rub eyes. Rinse with water. Get medical attention. Get medical attention if irritation

develops and persists. In case of contact, immediately flush eyes with large amounts of water,

continuing to flush for 15 minutes.

Ingestion Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not

induce vomiting without advice from poison control center. Get medical attention.

Most important symptoms/effects, acute and

symptoms/effects, acute and delayed

chronic effects.

Indication of immediate medical attention and special

medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Dusts may irritate the respiratory tract, skin and eyes. Coughing, Prolonged exposure may cause

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Keep victim under observation. Keep victim warm.

5. Fire-fighting measures

environment.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

and precautions for firefighters
Fire fighting

In the event of fire, cool tanks with water spray.

equipment/instructions
Specific methods

Cool containers exposed to flames with water until well after the fire is out.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Collect dust using a vacuum cleaner equipped with HEPA filter. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Use only with adequate ventilation. Do not breathe dust. Do not breathe dust. Do not get in eyes, on skin, on clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep container tightly closed. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children. Store in a cool, dry place.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit At this time, the other constituents have no known exposure limits.

Components	ntaminants (29 CFR 1910.1000) Type	Value	Form
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 CFR 1910.10 Components	00) Type	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Values Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Chemica Components	l Hazards Type	Value	Form
DISODIUM HEXAFLUOROSILICATE (CAS 16893-85-9)	TWA	2.5 mg/m3	
HEXAFLUOROSILICATE	TWA	2.5 mg/m3 3 fibers/cm3	Fiber.
HEXAFLUOROSILICATE (CAS 16893-85-9) Glass, oxide, chemicals (CAS		-	Fiber. Fibrous dust.
HEXAFLUOROSILICATE (CAS 16893-85-9) Glass, oxide, chemicals (CAS		3 fibers/cm3	
HEXAFLUOROSILICATE (CAS 16893-85-9) Glass, oxide, chemicals (CAS		3 fibers/cm3	Fibrous dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

Appropriate engineering

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

controls

Material name: TUFCHEM SILICATE CONCRETE FOUNDATION GRADE POWDER W/PP FIBERS 5891 Version #: 03 Revision date: 03-13-2020 Issue date: 04-10-2015

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter. Goggles/face

shield are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Wear

appropriate clothing to prevent any possibility of skin contact with solutions containing 10% or

more of this chemical.

Respiratory protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels

exceeding the exposure limits. Chemical respirator with organic vapor cartridge, full facepiece, dust

and mist filter.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Powder.
Physical state Solid.

Form
Color
Light tan to grey
Odor
Not available.
Odor threshold
Not available.
PH
Not available.
Melting point/freezing point
Not available.
Not available.
Not available.
Not available.

boiling range

Flash point 450.0 °F (232.2 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Insoluble **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature 400 °F (204.44 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials. None under normal conditions.

Incompatible materials

Strong oxidizing agents. Powerful oxidizers. Chlorine. Hydrogen fluoride.

Hazardous decomposition

products

Oxides of silicon.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause cancer by inhalation. Dust may irritate respiratory system. Prolonged inhalation may be

harmful.

Skin contactCauses mild skin irritation. **Eye contact**Harmful in contact with eyes.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics

Dusts may irritate the respiratory tract, skin and eyes. Coughing.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

Germ cell mutagenicity

irritation

Harmful in contact with eyes. None known.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This material contains a component that is capable of being absorbed through intact skin and tha

has been shown to cause reproductive and developmental effects in laboratory animals. No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Hazardous by OSHA criteria. Cancer Hazard. Hazardous by WHMIS criteria. In 1997, IARC (the

International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation,

IARC noted that "carcinogenicity was not detected in all industrial circumstances studied.

Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June

2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause

cancer. Occupational exposure to respirable dust and respirable crystalline silica should be

monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity Not classified.

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful. Prolonged exposure may cause chronic effects.

Further information This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Product Species Test Results

TUFCHEM SILICATE CONCRETE FOUNDATION GRADE POWDER W/PP FIBERS

Aquatic

Fish LC50 Fish 1229.4117 mg/l, 96 hours estimated

Components Species **Test Results**

DISODIUM HEXAFLUOROSILICATE (CAS 16893-85-9)

Aquatic

Fish LC50 Bluegill (Lepomis macrochirus) 49 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available. Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues /

unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

Material name: TUFCHEM SILICATE CONCRETE FOUNDATION GRADE POWDER W/PP FIBERS 5891 Version #: 03 Revision date: 03-13-2020 Issue date: 04-10-2015

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cancer

lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

Classified hazard Acute toxicity (any route of exposure)

categories Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to QUARTZ, which is known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Glass, oxide, chemicals (CAS 65997-17-3) QUARTZ (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

On inventory (yes/no)* Country(s) or region **Inventory name**

Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

16. Other information, including date of preparation or last revision

04-10-2015 **Issue date Revision date** 03-13-2020

Version # 03

country(s).

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings

Flammability: 0 Instability: 0

ACGIH References

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

EPA: AQUIRE database

HSDB® - Hazardous Substances Data Bank

IARC Monographs, Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge

> information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information This document has undergone significant changes and should be reviewed in its entirety

Material name: TUFCHEM SILICATE CONCRETE FOUNDATION GRADE POWDER W/PP FIBERS