SAFETY DATA SHEET



1. Identification

Product identifier R-17-A-73 COATING/PRIMER

Other means of identification None.

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

1-800-222-7122

Normal work hours

telephone number

1-877-982-7667

Website www.ergonarmor.com
E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

Health hazards

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Gases under pressure Liquefied gas
Skin corrosion/irritation Category 2

Germ cell mutagenicity Category 1B
Carcinogenicity Category 1B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

Environmental hazards Not classified. **OSHA defined hazards** Not classified.

Label elements



Signal word Danger

Hazard statementContains gas under pressure; may explode if heated. May cause cancer. May be fatal if swallowed and enters airways. Extremely flammable aerosol. Causes skin irritation. May cause drowsiness or

dizziness. May cause genetic defects.

Precautionary statement

Prevention Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only

outdoors or in a well-ventilated area. Pressurized container: Do not pierce or burn, even after use. Wear protective gloves/protective clothing/eye protection/face protection. Do not spray on an open flame or other ignition source. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Obtain special instructions before use. Do not handle until all safety precautions have

been read and understood.

Response IF ON SKIN: Wash with plenty of soap and water. Specific treatment see Section 4 of this SDS.

Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medica advice/attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center/doctor if you feel unwell. IF exposed or concerned:

Get medical advice/attention.

Storage Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT, OXIDIZED		64742-93-4	30 - 50
SOLVENT NAPHTHA (PETROLEUM) LIGHT ALIPH.	,	64742-89-8	25 - 45
Propellant		Proprietary	0 - 40

4. First-aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if

victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. For breathing difficulties, oxygen may be necessary. Get medical attention, if needed. Call a physician if symptoms develop or persist.

Skin contactTake off immediately all contaminated clothing. Wash off immediately with plenty of water. Wash

off with soap and water. Rinse skin with water/shower. Get medical attention if irritation develops and persists. For minor skin contact, avoid spreading material on unaffected skin. Take off

contaminated clothing and wash before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Rinse with water. If a contact

lens is present, DO NOT delay irrigation or attempt to remove the lens. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately. Get medical attention

if irritation develops and persists.

Ingestion Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention if symptoms occur. If ingestion of a large amount does occur, call a poison

control center immediately.

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

General information In case of shortness of breath, give oxygen. Get medical attention if symptoms occur. Ensure that

medical personnel are aware of the material(s) involved, and take precautions to protect

themselves.

5. Fire-fighting measures

Suitable extinguishing media

Foam. Dry powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed. Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of nitrogen and sulfur may also be

formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions Specific methods

Stop leak if you can do so without risk. Move containers from fire area if you can do so without risk.

In the event of fire, cool tanks with water spray.

Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unnecessary personnel away. Ensure adequate ventilation. Wear appropriate personal protective equipment. Keep people away from and upwind of spill/leak.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Prevent entry into waterways, sewer, basements or confined areas.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Observe good industrial hygiene practices. Keep away from sources of ignition - No smoking. Avoid contact with skin. Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Store in a closed container away from incompatible materials. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Refrigeration recommended. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSI	IA Table Z-:	L Limits for A	ir Contaminants	(29 CFR	1910.1000)
---------	--------------	----------------	-----------------	---------	------------

Components	Туре	Value	
Propellant	PEL	1800 mg/m3	
		1000 ppm	
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. (CAS 64742-89-8)	PEL	400 mg/m3	
		100 ppm	
U.S NIOSH			
Components	Туре	Value	
ASPHALT, OXIDIZED (CAS 64742-93-4)	REL	5 mg/m3	
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	
Propellant	TWA	1800 mg/m3	
		1000 ppm	
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. (CAS 64742-89-8)	TWA	400 mg/m3	
		100 ppm	

Biological limit values No biological exposure limits noted for the ingredient(s).

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

controls

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Appropriate engineering

Hand protection Wear protective gloves.

Material name: R-17-A-73 COATING/PRIMER 6369 Version #: 01 Issue date: 12-06-2021 Other Wear appropriate chemical resistant clothing.

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

-43.78 °F (-42.1 °C) estimated

-156.0 °F (-104.4 °C) estimated

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid. Not available. Color Odor Not available. **Odor threshold** Not available.

Melting point/freezing point -305.68 °F (-187.6 °C) estimated Initial boiling point and

boiling range

Flash point

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower 1.9 % estimated

Not available.

(%)

Flammability limit -

upper (%)

9.5 % estimated

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure Not available. Vapor density Not available. Not available. Relative density

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature 550 °F (287.78 °C) estimated

Decomposition temperature Not available. Not available. **Viscosity**

Other information

Specific gravity 0.32292 estimated

VOC < 500 g/l

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions **Conditions to avoid**

Avoid temperatures exceeding the flash point. Heat, flames and sparks. Contact with incompatible

materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition Carbon monoxide. Volatile hydrocarbon vapors.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Skin contact Causes skin irritation.

Eve contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Breathing of high vapor concentrations may cause dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause

temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results	
SOLVENT NAPHTHA (PETROLEUM	1), LIGHT ALIPH. (CAS 64742-89-8)		

Acute

Inhalation

LC50 Rat 61 mg/l, 4 Hours

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT, OXIDIZED (CAS 64742-93-4) 2A Probably carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects

Specific target organ toxicity

- single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity

- repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results
R-17-A-73 COATING/I	PRIMER		
Aquatic			
Crustacea	EC50	Daphnia	12.5 mg/l, 48 hours estimated
Fish	LC50	Fish	30 mg/l, 96 hours estimated

Material name: R-17-A-73 COATING/PRIMER 6369 Version #: 01 Issue date: 12-06-2021 Components Species Test Results

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. (CAS 64742-89-8)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours

Fish LC50 Rainbow trout, donaldson trout 8.8 mg/l, 96 hours

(Oncorhynchus mykiss)

8.8 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Propellant 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues /

unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing groupNot available.Special precautions forNot available.

user

Special provisions N82
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)
Class 2.1
Subsidiary risk -

Packing group Not available.

Environmental hazards No. **ERG Code** 10L

Special precautions for

user

Not available.

Other information

Passenger and cargo Allowed with restrictions.

aircraft

^{*} Estimates for product may be based on additional component data not shown.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not available.

Environmental hazards

Marine pollutantNo.EmSF-D, S-USpecial precautions forNot available.

user

Transport in bulk according to Not available. **Annex II of MARPOL 73/78**

and the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Yes

Hazardous chemical

Material name: R-17-A-73 COATING/PRIMER 6369 Version #: 01 Issue date: 12-06-2021

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)

Gas under pressure Skin corrosion or irritation Germ cell mutagenicity Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Propellant (CAS Proprietary)

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT, OXIDIZED (CAS 64742-93-4) Listed: January 1, 1990

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. (CAS 64742-89-8)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 12-06-2021

Version # 01

NFPA ratings Health: 2

Flammability: 4 Instability: 0

Material name: R-17-A-73 COATING/PRIMER 6369 Version #: 01 Issue date: 12-06-2021

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Material name: R-17-A-73 COATING/PRIMER 6369 Version #: 01 Issue date: 12-06-2021