# SAFETY DATA SHEET



#### 1. Identification

**Product identifier EPOXY COLD ROOM HARDENER** 

Other means of identification None.

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc. **Company Name** 

**Address** 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

**Normal work hours** 

telephone number

1-877-982-7667

1-800-222-7122

Website www.ergonarmor.com E-mail sds@ergon.com

**Emergency 24-hour** telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

**Information on operation** 

hours

8:00 a.m. to 5:00 p.m.

# 2. Hazard(s) identification

**Physical hazards** Not classified. **Health hazards** 

Acute toxicity, oral Acute toxicity, dermal Category 4 Acute toxicity, inhalation Category 2 Skin corrosion/irritation Category 1 Serious eye damage/eye irritation Category 1 Sensitization, skin Category 1 Reproductive toxicity Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Category 4

**Environmental hazards** Not classified. **OSHA** defined hazards Not classified.

**Label elements** 



Signal word Danger

**Hazard statement** Fatal if inhaled. Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and

eye damage. May cause an allergic skin reaction. May damage fertility or the unborn child. May

cause respiratory irritation.

**Precautionary statement Prevention** 

Obtain special instructions before use. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Avoid release to the environment.

Material name: EPOXY COLD ROOM HARDENER

Response IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing, IF ON SKIN (or hair): Take off immediately all contaminated clothing, Rinse skin

with water/shower. If skin irritation or rash occurs: Get medical advice/attention. IF

SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. Specific treatment is urgent (see this

label). Take off contaminated clothing and wash it before reuse. Collect spillage.

Storage Keep container tightly closed. Store in a well-ventilated place. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

Not applicable.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
2,2'-IMINODI(ETHYLAMINE)		111-40-0	45 - 70
4,4'-ISOPROPYLIDENEDIPHENOL		80-05-7	15 - 40

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical

advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open Eye contact

eyes wide apart. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical

attention immediately.

**Ingestion** Rinse mouth thoroughly. Do not induce vomiting. If vomiting occurs, keep head low so that

stomach content doesn't get into the lungs. Never give anything by mouth to a victim who is unconscious or is having convulsions. Call a physician or poison control center immediately.

Most important

symptoms/effects, acute and

delaved

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Vapors have a narcotic effect and may cause headache, fatique, dizziness and nausea.

**Indication of immediate** medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim

under observation. Symptoms may be delayed.

General information Show this safety data sheet to the doctor in attendance. Ensure that medical personnel are aware

of the material(s) involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder. Dry sand. Limestone powder.

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed. May generate ammonia gas. Nitrogen Oxides (NOx). Burning produces noxious and toxic fumes. Combustion may form carbon

monoxide.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Use standard firefighting procedures and consider the hazards of other involved materials.

Move containers from fire area if you can do so without risk.

Fire fighting equipment/instructions

Specific methods

No unusual fire or explosion hazards noted. General fire hazards

Material name: EPOXY COLD ROOM HARDENER

5893 Version #: 03 Revision date: 12-14-2022 Issue date: 04-14-2015

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch or walk through spilled material. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling

Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry place. Store in tightly closed container. Store in a well-ventilated place. Store locked up. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

# **Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US.	<b>ACGTH</b>	Thresho	old Lir	nit Values

Components	Туре	Value		
2,2'-IMINODI(ETHYLAMINE) (CAS 111-40-0)	TWA	1 ppm		
US. NIOSH: Pocket Guide to Chemical Hazards				
Components	Туре	Value		
2,2'-IMINODI(ETHYLAMINE) (CAS 111-40-0)	TWA	4 mg/m3		

Biological limit values

No biological exposure limits noted for the ingredient(s).

**Exposure guidelines** 

**US - California OELs: Skin designation** 

2,2'-IMINODI(ETHYLAMINE) (CAS 111-40-0) Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies** 

2,2'-IMINODI(ETHYLAMINE) (CAS 111-40-0) Skin designation applies.

**US ACGIH Threshold Limit Values: Skin designation** 

2,2'-IMINODI(ETHYLAMINE) (CAS 111-40-0)

Danger of cutaneous absorption

**US NIOSH Pocket Guide to Chemical Hazards: Skin designation** 

2,2'-IMINODI(ETHYLAMINE) (CAS 111-40-0) Can be absorbed through the skin.

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Provide evewash station and safety shower.

1 ppm

# Individual protection measures, such as personal protective equipment

**Eye/face protection** Chemical goggles and face shield are recommended.

Skin protection

**Hand protection** Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves. Impervious gloves. Nitrile, butyl rubber or neoprene gloves are recommended.

**Other** Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Use

gloves to protect hands from abrasions. PVC or rubber boots.

5893 Version #: 03 Revision date: 12-14-2022 Issue date: 04-14-2015

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Contaminated work clothing should not be allowed out of the workplace.

# 9. Physical and chemical properties

**Appearance** Amber Liquid

Physical state Liquid. **Form** Liquid. Amber. Color Odor Ammoniacal. Odor threshold Not available.

pΗ 11

Melting point/freezing point Not available.

Initial boiling point and

boiling range

> 392 °F (> 200 °C)

Flash point 217.0 °F (102.8 °C)

**Evaporation rate** Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

**Explosive limit - lower** 

(%)

Not available.

**Explosive limit - upper** 

(%)

Not available.

Vapor pressure < 0.13 hPa @21°C Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) 140 g/cm3 **Partition coefficient** Not available. (n-octanol/water)

Not available. Auto-ignition temperature **Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**Density** 1.03 g/cm3 @21°C **Dynamic viscosity** 150 mPa.s @25°C Kinematic viscosity 130 mm2/s @25°C

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials. **Incompatible materials** Do not add sodium nitrite or other nitrosating agents which may form cancer causing

> nitrosamines. Nitrous acid. Sodium hypochlorite. Product corrodes copper, aluminum, zinc, and galvanized surfaces. Oxidizing agents. Reaction with peroxides may result in violent decomposition

of peroxide possibly creating an explosion.

Hazardous decomposition

products

Nitric Acid. Ammonia. Nitrogen oxides (NOx). Carbon dioxide. Carbon monoxide. Nitrosamine. Aldehydes. Nitrogen oxide can react with water vapors to form corrosive nitric acid. Flammable

hydrocarbon fragments.

## 11. Toxicological information

Information on likely routes of exposure

**Inhalation** Fatal if inhaled.

Skin contact Causes severe skin burns and eye damage. Harmful in contact with skin. May cause an allergic

skin reaction.

Eye contact Causes serious eye damage.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing, May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Causes serious eye

damage. Burning pain and severe corrosive skin damage. May cause respiratory irritation.

Information on toxicological effects

Acute toxicity Harmful in contact with skin. Fatal if inhaled. Harmful if swallowed.

**Product Species Test Results** 

**EPOXY COLD ROOM HARDENER** 

Acute

Oral

1627 mg/kg LD50 Rat Components **Species Test Results** 

2,2'-IMINODI(ETHYLAMINE) (CAS 111-40-0)

**Acute** Oral

LD50 Rat 1080 mg/kg

\* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity May damage fertility or the unborn child.

Specific target organ toxicity

- single exposure

May cause respiratory irritation.

Specific target organ toxicity

- repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Material name: EPOXY COLD ROOM HARDENER

Product Species Test Results

**EPOXY COLD ROOM HARDENER** 

**Aquatic** 

Crustacea EC50 Daphnia 18.4, 48 hours
Fish LC50 Fish 10.5449, 96 hours

Acute

Crustacea EC50 Daphnia 26.2857, 48 hours estimated Fish LC50 Fish 10.2183, 96 hours estimated

Components Species Test Results

2,2'-IMINODI(ETHYLAMINE) (CAS 111-40-0)

Aquatic

Acute

Fish LC50 Guppy (Poecilia reticulata) 1014, 96 hours

4,4'-ISOPROPYLIDENEDIPHENOL (CAS 80-05-7)

**Aquatic** 

Acute

Crustacea EC50 Water flea (Daphnia magna) >= 9.2 - <= 11.4 mg/l, 48 hours Fish LC50 Fathead minnow (Pimephales promelas) >= 3.6 - <= 5.4 mg/l, 96 hours

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** 

Partition coefficient n-octanol / water (log Kow)

4,4'-ISOPROPYLIDENEDIPHENOL 3.32

**Mobility in soil** No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

**Disposal instructions** Dispose of this material and its container to hazardous or special waste collection point. Incinerate

the material under controlled conditions in an approved incinerator. Dispose of contents/container

in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

## 14. Transport information

DOT

UN number UN2079

**UN proper shipping name** Diethylenetriamine Solution

Transport hazard class(es)

Class 8
Subsidiary risk Label(s) 8
Packing group II
Environmental hazards

Marine pollutant no

**Special precautions for** Read safety instructions, SDS and emergency procedures before handling.

user

**Special provisions** B2, IB2, T7, TP2

Material name: EPOXY COLD ROOM HARDENER
5893 Version #: 03 Revision date: 12-14-2022 Issue date: 04-14-2015

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Packaging exceptions** 154 Packaging non bulk 202 **Packaging bulk** 242

**IATA** 

**UN** number UN2079

**UN proper shipping name** Diethylenetriamine Solution

Transport hazard class(es) Class 8 **Subsidiary risk** 

**Packing group** ΙΙ **Environmental hazards** Yes **ERG Code** 8L

**Special precautions for** 

Other information

user

Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

**IMDG** 

**UN** number UN2079

**UN proper shipping name** DIETHYLENETRIAMINE SOULTION, MARINE POLLUTANT Transport hazard class(es)

**Class** 8 **Subsidiary risk Packing group** ΙΙ **Environmental hazards** 

Marine pollutant Yes F-A, S-B **EmS** 

Special precautions for Read safety instructions, SDS and emergency procedures before handling.

user

Transport in bulk according to Not established.

Annex II of MARPOL 73/78

and the IBC Code

DOT



# IATA; IMDG



5893 Version #: 03 Revision date: 12-14-2022 Issue date: 04-14-2015

#### Marine pollutant



### 15. Regulatory information

**US federal regulations** 

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard,

29 CFR 1910.1200.

**Toxic Substances Control Act (TSCA)** 

All components of the mixture on the TSCA 8(b) inventory are designated

"active".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**TSCA Chemical Action Plans, Chemicals of Concern** 

4,4'-ISOPROPYLIDENEDIPHENOL (CAS 80-05-7) Bisphenol A Action Plan

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

4,4'-ISOPROPYLIDENEDIPHENOL (CAS 80-05-7)

Listed.

**SARA 304 Emergency release notification** 

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

**SARA 302 Extremely hazardous substance** 

Not listed.

SARA 311/312 Hazardous Yes

chemical

**Classified hazard** 

categories

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical nameCAS number% by wt.4,4'-ISOPROPYLIDENEDIPHENOL80-05-715 - 40

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

4,4'-ISOPROPYLIDENEDIPHENOL (CAS 80-05-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

#### **US state regulations**

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

4,4'-ISOPROPYLIDENEDIPHENOL (CAS 80-05-7)

## **California Proposition 65**



WARNING: This product can expose you to 4,4'-ISOPROPYLIDENEDIPHENOL, which is known to the State of

California to cause birth defects or other reproductive harm. For more information go

to www.P65Warnings.ca.gov.

#### California Proposition 65 - CRT: Listed date/Developmental toxin

4,4'-ISOPROPYLIDENEDIPHENOL (CAS 80-05-7) Listed: December 18, 2020

Material name: EPOXY COLD ROOM HARDENER
5893 Version #: 03 Revision date: 12-14-2022 Issue date: 04-14-2015

#### California Proposition 65 - CRT: Listed date/Female reproductive toxin

Listed: May 11, 2015 4,4'-ISOPROPYLIDENEDIPHENOL (CAS 80-05-7)

## **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

04-14-2015 **Issue date Revision date** 12-14-2022

Version # 03

Disclaimer Ergon Armor cannot anticipate all conditions under which this information and its product, or the

products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

**Revision information** This document has undergone significant changes and should be reviewed in its entirety.

SDS US 5893 Version #: 03 Revision date: 12-14-2022 Issue date: 04-14-2015