SAFETY DATA SHEET



1. Identification

Product identifier NOVOCOAT™ EP3300 PASTE/CAULK PART B

Other means of identification None.

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

1-800-222-7122

Normal work hours

telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1

> Serious eye damage/eye irritation Category 1 Sensitization, respiratory Category 1 Sensitization, skin Category 1 Germ cell mutagenicity Category 2 Specific target organ toxicity, repeated Category 2

exposure

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye

damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing genetic defects. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions

before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Wear protective aloves/protective clothing/eve protection/face protection. In case of inadequate ventilation wear

respiratory protection.

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B

If skin irritation or rash occurs, seek medical attention. IF SWALLOWED: Rinse mouth. Do NOT Response

induce vomiting. If experiencing respiratory symptoms: Call a POISON CENTER or

doctor/physician. IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Specific treatment (see this label). Take off contaminated clothing and wash before reuse. IF ON

SKIN: Wash with plenty of soap and water. IF exposed or concerned: Get medical

advice/attention.

Store locked up. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
BENZYL ALCOHOL		100-51-6	25 - 35
4,4'-METHYLENEBIS(CYCLOHEXYLA MINE)		1761-71-3	15 - 25
QUARTZ		14808-60-7	10 - 20
[3-(Aminomethyl)phenyl]methanami ne		1477-55-0	5 - 15
[(DIMETHYLAMINO)METHYL]PHEN OL		25338-55-0	1 - 10
3-AMINOPROPYLTRIETHOXYSILANE		919-30-2	< 1
BENZENE, HYDROXY-		108-95-2	< 1
Other components below reportable	levels		30 - 40

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists. Wash

contaminated clothing before reuse.

Eye contact Rinse with water. Continue to rinse for at least 15 minutes. Get medical attention if irritation

persists after washing.

Ingestion Rinse mouth. Do not induce vomiting. If vomiting occurs, the head should be kept low so that

Direct contact with eyes may cause temporary irritation.

stomach vomit doesn't enter the lungs. Call a POISON CENTER or doctor/physician if you feel

Most important

symptoms/effects, acute and

delaved

Indication of immediate medical attention and special

treatment needed **General information** Treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

and precautions for

Special protective equipment Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

firefighters

SDS US

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container.

8. Exposure controls/personal protection

US OSHA Table 7-1 Limits for Air Contaminants (20 CEP 1010 1000)

Occupational exposure limits

Components	ontaminants (29 CFR 1910 Type	Value	Form
BENZENE, HYDROXY- (CAS 108-95-2)	PEL	19 mg/m3	
		5 ppm	
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 CFR 1910.1 Components	.000) Type	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
[3-(Aminomethyl)phenyl]me thanamine (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
BENZENE, HYDROXY- (CAS 108-95-2)	TWA	5 ppm	
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Chemic Components	cal Hazards Type	Value	Form
[3-(Aminomethyl)phenyl]me thanamine (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
BENZENE, HYDROXY- (CAS 108-95-2)	Ceiling	60 mg/m3	
		15.6 ppm	
	TWA	19 mg/m3	
		5 ppm	
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B

SDS US

5549 Version #: 03 Revision date: 10-21-2021 Issue date: 06-12-2020

US. Workplace Environmental Exposure Level (WEEL) Guides

 Components
 Type
 Value

 BENZYL ALCOHOL (CAS 100-51-6)
 TWA 44.2 mg/m3

10 ppm

Biological limit values

ACGIH Biologica	l Exposure Indices
------------------------	--------------------

Components	Value	Determinant	Specimen	Sampling Time
BENZENE, HYDROXY- (CAS 108-95-2)	5 250 mg/g	Phenol with hydrolysis	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

[3-(Aminomethyl)phenyl]methanamine (CAS 1477-55-0) Can be absorbed through the skin. BENZENE, HYDROXY- (CAS 108-95-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

BENZENE, HYDROXY- (CAS 108-95-2) Skin designation applies.

US - Tennessee OELs: Skin designation

[3-(Aminomethyl)phenyl]methanamine (CAS 1477-55-0) Can be absorbed through the skin. BENZENE, HYDROXY- (CAS 108-95-2) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

[3-(Aminomethyl)phenyl]methanamine (CAS 1477-55-0) Can be absorbed through the skin. BENZENE, HYDROXY- (CAS 108-95-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

[3-(Aminomethyl)phenyl]methanamine (CAS 1477-55-0) Can be absorbed through the skin. BENZENE, HYDROXY- (CAS 108-95-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

BENZENE, HYDROXY- (CAS 108-95-2)

Can be absorbed through the skin.

Appropriate engineering

controls occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Wear suitable protective clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene Always observe good personal hygiene measures, such as washing after handling the material and

considerations before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance Paste.
Physical state Liquid.
Form Paste.
Color Various.

Odor Ammoniacal. Amine-like.

Odor threshold

pH

Alkaline

Melting point/freezing point

Initial boiling point and

Not available.

Not available.

boiling range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Partial

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 11.72 lb/gal estimated

Specific gravity 1.40 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Material is stable under normal conditions. **Possibility of hazardous** Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause sensitization by inhalation.

Skin contact May cause an allergic skin reaction. Causes severe skin burns and eye damage

Eye contact Causes serious eye damage. **Ingestion** May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Causes serious eye damage. May cause an allergic skin reaction.

Information on toxicological effects

Acute toxicity

Components Species Test Results

BENZYL ALCOHOL (CAS 100-51-6)

<u>Acute</u> Dermal

LD50 Rabbit 2000 mg/kg

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B

5549 Version #: 03 Revision date: 10-21-2021 Issue date: 06-12-2020 5 / 9

Components Species Test Results

Inhalation

LC50 Rat 1000 mg/l, 8 Hours

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes eye burns.

Respiratory or skin sensitization

Respiratory sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled

Skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity Known or suspected mutagen.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. This product

contains crystalline silica. Silica is a known carcinogen; however in this encapsulated form the

Tost Posulto

normal routes of exposure are unavailable.

IARC Monographs. Overall Evaluation of Carcinogenicity

BENZENE, HYDROXY- (CAS 108-95-2)

3 Not classifiable as to carcinogenicity to humans.

QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects

Specific target organ toxicity

- single exposure

Droduct

Not classified.

Specific target organ toxicity N

- repeated exposure

Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

EcotoxicityThe product contains a substance which is toxic to aquatic organisms.

Species

Product		Species	lest Results
NOVOCOAT™ EP3300 PAST	E/CAULK PART B		
Aquatic			
Crustacea	EC50	Daphnia	4444.7607 mg/l, 48 hours estimated
Fish	LC50	Fish	903.2863 mg/l, 96 hours estimated
Components		Species	Test Results
BENZENE, HYDROXY- (CAS	108-95-2)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia obtusa)	4.7 - 6.4 mg/l, 48 hours
Fish	LC50	Asiatic knifefish (Notopterus notopterus)	8 - 8.25 mg/l, 96 hours
BENZYL ALCOHOL (CAS 100)-51-6)		
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	10 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

BENZENE, HYDROXY- 1.46
BENZYL ALCOHOL 1.1

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions When this product as supplied is to be discarded as waste, it does not meet the definition of a

RCRA waste under 40 CFR 261.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

UN number UN3082

UN proper shipping name ENVIRONMENATALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S (BENZENE, HYDROXY-)

Transport hazard class(es)

Class 9 **Subsidiary risk** Packing group III

Environmental hazards


Marine pollutant No.

Not available. **EmS** Special precautions for Not available.

Transport in bulk according to Not available. Annex II of MARPOL 73/78

and the IBC Code

IMDG



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BENZENE, HYDROXY- (CAS 108-95-2) Listed.

SARA 304 Emergency release notification

BENZENE, HYDROXY- (CAS 108-95-2) 1000 LBS OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cancer

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B

5549 Version #: 03 Revision date: 10-21-2021 Issue date: 06-12-2020 7/9

SDS US

lung effects immune system effects kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name CAS number Threshold **Threshold** Reportable **Threshold** planning quantity planning planning quantity (pounds) (pounds) quantity, lower quantity, upper value (pounds) value (pounds) 500 10000 BENZENE, HYDROXY-108-95-2 1000

SARA 311/312 Yes

Hazardous chemical

Classified hazard Skin corrosion or irritation

categories Serious eye damage or eye irritation Respiratory or skin sensitization

Germ cell mutagenicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. BENZENE, HYDROXY-108-95-2 < 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE, HYDROXY- (CAS 108-95-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

BENZENE, HYDROXY- (CAS 108-95-2) Low priority

US state regulations

California Proposition 65



WARNING: California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

OUARTZ (CAS 14808-60-7) Listed: October 1, 1988

US. California, Candidate Chemicals List, Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

BENZENE, HYDROXY- (CAS 108-95-2) QUARTZ (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B

SDS US

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 06-12-2020 **Revision date** 10-21-2021

Version # 03

NFPA ratings Health: 3

Flammability: 0 Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Composition / Information on Ingredients: Disclosure Overrides

Physical & Chemical Properties: Multiple Properties Toxicological Information: Toxicological Data Transport information: General information

HazReg Data: North America

GHS: Classification

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B
5549 Version #: 03 Revision date: 10-21-2021 Issue date: 06-12-2020