SAFETY DATA SHEET



1. Identification

Product identifier NOVOCOAT™ SC2200 RAPID SET PIPE COATING PART B

Other means of identification None.

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

1-800-222-7122

Normal work hours

telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1

8:00 a.m. to 5:00 p.m.

Serious eye damage/eye irritation Category 1 Sensitization, respiratory Category 1 Sensitization, skin Category 1 Germ cell mutagenicity Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, repeated Category 2

exposure

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word

Hazard statement Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye

damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing genetic defects. May cause damage to organs through

prolonged or repeated exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

SDS US

Material name: NOVOCOAT™ SC2200 RAPID SET PIPE COATING PART B

5873 Version #: 02 Revision date: 10-20-2021 Issue date: 06-15-2020 1/9 **Response** If swallowed: Rinse mouth. Do NOT induce vomiting. Specific treatment see Section 4 of this SDS.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	<u>%</u>
BENZYL ALCOHOL		100-51-6	15 - 25
2,4,6-TRIS(DIMETHYLAMINOMETH YL)PHENOL	1	90-72-2	1 - 10
4,4'-METHYLENEBIS(CYCLOHEXYL MINE)	A	1761-71-3	1 - 10
PHENOL		108-95-2	1 - 10
TRIENTINE		112-24-3	1 - 10
Other components below reportab	le levels		67.2641

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device. Call a physician or poison control center immediately.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a physician or

poison control center immediately. Chemical burns must be treated by a physician. For minor skin contact, avoid spreading material on unaffected skin. Wash contaminated clothing before reuse.

Wash clothing separately before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO

NOT delay irrigation or attempt to remove the lens. Continue rinsing. Call a physician or poison

control center immediately.

Ingestion Call a physician or poison control center immediately. If swallowed, rinse mouth with water (only if

the person is conscious). Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device.

Most important Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may

symptoms/effects, acute and

delayed

General information

Indication of immediate medical attention and special treatment needed

include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Alcohol foam. Foam. Dry chemical powder. Carbon dioxide (CO2). Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Material name: NOVOCOAT™ SC2200 RAPID SET PIPE COATING PART B

5873 Version #: 02 Revision date: 10-20-2021 Issue date: 06-15-2020

Special protective equipment and precautions for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Fire fighting

equipment/instructions

In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers. Cool containers exposed to flames with water until well after the fire is out. Water runoff can cause

environmental damage.

Specific methods
General fire hazards

In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Extinguish all flames in the vicinity. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not get this material in contact with eyes. When using do not eat or drink. Do not get this material in contact with skin. Do not taste or swallow. Avoid prolonged exposure. Use personal protective equipment as required. Do not get this material on clothing. Observe good industrial hygiene practices. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from food, drink and animal feedingstuffs.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
PHENOL (CAS 108-95-2)	PEL	19 mg/m3	
		5 ppm	
US. ACGIH Threshold Limit Val	ues		
Components	Туре	Value	
PHENOL (CAS 108-95-2)	TWA	5 ppm	
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	
PHENOL (CAS 108-95-2)	Ceiling	60 mg/m3	
		15.6 ppm	
	TWA	19 mg/m3	
		5 ppm	

Material name: NOVOCOAT™ SC2200 RAPID SET PIPE COATING PART B 5873 Version #: 02 Revision date: 10-20-2021 Issue date: 06-15-2020

US. Workplace Environmental Exposure Level (WEEL) Guides Components Type Value BENZYL ALCOHOL (CAS 100-51-6) TWA 44.2 mg/m3 10 ppm TRIENTINE (CAS 112-24-3) TWA 6 mg/m3 1 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
PHENOL (CAS 108-95-2)	250 mg/g	Phenol with hydrolysis	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

PHENOL (CAS 108-95-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

PHENOL (CAS 108-95-2) Skin designation applies.

US - Tennessee OELs: Skin designation

PHENOL (CAS 108-95-2) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

PHENOL (CAS 108-95-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

PHENOL (CAS 108-95-2) Can be absorbed through the skin.

US WEEL Guides: Skin designation

TRIENTINE (CAS 112-24-3)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

PHENOL (CAS 108-95-2) Can be absorbed through the skin.

Appropriate engineering

controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical goggles and face shield are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Skin protection should include disposable chemical resistant coveralls with hoods. Hand protection

should include appropriate chemical resistant disposable gloves, such as nitrile rubber.

Respiratory protectionIf in spray application, respiratory protection should include at a minimum a fullface air purifying

respirator (APR) with combination particulate (P100) and organic vapor (OV) cartridges. A full-face APR has an assigned protection factor (APF) of 50, as designated by OSHA. As a substitute, a PAPF

with a loose-fitting hood could be used as respiratory protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygieneDo not get in eyes. Do not get this material in contact with skin. Do not get this material on clothing. Wash hands before breaks and immediately after handling the product. Keep away from

couling. Wash hards before breaks and infinediately after handling the product. Reep away nor

food and drink.

9. Physical and chemical properties

Appearance Liquid.
Physical state Liquid.
Form Liquid.
Color Light yellow
Odor Sulphurous.
Odor threshold Not available.
pH Not available.

Melting point/freezing point 4.64 °F (-15.2 °C) estimated

Initial boiling point and

boiling range

359.15 °F (181.75 °C) estimated

Flash point

250.0 °F (121.1 °C) estimated

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower 3 % estimated

(%)

Flammability limit -

10 % estimated

upper (%)

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Not available. Vapor pressure Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature 640 °F (337.78 °C) estimated

Decomposition temperature Not available. Not available. **Viscosity**

Other information

Density 8.74 lb/gal estimated Specific gravity 1.05 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Stable at normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization can occur with elevated temperatures.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Acids. Alkaline metals. Amines. Peroxides. Fluorine. Chlorine. Phenols. Strong acids, alkalies and **Incompatible materials**

oxidizing agents.

Hazardous decomposition

products

Toxic gas. If product is burned hazardous gases such as oxides of carbon and nitrogen and various

hydrocarbons may be produced. Upon combustion, oxides of chlorine may be released.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. Skin contact Causes severe skin burns and eye damage.

Eye contact Causes severe eye burns. Causes serious eye damage

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Irritation of eyes and mucous membranes.

Information on toxicological effects

Acute toxicity

Material name: NOVOCOAT™ SC2200 RAPID SET PIPE COATING PART B 5873 Version #: 02 Revision date: 10-20-2021 Issue date: 06-15-2020 Components Species Test Results

BENZYL ALCOHOL (CAS 100-51-6)

<u>Acute</u> Dermal

LD50 Rabbit 2000 mg/kg

Inhalation

LC50 Rat 1000 mg/l, 8 Hours

Skin corrosion/irritation Irritating and may cause redness and pain.

Serious eye damage/eye

Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled

Skin sensitization May cause an allergic skin reaction. **Germ cell mutagenicity** Suspected of causing genetic defects.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. This product

contains crystalline silica. Silica is a known carcinogen; however in this encapsulated form the

normal routes of exposure are unavailable.

IARC Monographs. Overall Evaluation of Carcinogenicity

PHENOL (CAS 108-95-2)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects

Specific target organ toxicity Not classified.

- single exposure

Not classifica.

Specific target organ toxicity

- repeated exposure

Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

NOVOCOAT™ SC2200 RAPID SET PIPE COATING PART B

12. Ecological information

Ecotoxicity Harmful to aquatic life. Components of this product are hazardous to aquatic life. Accumulation in

aquatic organisms is expected.

Product Species Test Results

Aquatic

Crustacea EC50 Daphnia 900.3535 mg/l, 48 hours estimated

Components Species Test Results

BENZYL ALCOHOL (CAS 100-51-6)

Aquatic

Fish LC50 Bluegill (Lepomis macrochirus) 10 mg/l, 96 hours

PHENOL (CAS 108-95-2)

Aquatic

Crustacea EC50 Water flea (Daphnia obtusa) 4.7 - 6.4 mg/l, 48 hours
Fish LC50 Asiatic knifefish (Notopterus notopterus) 8 - 8.25 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

BENZYL ALCOHOL 1.1
PHENOI 1.46

^{*} Estimates for product may be based on additional component data not shown.

Mobility in soil No data available.

Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsDispose of contents/container in accordance with local/regional/national/international regulations.

This product, in its present state, when discarded or disposed of, is not a hazardous wasted according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria

for hazardous waste.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues /

unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

UN number UN3334

UN proper shipping name Regulated Liquid, n.o.s. (Mercaptan Terminated Polymer)

Transport hazard class(es)

Class 9
Subsidiary risk Packing group III
Environmental hazards No.
ERG Code 6L

Special precautions for

user

Not available.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG


Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

IATA



15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

PHENOL (CAS 108-95-2) Listed.

SARA 304 Emergency release notification

PHENOL (CAS 108-95-2) 1000 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
DUENOL	100.05.3	1000	·	F00	10000

PHENOL 108-95-2 1000 500 10000

SARA 311/312

Hazardous chemical

Classified hazard Skin corrosion or irritation

Yes

categories Serious eye damage or eye irritation Respiratory or skin sensitization

Germ cell mutagenicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
PHENOL	108-95-2	1 - 10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

PHENOL (CAS 108-95-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated. **(SDWA)**

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

PHENOL (CAS 108-95-2) Low priority

US state regulations

California Proposition 65



WARNING: California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

PHENOL (CAS 108-95-2)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

Country(s) or region Inventory name On inventory (yes/no)*

Philippines Philippine Inventory of Chemicals and Chemical Substances Ye

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 06-15-2020 **Revision date** 10-20-2021

Version # 02

NFPA ratings Health: 4

Flammability: 0 Instability: 0

References EPA: AQUIRE database

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Composition / Information on Ingredients: Disclosure Overrides

Physical & Chemical Properties: Multiple Properties

GHS: Classification

Material name: NOVOCOAT™ SC2200 RAPID SET PIPE COATING PART B 5873 Version #: 02 Revision date: 10-20-2021 Issue date: 06-15-2020