SAFETY DATA SHEET



1. Identification

Product identifier BLACKHAWK™ R-17-A-73 LV ASPHALT COATING

Other means of identification None. Recommended use Coatings **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

2829 Lakeland Drive **Address** Jackson, MS 39232

USA

After hours telephone

number

1-800-222-7122

Normal work hours

telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards Flammable liquids Category 2 **Health hazards** Skin corrosion/irritation Category 2 Germ cell mutagenicity Category 1B

Carcinogenicity

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes skin irritation. May cause genetic defects. May cause

cancer. May cause drowsiness or dizziness.

Precautionary statement

Prevention Obtain special instructions before use. Wash thoroughly after handling. Use only outdoors or in a

well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Do not handle until all safety precautions have been read and

Category 1B

understood. Ground/bond container and receiving equipment.

Response IF ON SKIN: Wash with plenty of soap and water. Specific treatment see Section 4 of this SDS.

Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish. IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. Do NOT induce vomiting. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If skin irritation occurs, seek medical advice/attention. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel

unwell.

Storage Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Not available.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT, OXIDIZED		64742-93-4	55 - 65
SOLVENT NAPHTHA (PETROLEUM LIGHT ALIPH.),	64742-89-8	35 - 45

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device. Get medical attention if symptoms occur.

Skin contact Wash off with soap and plenty of water. For minor skin contact, avoid spreading material on

unaffected skin. If skin irritation occurs: Get medical advice/attention.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO

NOT delay irrigation or attempt to remove the lens. Remove contact lenses, if present and easy to

do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Aspiration may cause pulmonary edema and pneumonitis. If ingestion of a large amount does

occur, call a poison control center immediately.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

In case of shortness of breath, give oxygen. Symptoms may be delayed.

Foam. Dry powder. Carbon dioxide (CO2). Extinguish with water fog.

Do not use water jet as an extinguisher, as this will spread the fire.

IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media
Specific hazards arising from

Fire may produce irritating, corrosive and/or toxic gases.

Special protective equipment and precautions for

firefighters

the chemical

Fire fighting equipment/instructions

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective

clothing will only provide limited protection.

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue. Water runoff can cause environmental damage.

In the event of fire, cool tanks with water spray. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Remove sources of ignition. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

Methods and materials for containment and cleaning up

Dike far ahead of spill for later disposal. Cover with DRY earth, DRY sand, or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain. Collect spillage.

Prevent product from entering drains.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

7. Handling and storage

Precautions for safe handling

DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. All equipment used when handling the product must be grounded. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Do not use in areas without adequate ventilation. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash thoroughly after handling. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place. Keep container tightly closed. Use care in handling/storage.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. (CAS 64742-89-8)	PEL	400 mg/m3	
		100 ppm	
U.S NIOSH			
Components	Туре	Value	
ASPHALT, OXIDIZED (CAS 64742-93-4)	REL	5 mg/m3	
US. NIOSH: Pocket Guide to Che	emical Hazards		

Components	Туре	Value
SOLVENT NAPHTHA	TWA	400 mg/m3
(PETROLELIM) LIGHT		

ALIPH. (CAS 64742-89-8)

100 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical goggles are recommended.

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Wear appropriate chemical resistant clothing. Chemical resistant gloves.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Not available.

Material name: BLACKHAWK™ R-17-A-73 LV ASPHALT COATING

6853 Version #: 02 Revision date: 10-12-2021 Issue date: 11-20-2020 3/9 General hygiene considerations

When using do not smoke. When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance

Physical stateSolid.FormLiquid.

Color Dark brown Black.
Odor Hydrocarbon-like.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and

boiling range

240 - 315 °F (115.56 - 157.22 °C)

Flash point 69.0 - 73.0 °F (20.6 - 22.8 °C) Tag Open Cup ASTM D1310

Evaporation rate 0.2

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure 21.00 mm Hg at 100F

Vapor density > 4

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 550 °F (287.78 °C) estimated

Decomposition temperatureNot available.Viscosity320 cStViscosity temperature77 °F (25 °C)

Other information

Specific gravity 0.899 - 0.93 @60°F(15°C) ASTM D1298

VOC < 500 lb/gal

10. Stability and reactivity

Reactivity Not available.

Chemical stability Stable under normal temperature conditions. **Possibility of hazardous** Hazardous polymerization does not occur.

Conditions to avoidHeat, flames and sparks.Incompatible materialsStrong oxidizing agents.Hazardous decompositionIrritants. Toxic gas.

products

reactions

11. Toxicological information

Information on likely routes of exposure

Inhalation Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis Skin contact

Eye contact Causes eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

Not classified. Acute toxicity

Test Results Components **Species**

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. (CAS 64742-89-8)

Acute

Inhalation

LC50 Rat 61 mg/l, 4 Hours

Skin corrosion/irritation May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Serious eye damage/eye

May be irritating to eyes.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available. Skin sensitization Irritating to skin.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT, OXIDIZED (CAS 64742-93-4) 2A Probably carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity

- single exposure

Not available.

Specific target organ toxicity

Not available.

- repeated exposure

Not classified. **Aspiration hazard**

Further information Symptoms may be delayed.

12. Ecological information

Components of this product are hazardous to aquatic life. Accumulation in aquatic organisms is **Ecotoxicity**

expected. Not expected to be harmful to aquatic organisms.

Product Species **Test Results**

BLACKHAWK™ R-17-A-73 LV ASPHALT COATING

Aquatic

EC50 Crustacea Daphnia 8.8235 mg/l, 48 hours estimated Fish LC50 Fish 21.1765 mg/l, 96 hours estimated

^{*} Estimates for product may be based on additional component data not shown.

Test Results Components **Species**

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. (CAS 64742-89-8)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours

Fish LC50 Rainbow trout, donaldson trout 8.8 mg/l, 96 hours

(Oncorhynchus mykiss)

8.8 mg/l, 96 hours

Persistence and degradability Not available. **Bioaccumulative potential** Not available. Mobility in soil Not available. Other adverse effects Not available.

13. Disposal considerations

Disposal instructions Contract with a disposal operator licensed by the Law on Disposal and Cleaning. Dispose of this

> material and its container to hazardous or special waste collection point. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose in accordance with all applicable

regulations.

Not available.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Waste from residues / unused products

Dispose of in accordance with local regulations.

Contaminated packaging

Offer rinsed packaging material to local recycling facilities.

14. Transport information

DOT

UN number UN1999 **UN proper shipping name** Tars, liquid

Transport hazard class(es)

3 Class **Subsidiary risk** Label(s) 3 ΙΙ **Packing group Environmental hazards**

> Marine pollutant No

Special precautions for

user

Special provisions B1, B13, IB3, T1, TP3

Packaging exceptions 150 Packaging non bulk 203 Packaging bulk 242

IATA

UN number UN1999 **UN proper shipping name** Tars, liquid

Transport hazard class(es)

Class 3 **Subsidiary risk Packing group** TT **Environmental hazards** No. **ERG Code**

Special precautions for Not available.

user

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

6853 Version #: 02 Revision date: 10-12-2021 Issue date: 11-20-2020

Material name: BLACKHAWK™ R-17-A-73 LV ASPHALT COATING

^{*} Estimates for product may be based on additional component data not shown.

IMDG

UN1999 **UN number UN** proper shipping name Tars, liquid

Transport hazard class(es)

Class 3 **Subsidiary risk Packing group** ΙΙ **Environmental hazards**

Marine pollutant No. **EmS** F-A, S-G **Special precautions for** Not available.

Transport in bulk according to Not available. Annex II of MARPOL 73/78 and the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Yes

Hazardous chemical

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation

Serious eye damage or eye irritation

Germ cell mutagenicity Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65

California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT, OXIDIZED (CAS 64742-93-4) Listed: January 1, 1990

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. (CAS 64742-89-8)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

 Issue date
 11-20-2020

 Revision date
 10-12-2021

Version # 02

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Health: 2

Flammability: 3 Instability: 0

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

References ACGIH

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Composition / Information on Ingredients: Ingredients

Material name: BLACKHAWK™ R-17-A-73 LV ASPHALT COATING

SDS US 6853 Version #: 02 Revision date: 10-12-2021 Issue date: 11-20-2020