

1. Identification

Product identifier	BLACKHAWK™ 5330 ROOFING ADHESIVE
Other means of identification	None.
Recommended use	Not available.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Company Name	ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.
Address	2829 Lakeland Drive Jackson, MS 39232 USA
After hours telephone number	1-800-222-7122
Normal work hours telephone number	1-877-982-7667
Website	www.ergonarmor.com
E-mail	sds@ergon.com
Emergency 24-hour telephone number	CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887
Information on operation hours	8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Germ cell mutagenicity	Category 1
	Carcinogenicity	Category 1
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Causes serious eye irritation. May cause genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure. Flammable liquid and vapor. May cause drowsiness or dizziness. Causes skin irritation.
Precautionary statement	
Prevention	Keep container tightly closed. Take precautionary measures against static discharge. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs, seek medical advice/attention. If eye irritation persists: Get medical advice/attention. Specific treatment see Section 4 of this SDS. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. In case of fire: Use appropriate media for extinction. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell.

Storage Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations. See section 13 of this SDS for disposal instructions.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	30 - 40
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY		64742-48-9	20 - 30
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.		64742-95-6	1 - 10
1,2,4-TRIMETHYLBENZENE		95-63-6	0 - 5
BENZENE		71-43-2	< 1
QUARTZ		14808-60-7	< 1
Other components below reportable levels			35.48

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing difficulties, oxygen may be necessary. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if needed.

Skin contact For hot product, immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. For minor skin contact, avoid spreading material on unaffected skin. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth thoroughly. Call a POISON CENTER or doctor/physician. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed Not available.

Indication of immediate medical attention and special treatment needed In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Foam. Carbon dioxide (CO2). Water fog. Dry chemical powder.

Unsuitable extinguishing media Do not use water jet.

Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Do not get water inside container. Some of these materials, if spilled, may evaporate leaving a flammable residue.
Specific methods	In the event of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Never return spills in original containers for re-use.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

7. Handling and storage

Precautions for safe handling	Avoid heat, sparks, open flames and other ignition sources. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Do not use in areas without adequate ventilation. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings.
Conditions for safe storage, including any incompatibilities	Store in a well-ventilated place. Keep container closed. Keep container dry. Keep away from food, drink and animal feedingstuffs. Keep out of reach of children. Use care in handling/storage.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
BENZENE (CAS 71-43-2)	STEL	5 ppm
	TWA	1 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m ³	Respirable dust.

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
BENZENE (CAS 71-43-2)	Ceiling	25 ppm
	TWA	10 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m ³	Respirable.
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)	TWA	25 ppm	
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m ³	Inhalable fume.

US. ACGIH Threshold Limit Values Components

Components	Type	Value	Form
BENZENE (CAS 71-43-2)	STEL	2.5 ppm	
	TWA	0.5 ppm	
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards Components

Components	Type	Value	Form
1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)	TWA	125 mg/m3	
		25 ppm	
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.
BENZENE (CAS 71-43-2)	STEL	1 ppm	
	TWA	0.1 ppm	
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
BENZENE (CAS 71-43-2)	25 µg/g	S-Phenylmercapturic acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

BENZENE (CAS 71-43-2)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

BENZENE (CAS 71-43-2)

Can be absorbed through the skin.

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection**Hand protection**

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

Other

It is a good industrial hygiene practice to minimize skin contact. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards

Not available.

General hygiene considerations

When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties**Appearance****Physical state**

Liquid.

Form

Liquid.

Color

Not available.

Odor

Not available.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling range

212 °F (100 °C)

Flash point	100.0 - 140.0 °F (37.8 - 60.0 °C) Cleveland Open Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific gravity	1.08 - 1.2
VOC	< 250 g/l

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport
Chemical stability	Stable at normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Irritants. Carbon oxides. Sulphur oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

Acute toxicity Not classified.

Components	Species	Test Results
1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg
Oral		
LD50	Rat	6 g/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization Not a skin sensitizer.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

BENZENE (CAS 71-43-2) 1 Carcinogenic to humans.

QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

BENZENE (CAS 71-43-2) Cancer

QUARTZ (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

BENZENE (CAS 71-43-2) Known To Be Human Carcinogen.

QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity Not classified.

Specific target organ toxicity - single exposure Central nervous system. May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure May cause damage to organs through prolonged or repeated exposure by inhalation.

Aspiration hazard Not classified.

Chronic effects Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Product	Species	Test Results	
BLACKHAWK™ 5330 ROOFING ADHESIVE			
Aquatic			
Crustacea	EC50	Daphnia	4980.9971 mg/l, 48 hours estimated
Fish	LC50	Fish	369.4059 mg/l, 96 hours estimated
Components			
1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	7.19 - 8.28 mg/l, 96 hours
BENZENE (CAS 71-43-2)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	8.76 - 15.6 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	7.2 - 11.7 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	Not available.
Bioaccumulative potential	Not available.
Partition coefficient n-octanol / water (log Kow)	
BENZENE	2.13
Mobility in soil	Not available.
Other adverse effects	Not available.

13. Disposal considerations

Disposal instructions	Dispose of contents/container in accordance with local/regional/national/international regulations. If discarded, this product is considered a RCRA ignitable waste, D001.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	
UN number	UN1999
UN proper shipping name	Tars, liquid
Transport hazard class(es)	
Class	Combustible Liquid
Subsidiary risk	-
Label(s)	3
Packing group	III
Environmental hazards	
Marine pollutant	No
Special precautions for user	If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous material.
Special provisions	B1, B13, IB3, T1, TP3
Packaging exceptions	150
Packaging non bulk	203
Packaging bulk	242

IATA

UN number	UN1999
UN proper shipping name	Tars, liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Not available.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1999
UN proper shipping name	Tars, liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

IATA; IMDG



Further information

If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous material. If shipped by vessel in individual containers that are less than 7.9 gallons (30 L) each, then IMDG 2.3.2.5 exception applies: Not regulated as a hazardous material.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.
CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BENZENE (CAS 71-43-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

BENZENE (CAS 71-43-2)	Cancer
QUARTZ (CAS 14808-60-7)	Cancer
BENZENE (CAS 71-43-2)	Central nervous system
QUARTZ (CAS 14808-60-7)	lung effects
BENZENE (CAS 71-43-2)	Blood
QUARTZ (CAS 14808-60-7)	immune system effects
BENZENE (CAS 71-43-2)	Aspiration
QUARTZ (CAS 14808-60-7)	kidney effects
BENZENE (CAS 71-43-2)	Skin
	Eye
	respiratory tract irritation
	Flammability

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312

Yes

Hazardous chemical

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Serious eye damage or eye irritation
Germ cell mutagenicity
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2,4-TRIMETHYLBENZENE	95-63-6	0 - 5
BENZENE	71-43-2	< 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE (CAS 71-43-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

WARNING: This product contains chemicals known to the State of California to cause cancer and reproductive harm.

California Proposition 65

California Proposition 65 - CRT: Listed date/Carcinogenic substance

BENZENE (CAS 71-43-2) Listed: February 27, 1987

QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

California Proposition 65 - CRT: Listed date/Developmental toxin

BENZENE (CAS 71-43-2) Listed: December 26, 1997

California Proposition 65 - CRT: Listed date/Male reproductive toxin

BENZENE (CAS 71-43-2) Listed: December 26, 1997

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)

BENZENE (CAS 71-43-2)

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS 64742-48-9)

QUARTZ (CAS 14808-60-7)

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. (CAS 64742-95-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	11-24-2020
Revision date	11-23-2021
Version #	02
Further information	HMIS® is a registered trade and service mark of the NPCA.
NFPA ratings	Health: 2 Flammability: 2 Instability: 0

References

ACGIH
EPA: AQUIRE database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents
HSDB® - Hazardous Substances Data Bank
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

Composition / Information on Ingredients: Disclosure Overrides
Physical & Chemical Properties: Multiple Properties
HazReg Data: International Inventories