# SAFETY DATA SHEET



### 1. Identification

**Product identifier** BLACKHAWK™ 5400 FLASHING CEMENT SG

Other means of identification None.

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

**Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

**Address** 2829 Lakeland Drive Jackson, MS 39232

**USA** 

After hours telephone

number

1-800-222-7122

**Normal work hours** 

telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

**Emergency 24-hour** telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

8:00 a.m. to 5:00 p.m.

# 2. Hazard(s) identification

**Physical hazards** Flammable liquids Category 3 **Health hazards** Skin corrosion/irritation Category 2 Germ cell mutagenicity Category 1 Carcinogenicity Category 1

Specific target organ toxicity, single exposure Category 3 narcotic effects

**Environmental hazards** Not classified. **OSHA** defined hazards Not classified.

**Label elements** 



Signal word Danger

**Hazard statement** May cause genetic defects. May cause cancer. Flammable liquid and vapor. Causes skin irritation.

May cause drowsiness or dizziness.

**Precautionary statement** 

**Prevention** Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing

dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood.

If skin irritation occurs: Get medical advice/attention. Specific treatment see Section 4 of this SDS. Response

In case of fire: Use appropriate media for extinction. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Material name: BLACKHAWK™ 5400 FLASHING CEMENT SG

**Storage** Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

See section 13 of this SDS for disposal instructions.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	35 - 45
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY		64742-48-9	20 - 30
BENZENE		71-43-2	< 1
QUARTZ		14808-60-7	< 1

#### 4. First-aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

> artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device. Get medical attention if symptoms occur.

Skin contact Wash off with soap and plenty of water. For minor skin contact, avoid spreading material on

unaffected skin. If skin irritation occurs: Get medical advice/attention.

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO Eye contact

NOT delay irrigation or attempt to remove the lens. Remove contact lenses, if present and easy to

do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Aspiration may cause pulmonary edema and pneumonitis. If ingestion of a large amount does

occur, call a poison control center immediately.

Not available.

**Most important** 

symptoms/effects, acute and

delayed

**Indication of immediate** medical attention and special

treatment needed

In case of shortness of breath, give oxygen. Symptoms may be delayed.

**General information** IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Foam. Dry powder. Carbon dioxide (CO2). Extinguish with water fog. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Fire may produce irritating, corrosive and/or toxic gases.

**Special protective equipment** 

and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with

Fire fighting

equipment/instructions

face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue.

Water runoff can cause environmental damage.

**Specific methods** In the event of fire, cool tanks with water spray. Self-contained breathing apparatus and full

protective clothing must be worn in case of fire.

Material name: BLACKHAWK™ 5400 FLASHING CEMENT SG

5037 Version #: 02 Revision date: 11-23-2021 Issue date: 11-25-2020

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Methods and materials for Remove sources of ignition. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

**Methods and materials for** Di **containment and cleaning up** materials for

Dike far ahead of spill for later disposal. Cover with DRY earth, DRY sand, or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain. Collect spillage. Prevent product from entering drains.

Never return spills in original containers for re-use.

**Environmental precautions** 

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

# 7. Handling and storage

**Precautions for safe handling** 

DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. All equipment used when handling the product must be grounded. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Do not use in areas without adequate ventilation. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash thoroughly after handling. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place. Keep container tightly closed. Use care in handling/storage.

# 8. Exposure controls/personal protection

#### **Occupational exposure limits**

US. OSHA Specifically Regulated Components	Substances (29 CFR 1910.1 Type	.001-1050) Value	
BENZENE (CAS 71-43-2)	STEL	5 ppm	
	TWA	1 ppm	
US. OSHA Table Z-1 Limits for Ai	r Contaminants (29 CFR 19:	LO.1000)	
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-2 (29 CFR 191	.0.1000)		
Components	Туре	Value	
BENZENE (CAS 71-43-2)	Ceiling	25 ppm	
	TWA	10 ppm	
US. OSHA Table Z-3 (29 CFR 191	.0.1000)		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.
BENZENE (CAS 71-43-2)	STEL	2.5 ppm	
	TWA	0.5 ppm	
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.
BENZENE (CAS 71-43-2)	STEL	1 ppm	
	TWA	0.1 ppm	
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Material name: BLACKHAWK™ 5400 FLASHING CEMENT SG

5037 Version #: 02 Revision date: 11-23-2021 Issue date: 11-25-2020 3 / 9

#### **Biological limit values**

# **ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
BENZENE (CAS 71-43-2)	25 μg/g	S-Phenylmerca pturic acid	Creatinine in urine	*

<sup>\* -</sup> For sampling details, please see the source document.

### **Exposure guidelines**

**US - California OELs: Skin designation** 

BENZENE (CAS 71-43-2) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation** 

BENZENE (CAS 71-43-2) Can be absorbed through the skin.

**Appropriate engineering** controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical goggles are recommended.

Skin protection

**Hand protection** Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Wear appropriate chemical resistant clothing. Chemical resistant gloves.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Not available.

**General hygiene** considerations

When using do not smoke. When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Handle in

accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

**Appearance** Viscous liquid

Physical state Liquid. **Form** Liquid.

Color Brown to Black Odor Mild Petroleum Odor

**Odor threshold** Not available. Not available. Hq Melting point/freezing point Not available. Initial boiling point and 300 °F (148.89 °C)

boiling range

Flash point 100.0 - 140.0 °F (37.8 - 60.0 °C) Cleveland Open Cup

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

**Flammability limit - lower** Not available.

(%)

Flammability limit -

upper (%)

Not available.

**Explosive limit - lower** 

(%)

Not available.

**Explosive limit - upper** 

(%)

Not available.

Vapor pressure Not available. Vapor density Not available. Relative density Not available.

SDS US

5037 Version #: 02 Revision date: 11-23-2021 Issue date: 11-25-2020

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot availableDecomposition temperatureNot availableViscosityNot available

Other information

**Specific gravity** 1.18 - 1.27 **VOC** < 250 g/l

# 10. Stability and reactivity

**Reactivity** Not available.

**Chemical stability** Stable under normal temperature conditions. **Possibility of hazardous** Hazardous polymerization does not occur.

reactions

Conditions to avoidHeat, flames and sparks.Incompatible materialsStrong oxidizing agents.Hazardous decompositionIrritants. Toxic gas.

products

# 11. Toxicological information

### Information on likely routes of exposure

**Inhalation** Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea

**Skin contact** Causes skin irritation. Frequent or prolonged contact may defat and dry the skin, leading to

discomfort and dermatitis.

**Eye contact** May be irritating to eyes.

**Ingestion** May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Not available.

Symptoms related to the physical, chemical and

physical, chemical and toxicological characteristics

#### Information on toxicological effects

**Acute toxicity** Not classified.

**Skin corrosion/irritation**Causes skin irritation. **Serious eye damage/eye**May be irritating to eyes.

irritation

### Respiratory or skin sensitization

Respiratory sensitizationNot a vailable.Skin sensitizationNot a skin sensitizer.Germ cell mutagenicityMay cause genetic defects.

**Carcinogenicity** May cause cancer.

### IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

BENZENE (CAS 71-43-2) 1 Carcinogenic to humans. QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

# OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

BENZENE (CAS 71-43-2) Cancer
QUARTZ (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

BENZENE (CAS 71-43-2) Known To Be Human Carcinogen. QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

**Reproductive toxicity** Not classified.

SDS US

Specific target organ toxicity

- single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity

- repeated exposure

Not available.

Not classified. **Aspiration hazard** 

**Chronic effects** Prolonged exposure may cause chronic effects.

# 12. Ecological information

**Ecotoxicity** Components of this product are hazardous to aquatic life. Accumulation in aquatic organisms is

expected. Not expected to be harmful to aquatic organisms.

Product		Species	Test Results
BLACKHAWK™ 5400 F	LASHING CEMENT	SG	
Aquatic			
Crustacea	EC50	Daphnia	11307.1426 mg/l, 48 hours estimated
Fish	LC50	Fish	46903.2305 mg/l, 96 hours estimated
Components		Species	Test Results
BENZENE (CAS 71-43-	-2)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	8.76 - 15.6 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	7.2 - 11.7 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Persistence and degradability** Not available. **Bioaccumulative potential** Not available.

Partition coefficient n-octanol / water (log Kow)

**BENZENE** 2.13

Mobility in soil Not available. Other adverse effects Not available.

### 13. Disposal considerations

**Disposal instructions** Contract with a disposal operator licensed by the Law on Disposal and Cleaning. Dispose of this

material and its container to hazardous or special waste collection point. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose in accordance with all applicable

regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Waste from residues /

unused products

Dispose of in accordance with local regulations.

Contaminated packaging Offer rinsed packaging material to local recycling facilities.

### 14. Transport information

DOT

user

UN1999 **UN number UN proper shipping name** Tars, liquid

Transport hazard class(es)

Class Combustible Liquid

**Subsidiary risk** Label(s) 3 Packing group III**Environmental hazards** 

> Marine pollutant No

Special precautions for If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous

material.

Special provisions B1, B13, IB3, T1, TP3

5037 Version #: 02 Revision date: 11-23-2021 Issue date: 11-25-2020

**Packaging exceptions** 150

Material name: BLACKHAWK™ 5400 FLASHING CEMENT SG

Packaging non bulk 203 Packaging bulk 242

**IATA** 

UN number UN1999
UN proper shipping name Tars, liquid
Transport hazard class(es)

Class 3
Subsidiary risk Packing group III
Environmental hazards No.
ERG Code 3L

**Special precautions for** Not available.

user

Other information

**Passenger and cargo** 

aircraft

Allowed with restrictions.

Cargo aircraft only All

Allowed with restrictions.

**IMDG** 

**UN number** UN1999 **UN proper shipping name** Tars, liquid

Transport hazard class(es)
Class 3
Subsidiary risk -

Packing group Environmental hazards

Marine pollutant No.

EmS F-E, S-E

Special precautions for Not available.

III

user

Transport in bulk according to Not available.

Annex II of MARPOL 73/78 and the IBC Code

IATA; IMDG



**Further information**If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous material. If shipped by vessel in individual containers that are less than 7.9 gallons (30 L) each,

then IMDG 2.3.2.5 exception applies: Not regulated as a hazardous material.

# 15. Regulatory information

**US federal regulations**This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

BENZENE (CAS 71-43-2) Listed.

**SARA 304 Emergency release notification** 

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

BENZENE (CAS 71-43-2) Cancer

QUARTZ (CAS 14808-60-7) Cancer

BENZENE (CAS 71-43-2) Central nervous system

QUARTZ (CAS 14808-60-7) lung effects BENZENE (CAS 71-43-2) Blood

BENZENE (CAS 71-43-2) Aspiration
QUARTZ (CAS 14808-60-7) kidney effects

BENZENE (CAS 71-43-2) Skin Eye

respiratory tract irritation

immune system effects

Flammability

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

# **SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312** Yes

QUARTZ (CAS 14808-60-7)

**Hazardous chemical** 

**Classified hazard** Flammable (gases, aerosols, liquids, or solids)

**categories** Skin corrosion or irritation Germ cell mutagenicity

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
BENZENE	71-43-2	< 1	

#### Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE (CAS 71-43-2)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

**US state regulations** WARNING: This product contains chemicals known to the State of California to cause cancer and

reproductive harm.

### **California Proposition 65**

### California Proposition 65 - CRT: Listed date/Carcinogenic substance

BENZENE (CAS 71-43-2) Listed: February 27, 1987 QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

### California Proposition 65 - CRT: Listed date/Developmental toxin

BENZENE (CAS 71-43-2) Listed: December 26, 1997

### California Proposition 65 - CRT: Listed date/Male reproductive toxin

BENZENE (CAS 71-43-2) Listed: December 26, 1997

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

BENZENE (CAS 71-43-2)

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS 64742-48-9)

QUARTZ (CAS 14808-60-7)

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes

Country(s) or region **Inventory name** On inventory (yes/no)\* Korea Existing Chemicals List (ECL) New Zealand **New Zealand Inventory** Yes **Philippines** Yes

Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Chemical Substance Inventory (TCSI) **Taiwan** Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

# 16. Other information, including date of preparation or last revision

11-25-2020 **Issue date Revision date** 11-23-2021

Version # 02

**Further information** HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Flammability: 2

Instability: 0

References **ACGIH** 

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer Additional information is given in the Material Safety Data Sheet. The information in the sheet was

> written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless

specified in the text.

**Revision information** Composition / Information on Ingredients: Disclosure Overrides

Physical & Chemical Properties: Multiple Properties

Transport Information: Proper Shipping Name/Packing Group

HazReg Data: International Inventories

Material name: BLACKHAWK™ 5400 FLASHING CEMENT SG

5037 Version #: 02 Revision date: 11-23-2021 Issue date: 11-25-2020

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).