## SAFETY DATA SHEET



## 1. Identification

**Product identifier BLACKHAWK™ 5500 SEAL KOTE LIGHT** 

Other means of identification None.

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

**Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

**Address** 2829 Lakeland Drive Jackson, MS 39232

**USA** 

After hours telephone

number

1-800-222-7122

**Normal work hours** 

telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

**Emergency 24-hour** telephone number

Information on operation

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

8:00 a.m. to 5:00 p.m.

hours

## 2. Hazard(s) identification

**Physical hazards** Flammable liquids Category 3 **Health hazards** Skin corrosion/irritation Category 2 Germ cell mutagenicity Category 1 Carcinogenicity Category 1

Specific target organ toxicity, single exposure Category 3 narcotic effects

**Environmental hazards** Not classified. **OSHA** defined hazards Not classified.

**Label elements** 



Signal word Danger

**Hazard statement** May cause genetic defects. May cause cancer. Flammable liquid and vapor. Causes skin irritation.

May cause drowsiness or dizziness.

**Precautionary statement** 

**Prevention** Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing

dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Ground/bond container and receiving equipment. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all

safety precautions have been read and understood.

IF exposed or concerned: Call a POISON CENTER/doctor. If skin irritation occurs: Get medical Response

> advice/attention. Specific treatment see Section 4 of this SDS. In case of fire: Use appropriate media for extinction. Take off contaminated clothing and wash before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF ON

SKIN: Wash with plenty of soap and water.

Material name: BLACKHAWK™ 5500 SEAL KOTE LIGHT

Storage Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal** 

See section 13 of this SDS for disposal instructions.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
ASPHALT, OXIDIZED		64742-93-4	45 - 55
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY		64742-48-9	20 - 30
BENZENE		71-43-2	< 1
QUARTZ		14808-60-7	< 1
Other components below reportable I	evels		19.0509

## 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing

> difficulties, oxygen may be necessary. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if

needed.

Skin contact For hot product, immediately immerse in or flush the affected area with large amounts of cold

water to dissipate heat. For minor skin contact, avoid spreading material on unaffected skin. Wash

off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO **Eye contact** 

NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and

persists.

Not available.

**Ingestion** Rinse mouth thoroughly. Call a POISON CENTER or doctor/physician. Do not induce vomiting

without advice from poison control center. If vomiting occurs, keep head low so that stomach

content doesn't get into the lungs.

Most important

symptoms/effects, acute and

delayed

**Indication of immediate** medical attention and special

treatment needed **General information** 

In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give

oxygen. Keep victim warm. Keep victim under observation. Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Foam. Carbon dioxide (CO2). Water fog. Dry chemical powder.

Do not use water jet.

Specific hazards arising from

the chemical

Fire may produce irritating, corrosive and/or toxic gases.

**Special protective equipment** 

and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective

Fire fighting

equipment/instructions

clothing will only provide limited protection. In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective

equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Do not get water inside container. Some of these materials, if spilled, may evaporate leaving a flammable residue.

**Specific methods** In the event of fire and/or explosion do not breathe fumes.

Material name: BLACKHAWK™ 5500 SEAL KOTE LIGHT

SDS US 5034 Version #: 02 Revision date: 11-23-2021 Issue date: 11-25-2020

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Never return spills in original containers for re-use.

**Environmental precautions** 

Prevent further leakage or spillage if safe to do so. Do not contaminate water. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

## 7. Handling and storage

**Precautions for safe handling** 

Avoid heat, sparks, open flames and other ignition sources. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Do not use in areas without adequate ventilation. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container closed. Keep container dry. Keep away from food, drink and animal feedingstuffs. Keep out of reach of children. Use care in handling/storage.

## 8. Exposure controls/personal protection

#### **Occupational exposure limits**

US. OSHA Specifically Regulated Components	I Substances (29 CFR 1910.1) Type	001-1050) Value	
BENZENE (CAS 71-43-2)	STEL	5 ppm	
/	TWA	1 ppm	
US. OSHA Table Z-1 Limits for A			
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-2 (29 CFR 193	10.1000)		
Components	Туре	Value	
BENZENE (CAS 71-43-2)	Ceiling	25 ppm	
	TWA	10 ppm	
US. OSHA Table Z-3 (29 CFR 193	LO.1000)		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	Form
BENZENE (CAS 71-43-2)	STEL	2.5 ppm	
	TWA	0.5 ppm	
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
U.S NIOSH			
Components	Туре	Value	
ASPHALT, OXIDIZED (CAS 64742-93-4)	REL	5 mg/m3	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	Form
BENZENE (CAS 71-43-2)	STEL	1 ppm	
	TWA	0.1 ppm	
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Material name: BLACKHAWK™ 5500 SEAL KOTE LIGHT

#### **Biological limit values**

#### **ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
BENZENE (CAS 71-43-2)	25 μg/g	S-Phenylmerca pturic acid	Creatinine in urine	*

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

**US - California OELs: Skin designation** 

BENZENE (CAS 71-43-2) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation** 

BENZENE (CAS 71-43-2) Can be absorbed through the skin.

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection

**Hand protection** Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other It is a good industrial hygiene practice to minimize skin contact. Wear appropriate clothing to

prevent any possibility of liquid contact and repeated or prolonged vapor contact.

When workers are facing concentrations above the exposure limit they must use appropriate **Respiratory protection** 

certified respirators.

Thermal hazards Not available.

**General hygiene** considerations

When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Handle in accordance with good

industrial hygiene and safety practice.

## 9. Physical and chemical properties

**Appearance** Viscous liquid

Physical state Solid. **Form** Liquid.

Color Brown to Black Odor Mild Petroleum Odor

**Odor threshold** Not available. Not available. Melting point/freezing point Not available. Initial boiling point and

boiling range

212 °F (100 °C)

100.0 - 140.0 °F (37.8 - 60.0 °C) Cleveland Open Cup Flash point

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit -

upper (%)

Not available.

**Explosive limit - lower** 

(%)

Not available.

**Explosive limit - upper** 

(%)

Not available.

4.00 hPa estimated Vapor pressure

Vapor density > 1

Relative density Not available. Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot availableDecomposition temperatureNot availableViscosityNot available

Other information

**Specific gravity** 1.01 **VOC** < 350 g/l

## 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport

**Chemical stability** Stable at normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

**Conditions to avoid** Heat, flames and sparks. **Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition** 

products

Irritants. Carbon oxides. Sulphur oxides.

## 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation** Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea

**Skin contact** May be irritating to the skin. Frequent or prolonged contact may defat and dry the skin, leading to

discomfort and dermatitis.

**Eye contact** May be irritating to eyes.

**Ingestion** May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics

Not available.

#### Information on toxicological effects

**Acute toxicity** Not classified.

**Skin corrosion/irritation**Causes skin irritation. **Serious eye damage/eye**May be irritating to eyes.

irritation

Respiratory or skin sensitization

**Respiratory sensitization** Not available. **Skin sensitization** Not a skin sensitizer.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** May cause cancer.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT, OXIDIZED (CAS 64742-93-4) 2A Probably carcinogenic to humans.

BENZENE (CAS 71-43-2) 1 Carcinogenic to humans. QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

BENZENE (CAS 71-43-2) Cancer
QUARTZ (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

BENZENE (CAS 71-43-2) Known To Be Human Carcinogen. QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

**Reproductive toxicity** Not classified.

SDS US

Specific target organ toxicity

- single exposure

Central nervous system. May cause drowsiness and dizziness.

Specific target organ toxicity

- repeated exposure

Not available.

Not classified. **Aspiration hazard** 

**Chronic effects** Prolonged exposure may cause chronic effects.

## 12. Ecological information

**Ecotoxicity** Components of this product are hazardous to aquatic life. Accumulation in aquatic organisms is

expected. Not expected to be harmful to aquatic organisms.

Product		Species	Test Results
BLACKHAWK™ 5500 S	SEAL KOTE LIGHT		
Aquatic			
Crustacea	EC50	Daphnia	10499.4902 mg/l, 48 hours estimated
Fish	LC50	Fish	43553 mg/l, 96 hours estimated
Components		Species	Test Results
BENZENE (CAS 71-43	-2)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	8.76 - 15.6 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	7.2 - 11.7 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Persistence and degradability** Not available. **Bioaccumulative potential** Not available.

Partition coefficient n-octanol / water (log Kow)

**BENZENE** 2.13

Mobility in soil Not available. Other adverse effects Not available.

## 13. Disposal considerations

**Disposal instructions** Contract with a disposal operator licensed by the Law on Disposal and Cleaning. Dispose of this

material and its container to hazardous or special waste collection point. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose in accordance with all applicable

regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Waste from residues /

unused products

Dispose of in accordance with local regulations.

Offer rinsed packaging material to local recycling facilities. Contaminated packaging

## 14. Transport information

DOT

user

UN1999 **UN number** UN proper shipping name Tars, liquid

Transport hazard class(es)

Class Combustible Liquid

**Subsidiary risk** Label(s) 3 Packing group III**Environmental hazards** 

> Marine pollutant No

Special precautions for If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous

material.

Special provisions B1, B13, IB3, T1, TP3

**Packaging exceptions** 150

Material name: BLACKHAWK™ 5500 SEAL KOTE LIGHT

Packaging non bulk 203 Packaging bulk 242

**IATA** 

**UN number** UN1999 **UN proper shipping name** Tars, liquid

Transport hazard class(es)
Class 3
Subsidiary risk Packing group III
Environmental hazards No.
ERG Code 3L

Special precautions for

user

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Not available.

Cargo aircraft only

Allowed with restrictions.

**IMDG** 

UN number UN1999
UN proper shipping name Tars, liquid
Transport hazard class(es)

Class 3
Subsidiary risk Packing group III
Environmental hazards

Marine pollutantNo.EmSF-E, S-ESpecial precautions forNot available.

user

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

IATA; IMDG



**Further information**If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous material. If shipped by vessel in individual containers that are less than 7.9 gallons (30 L) each,

then IMDG 2.3.2.5 exception applies: Not regulated as a hazardous material.

## 15. Regulatory information

**US federal regulations**This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

BENZENE (CAS 71-43-2) Listed.

**SARA 304 Emergency release notification** 

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

BENZENE (CAS 71-43-2) Cancer

QUARTZ (CAS 14808-60-7) Cancer

BENZENE (CAS 71-43-2) Central nervous system

QUARTZ (CAS 14808-60-7) lung effects BENZENE (CAS 71-43-2) Blood

QUARTZ (CAS 14808-60-7) immune system effects

BENZENE (CAS 71-43-2) Aspiration
QUARTZ (CAS 14808-60-7) kidney effects

BENZENE (CAS 71-43-2) Skin Eye

respiratory tract irritation

Flammability

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

## **SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312** Yes

**Hazardous chemical** 

**Classified hazard** Flammable (gases, aerosols, liquids, or solids)

**categories** Skin corrosion or irritation Germ cell mutagenicity

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

#### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
BENZENE	71-43-2	< 1	_

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE (CAS 71-43-2)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

**US state regulations** WARNING: This product contains a chemical known to the State of California to cause cancer.

## **California Proposition 65**

## California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT, OXIDIZED (CAS 64742-93-4)

BENZENE (CAS 71-43-2)

QUARTZ (CAS 14808-60-7)

Listed: January 1, 1990

Listed: February 27, 1987

Listed: October 1, 1988

## California Proposition 65 - CRT: Listed date/Developmental toxin

BENZENE (CAS 71-43-2) Listed: December 26, 1997

## California Proposition 65 - CRT: Listed date/Male reproductive toxin

BENZENE (CAS 71-43-2) Listed: December 26, 1997

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

BENZENE (CAS 71-43-2)

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS 64742-48-9)

QUARTZ (CAS 14808-60-7)

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes

Country(s) or region **Inventory name** On inventory (yes/no)\* Korea Existing Chemicals List (ECL) New Zealand **New Zealand Inventory** Yes **Philippines** Yes

Philippine Inventory of Chemicals and Chemical Substances

Taiwan Chemical Substance Inventory (TCSI) **Taiwan** Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

## 16. Other information, including date of preparation or last revision

11-25-2020 **Issue date Revision date** 11-23-2021

Version # 02

**Further information** HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Flammability: 2

Instability: 0

References **ACGIH** 

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

The information provided in this Safety Data Sheet is correct to the best of our knowledge Disclaimer

> information and belief at the date of its publication. The information given is designed only as a quidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

**Revision information** Hazard(s) identification: Response

Composition / Information on Ingredients: Disclosure Overrides

Physical & Chemical Properties: Multiple Properties

GHS: Classification

Material name: BLACKHAWK™ 5500 SEAL KOTE LIGHT

5034 Version #: 02 Revision date: 11-23-2021 Issue date: 11-25-2020 9/9

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).