

1. Identification

| | |
|---|---|
| Product identifier | BLACKHAWK™ 5710 MEMBRANE PART A |
| Other means of identification | None. |
| Recommended use | Not available. |
| Recommended restrictions | None known. |
| Manufacturer/Importer/Supplier/Distributor information | |
| Company Name | ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc. |
| Address | 2829 Lakeland Drive Jackson, MS 39232 USA |
| After hours telephone number | 1-800-222-7122 |
| Normal work hours telephone number | 1-877-982-7667 |
| Website | www.ergonarmor.com |
| E-mail | sds@ergon.com |
| Emergency 24-hour telephone number | CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887 |
| Information on operation hours | 8:00 a.m. to 5:00 p.m. |

2. Hazard(s) identification

| | | |
|------------------------------|---|-----------------------------|
| Physical hazards | Flammable liquids | Category 3 |
| Health hazards | Skin corrosion/irritation | Category 2 |
| | Serious eye damage/eye irritation | Category 2 |
| | Germ cell mutagenicity | Category 1 |
| | Carcinogenicity | Category 1 |
| | Specific target organ toxicity, single exposure | Category 3 narcotic effects |
| | Specific target organ toxicity, repeated exposure | Category 2 |
| Environmental hazards | Not classified. | |
| OSHA defined hazards | Not classified. | |

Label elements



| | |
|-------------------------|---|
| Signal word | Danger |
| Hazard statement | Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause cancer. May cause genetic defects. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. |

Precautionary statement Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Wash thoroughly after handling. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Ground/bond container and receiving equipment. Use only outdoors or in a well-ventilated area.

| | |
|--|---|
| Response | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Call a poison center/doctor. Specific treatment see Section 4 of this SDS. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media for extinction. |
| Storage | Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. See section 13 of this SDS for disposal instructions. |
| Hazard(s) not otherwise classified (HNOC) | None known. |
| Supplemental information | None. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|----------------------|---------|
| ASPHALT | | 8052-42-4 | 30 - 40 |
| MINERAL SPIRITS | | 8052-41-3/64742-48-9 | 20 - 30 |
| BENZENE | | 71-43-2 | < 1 |
| QUARTZ | | 14808-60-7 | < 1 |
| Other components below reportable levels | | | 39.62 |

4. First-aid measures

| | |
|---|--|
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. For breathing difficulties, oxygen may be necessary. Call a poison center or doctor/physician if you feel unwell. |
| Skin contact | For hot product, immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. Rinse skin with water/shower. Wash contaminated clothing before reuse. For minor skin contact, avoid spreading material on unaffected skin. Get medical attention if irritation develops and persists. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Continue rinsing. Get medical attention if irritation develops and persists. |
| Ingestion | Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Call a POISON CENTER or doctor/physician. |
| Most important symptoms/effects, acute and delayed | May cause drowsiness or dizziness. Headache. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed. |
| General information | Show this safety data sheet to the doctor in attendance. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. In case of shortness of breath, give oxygen. Keep victim under observation. Wash contaminated clothing before reuse. |

5. Fire-fighting measures

| | |
|--|--|
| Suitable extinguishing media | Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO ₂). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection. |

| | |
|---|--|
| Fire fighting equipment/instructions | In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Do not get water inside container. Some of these materials, if spilled, may evaporate leaving a flammable residue. |
| Specific methods | Move container from fire area if it can be done without risk. In the event of fire and/or explosion do not breathe fumes. |
| General fire hazards | Flammable liquid and vapor. |

6. Accidental release measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | <p>Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.</p> <p>Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.</p> <p>Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.</p> <p>Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.</p> |
| Environmental precautions | Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. |

7. Handling and storage

| | |
|---|---|
| Precautions for safe handling | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Do not use in areas without adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Do not empty into drains. Observe good industrial hygiene practices. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. |
| Conditions for safe storage, including any incompatibilities | Store locked up. Keep containers tightly closed. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store away from incompatible materials (see Section 10 of the SDS). Store in a well-ventilated place. Keep out of reach of children. |

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

| Components | Type | Value |
|-----------------------|------|-------|
| BENZENE (CAS 71-43-2) | STEL | 5 ppm |
| | TWA | 1 ppm |

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|-------------------------|------|------------|------------------|
| QUARTZ (CAS 14808-60-7) | PEL | 0.05 mg/m3 | Respirable dust. |

US. OSHA Table Z-2 (29 CFR 1910.1000)

| Components | Type | Value |
|-----------------------|---------|--------|
| BENZENE (CAS 71-43-2) | Ceiling | 25 ppm |
| | TWA | 10 ppm |

US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components | Type | Value | Form |
|-------------------------|------|-----------|-------------|
| QUARTZ (CAS 14808-60-7) | TWA | 0.1 mg/m3 | Respirable. |
| | | 2.4 mppcf | Respirable. |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|-------------------------|------|-------------|----------------------|
| ASPHALT (CAS 8052-42-4) | TWA | 0.5 mg/m3 | Inhalable fume. |
| BENZENE (CAS 71-43-2) | STEL | 2.5 ppm | |
| | TWA | 0.5 ppm | |
| QUARTZ (CAS 14808-60-7) | TWA | 0.025 mg/m3 | Respirable fraction. |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|-------------------------|---------|------------|------------------|
| ASPHALT (CAS 8052-42-4) | Ceiling | 5 mg/m3 | Fume. |
| BENZENE (CAS 71-43-2) | STEL | 1 ppm | |
| | TWA | 0.1 ppm | |
| QUARTZ (CAS 14808-60-7) | TWA | 0.05 mg/m3 | Respirable dust. |

Biological limit values**ACGIH Biological Exposure Indices**

| Components | Value | Determinant | Specimen | Sampling Time |
|-----------------------|---------|-------------------------------|------------------------|---------------|
| BENZENE (CAS 71-43-2) | 25 µg/g | S-Phenylmercap- turic acid | Creatinine in urine | * |

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

BENZENE (CAS 71-43-2) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

BENZENE (CAS 71-43-2) Danger of cutaneous absorption

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Avoid contact with clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

| | |
|-----------------------|---|
| Appearance | Black liquid |
| Physical state | Liquid. |
| Form | Liquid. Semi-solid at ambient temperature |

| | |
|---|-----------------------------------|
| Color | Brown to Black |
| Odor | Not available. |
| Odor threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | Not available. |
| Initial boiling point and boiling range | Not available. |
| Flash point | 100.0 - 140.0 °F (37.8 - 60.0 °C) |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | Not available. |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Not available. |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Explosive properties | Not explosive. |
| Oxidizing properties | Not oxidizing. |

10. Stability and reactivity

| | |
|---|--|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Stable under normal temperature conditions. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Acids. Strong oxidizing agents. Strong oxidizing agents. Fluorine. |
| Hazardous decomposition products | Irritants. Toxic gas. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|---|
| Inhalation | Prolonged inhalation may be harmful. |
| Skin contact | Causes skin irritation. |
| Eye contact | Causes serious eye irritation. |
| Ingestion | May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure. |

| | |
|---|--|
| Symptoms related to the physical, chemical and toxicological characteristics | May cause drowsiness or dizziness. Headache. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. |
|---|--|

Information on toxicological effects

| | |
|-----------------------|----------------------------|
| Acute toxicity | Not known. Not classified. |
|-----------------------|----------------------------|

| Product | Species | Test Results |
|---------------------------------|---------|--------------|
| BLACKHAWK™ 5710 MEMBRANE PART A | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | 848000 mg/kg |

* Estimates for product may be based on additional component data not shown.

| | |
|--|----------------------------|
| Skin corrosion/irritation | Causes skin irritation. |
| Serious eye damage/eye irritation | May be irritating to eyes. |

Respiratory or skin sensitization

| | |
|----------------------------------|-------------------------------|
| Respiratory sensitization | Not a respiratory sensitizer. |
| Skin sensitization | Causes skin irritation. |
| Germ cell mutagenicity | May cause genetic defects. |
| Carcinogenicity | May cause cancer. |

IARC Monographs. Overall Evaluation of Carcinogenicity

| | |
|--|---|
| ASPHALT (CAS 8052-42-4) | 2B Possibly carcinogenic to humans. |
| BENZENE (CAS 71-43-2) | 1 Carcinogenic to humans. |
| MINERAL SPIRITS (CAS 8052-41-3/64742-48-9) | 3 Not classifiable as to carcinogenicity to humans. |
| QUARTZ (CAS 14808-60-7) | 1 Carcinogenic to humans. |

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

| | |
|-------------------------|--------|
| BENZENE (CAS 71-43-2) | Cancer |
| QUARTZ (CAS 14808-60-7) | Cancer |

US. National Toxicology Program (NTP) Report on Carcinogens

| | |
|-------------------------|-------------------------------|
| BENZENE (CAS 71-43-2) | Known To Be Human Carcinogen. |
| QUARTZ (CAS 14808-60-7) | Known To Be Human Carcinogen. |

| | |
|---|--|
| Reproductive toxicity | Not classified. |
| Specific target organ toxicity - single exposure | May cause drowsiness or dizziness. |
| Specific target organ toxicity - repeated exposure | May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | Not classified. |
| Chronic effects | Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. |

12. Ecological information

| | |
|--------------------|--|
| Ecotoxicity | Accumulation in aquatic organisms is expected. Components of this product are hazardous to aquatic life. |
|--------------------|--|

| Product | Species | | Test Results |
|---------------------------------|----------------|---|----------------------------------|
| BLACKHAWK™ 5710 MEMBRANE PART A | | | |
| Aquatic | | | |
| Crustacea | EC50 | Daphnia | 12244.0615, 48 hours |
| Fish | LC50 | Fish | 50774.9375, 96 hours |
| Acute | | | |
| Crustacea | EC50 | Daphnia | 6255.7485, 48 hours estimated |
| Fish | LC50 | Fish | 4192.4731, 96 hours estimated |
| Components | Species | | Test Results |
| BENZENE (CAS 71-43-2) | | | |
| Aquatic | | | |
| Acute | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | >= 8.76 - <= 15.6 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 5.9, 96 hours |

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

BENZENE

2.13

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Contract with a disposal operator licensed by the Law on Disposal and Cleaning. Dispose of this material and its container to hazardous or special waste collection point. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

D001: Waste Flammable material with a flash point <140 F

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Offer rinsed packaging material to local recycling facilities.

14. Transport information

DOT

UN number

UN1999

UN proper shipping name

Tars, liquid including road oils and cut back bitumens

Transport hazard class(es)

Class

3

Subsidiary risk

-

Label(s)

3

Packing group

III

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling. If shipped by ground in individual containers that are less than 119 gallons (450 L): Not regulated as a hazardous material. (49 CFR 173.121)

Special provisions

B1, B13, IB3, T1, TP3

Packaging exceptions

150

Packaging non bulk

203

Packaging bulk

242

IATA

UN number

UN1999

UN proper shipping name

Tars, liquid including road asphalt and oils, bitumen and cut backs

Transport hazard class(es)

Class

3

Subsidiary risk

-

Packing group

III

Environmental hazards

No.

ERG Code

3L

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN number

UN1999

UN proper shipping name

TARS, LIQUID including road oils, and cutback bitumens

Transport hazard class(es)

Class

3

Subsidiary risk

-

Packing group

III

Environmental hazards**Marine pollutant****EmS****Special precautions for user**

No.

F-E, S-E

Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

DOT**IATA; IMDG****General information**

If shipped by ground in individual containers that are less than 119 gallons (450 L): Not regulated as a hazardous material (49 CFR 173.121). If shipped by vessel in individual containers that are less than 119 gallons (450 L) each, then IMDG 2.3.2.5 exception applies. Not subject to the provisions for marking, labelling, and testing of packages. "Transport in accordance with 2.3.2.5 of the IMDG code."

15. Regulatory information**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

Toxic Substances Control Act (TSCA)

One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ASPHALT (CAS 8052-42-4)

Listed.

BENZENE (CAS 71-43-2)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

BENZENE (CAS 71-43-2)

Cancer

QUARTZ (CAS 14808-60-7)

Cancer

BENZENE (CAS 71-43-2)

Central nervous system

QUARTZ (CAS 14808-60-7)

lung effects

BENZENE (CAS 71-43-2)

Blood

QUARTZ (CAS 14808-60-7)

immune system effects

BENZENE (CAS 71-43-2)

Aspiration

QUARTZ (CAS 14808-60-7)

kidney effects

BENZENE (CAS 71-43-2)

Skin

Eye

respiratory tract irritation

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical Yes**Classified hazard categories**

Flammable (gases, aerosols, liquids, or solids)
 Skin corrosion or irritation
 Serious eye damage or eye irritation
 Germ cell mutagenicity
 Carcinogenicity
 Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. |
|---------------|------------|----------|
| BENZENE | 71-43-2 | < 1 |

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

BENZENE (CAS 71-43-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**US state regulations**

WARNING: This product contains chemicals known to the State of California to cause cancer and reproductive harm.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ASPHALT (CAS 8052-42-4)
 BENZENE (CAS 71-43-2)
 MINERAL SPIRITS (CAS 8052-41-3/64742-48-9)
 QUARTZ (CAS 14808-60-7)

California Proposition 65

WARNING: This product can expose you to chemicals including BENZENE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

BENZENE (CAS 71-43-2) Listed: February 27, 1987
 QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

California Proposition 65 - CRT: Listed date/Developmental toxin

BENZENE (CAS 71-43-2) Listed: December 26, 1997

California Proposition 65 - CRT: Listed date/Male reproductive toxin

BENZENE (CAS 71-43-2) Listed: December 26, 1997

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia | Australian Inventory of Industrial Chemicals (AICIS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | Yes |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| Taiwan | Taiwan Chemical Substance Inventory (TCSI) | Yes |

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|--|---|------------------------|
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |
| *A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s). | | |

16. Other information, including date of preparation or last revision

| | |
|----------------------|---|
| Issue date | 12-02-2021 |
| Revision date | 08-29-2023 |
| Version # | 07 |
| Further information | HMIS® is a registered trade and service mark of the NPCA. |
| NFPA ratings | Health: 2 Flammability: 2 Instability: 0 |
| References | ACGIH ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices EPA: AQUIRE database HSDB® - Hazardous Substances Data Bank IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents |
| Disclaimer | The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Ergon Armor cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. |
| Revision information | This document has undergone significant changes and should be reviewed in its entirety. |