

SELECTION & SPECIFICATION DATA

Type	Roof Flashing and Repair Cement
Description	Blackhawk 5405 Wet/Dry Flashing Cement is an asbestos free, fiber-reinforced asphalt roofing cement for wet weather repair of roof leaks in warmer application environments. Composed of select asphalt and special grade solvent, this material has a smooth troweling consistency. It is also available in a winter grade formula as Blackhawk™ Wet/Dry Flashing Cement WG for cooler application environments.
Uses	<ul style="list-style-type: none">• Patching temporary holes and cracks• Seals under standing water• Setting roof drains• Adhere modified bitumen membranes• Can also be used as a general-purpose flashing cement
Color	Black
Primer	Self-priming
Topcoats	Can be coated with urethane, acrylic or Silicone after full cure. Blackhawk 5405 Wet/Dry Flashing Cement can also receive granule embedment while still wet.

SUBSTRATES & SURFACE PREPARATION

All	All surfaces must be clean and free from debris and loose scale material or anything that may interfere with adhesion or act as a bond breaker with the desired substrate. Blackhawk 5405 Wet/Dry Flashing Cement is formulated to be applied to wet or damp surfaces and can even be applied under standing water.
------------	---

MIXING & THINNING

Mixing	No mixing necessary
Thinning	Do not thin
Cleanup	Mineral spirits or equivalent solvent

APPLICATION GUIDELINES

Trowel	1/8-inch square notched trowel or round/bullnose roofing trowel.
---------------	--

PACKAGING, ESTIMATING & HANDLING

ITEM #	PACKAGING
K-5405-005-001	Pail - 4.7 gallons
Theoretical Coverage Rate	14 square feet per gallon at 1/8-inch thickness
Storage & Shelf Life	Estimated shelf life is 24 months when stored in a dry area at 75°F (24°C). When kept at recommended storage conditions and in original unopened containers. Actual shelf life may vary with storage conditions. Do not store below 40°F (4°C) or above 110°F (43°C). Store indoors. This product is not affected by excursions below published storage temperatures. Always inspect the product prior to use to make sure it is smooth and homogeneous.

SAFETY

Safety	Mixes and applications of this product present various hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.
Ventilation	Thorough air circulation must be used during and after application until the product is cured. User should test and monitor exposure levels to ensure all personnel are within safe limits. Consult product SDS for further information.

TYPICAL PHYSICAL PROPERTIES

SPECIFICATIONS	CATEGORY	RESULTS
ASTM D4586	Type 1	Pass
ASTM D6511	Uniformity	Pass
ASTM D6511	Workability	Pass
ASTM D6511 Blistering	Behavior at 140°F (60°C)	None
ASTM D6511 Cracking	Pliability at 32°F (0°C)	Pass
ASTM D6511	Adhesion to Wet or Damp Surfaces	Pass
Sag/Slide	Behavior at 140°F (60°C)	Pass

Rev. 12/2024

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see ergonarmor.com.