### SAFETY DATA SHEET



#### 1. Identification

**Product identifier** R-17-A-73 ASPHALT COATING/PRIMER

Other means of identification

BH5136 **Synonyms** 

NSF/ANSI 61 Certified Asphalt Coating & Primer Recommended use

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

**Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

**Address** 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

E-mail

1-800-222-7122

**Normal work hours** telephone number

1-877-982-7667

Website

www.ergonarmor.com sds@ergon.com

**Emergency 24-hour** 

telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

**Information on** 8:00 a.m. to 5:00 p.m.

operation hours

# 2. Hazard(s) identification

# Hazards for the product as sold

**Physical hazards** Category 1 Aerosols **Health hazards** Serious eye damage/eye irritation Category 2

Carcinogenicity Category 2

Specific target organ toxicity, single

Specific target organ toxicity, repeated

exposure

Category 3 respiratory tract irritation

exposure

**Environmental hazards** Not classified. **OSHA** defined hazards Not classified.

**Label elements** 



Signal word Danger

**Hazard statement** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes

serious eye irritation. Suspected of causing cancer. May cause respiratory irritation. May cause

Category 2

damage to organs through prolonged or repeated exposure.

**Precautionary statement** 

**Prevention** 

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Pressurized container: Do not pierce or burn, even after use.

Material name: R-17-A-73 ASPHALT COATING/PRIMER

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

> and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Specific treatment see Section 4 of this SDS. IF exposed or concerned: Get medical

advice/attention. Call a poison center/doctor if you feel unwell.

Storage Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international

regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

**Supplemental information** None.

# 3. Composition/information on ingredients

### **Mixtures**

_	Chemical name	Common name and synonyms	CAS No./Unique ID	%
	ASPHALT		64742-93-4	25 - 50
	VM&P NAPHTHA		64742-89-8	25 - 50
	DIMETHYL ETHER		115-10-6	15 - 25

### 4. First-aid measures

**Inhalation** Move to fresh air. Oxygen or artificial respiration if needed. Induce artificial respiration with the

aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Get medical attention, if needed.

Wash off immediately with plenty of water. Take off contaminated clothing and wash before Skin contact

reuse. Get medical attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and

persists.

**Ingestion** Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting

occurs, keep head low so that stomach content doesn't get into the lungs. Get medical

attention if symptoms occur.

cause temporary irritation.

Most important symptoms/effects, acute

and delayed

**Indication of immediate** medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Causes eye irritation. Irritating to mouth, throat, and stomach. Direct contact with skin may

Coughing. Shortness of breath. May cause redness and pain. May cause drowsiness or dizziness.

**General information** Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

Suitable extinguishing media Foam. Dry powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Vapors may form explosive mixtures with air. During fire, gases hazardous to health may be formed.

**Special protective equipment** and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Stop leak if you can do so without risk. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray.

**Specific methods** 

Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards** No unusual fire or explosion hazards noted.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unnecessary personnel away. Keep upwind. Ensure adequate ventilation. Wear appropriate personal protective equipment. Keep people away from and upwind of spill/leak.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Prevent entry into waterways, sewer,

basements or confined areas.

**Environmental precautions** Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling Avoid prolonged exposure. Observe good industrial hygiene practices. Keep away from sources

of ignition - No smoking. Provide adequate ventilation. Do not breathe

dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Store in a closed container away from incompatible materials. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place.

### 8. Exposure controls/personal protection

#### **Occupational exposure limits**

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components **Type** Value VM&P NAPHTHA (CAS PEL 400 mg/m3 64742-89-8)

**US. ACGIH Threshold Limit Values (TLV)** 

Components **Type** Value VM&P NAPHTHA (CAS **TWA** 100 ppm 64742-89-8)

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components **Value Type** VM&P NAPHTHA (CAS **IDLH** 1 %

64742-89-8)

1000 ppm

100 ppm

**U.S. - NIOSH** 

**Components Value Type** ASPHALT (CAS **REL** 5 mg/m3 64742-93-4)

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Value **Type** 

VM&P NAPHTHA (CAS TWA 400 mg/m3 64742-89-8)

100 ppm

US. OARS. Workplace Environmental Exposure Level (WEEL) Guide

Components **Type Value** DIMETHYL ETHER (CAS **TWA** 1880 mg/m3 115-10-6) 1000 ppm

No biological exposure limits noted for the ingredient(s). **Biological limit values** 

**Exposure guidelines** 

**US ACGIH Threshold Limit Values: Skin designation** 

VM&P NAPHTHA (CAS 64742-89-8) Danger of cutaneous absorption

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Material name: R-17-A-73 ASPHALT COATING/PRIMER 6369 Version #: 03 Revision date: 07-23-2025 Issue date: 04-25-2022 Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Nitrile.

Other Wear appropriate chemical resistant clothing.

**Respiratory protection** When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

**General hygiene** considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

## 9. Physical and chemical properties

**Physical state** Liquid. **Form** Aerosol. Color Not available. Odor Aromatic. Melting point/freezing point Not available.

**Boiling point or initial boiling** 

-12.82 °F (-24.9 °C)

point and boiling range

**Flammability** Not available.

Upper/lower flammability or explosive limits

**Explosive limit - lower** 

3 %

(%)

**Explosive limit - upper** 

18.6 %

(%)

-43.6 °F (-42.0 °C) Flash point

**Auto-ignition temperature** Not available. **Decomposition temperature** Not available. pН Not available. Kinematic viscosity Not available.

Solubility

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

Not available. Vapor pressure

Density and/or relative density

> 0.77 - < 0.85 (Water equals 1.00) **Relative density** 

Vapor density Not available. **Particle characteristics** Not available.

### 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions. **Possibility of hazardous** Hazardous polymerization does not occur.

reactions Conditions to avoid

Avoid temperatures exceeding the flash point. Heat, flames and sparks. Contact with

incompatible materials.

**Incompatible materials** None known.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

Material name: R-17-A-73 ASPHALT COATING/PRIMER 6369 Version #: 03 Revision date: 07-23-2025 Issue date: 04-25-2022

### 11. Toxicological information

Information on likely routes of exposure

**Inhalation** May cause irritation to the respiratory system. Symptoms of overexposure may be headache,

dizziness, tiredness, nausea and vomiting.

**Skin contact** Prolonged skin contact may cause temporary irritation.

**Eye contact** Causes serious eye irritation.

**Ingestion** May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Breathing of high vapor concentrations may cause dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Irritating to mouth, throat,

and stomach. Causes serious eye irritation. Mild skin irritation.

Information on toxicological effects

**Acute toxicity** Not available.

Product Species Test Results

R-17-A-73 ASPHALT COATING/PRIMER

Acute Inhalation

LC50 Rat 175 mg/l, 4 Hours

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not available.

**Skin sensitization** Prolonged skin contact may cause temporary irritation.

**Germ cell mutagenicity** Not available.

**Carcinogenicity** Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 64742-93-4) 2A Probably carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity

- single exposure

May cause respiratory irritation.

Specific target organ toxicity

- repeated exposure

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Not available.

**Chronic effects** Prolonged inhalation may be harmful.

12. Ecological information

**Ecotoxicity** Components of this product are hazardous to aquatic life.

Product Species Test Results

R-17-A-73 ASPHALT COATING/PRIMER

**Aquatic** 

Crustacea EC50 Daphnia 12.5 mg/l, 48 hours
Fish LC50 Fish 30 mg/l, 96 hours

Material name: R-17-A-73 ASPHALT COATING/PRIMER

**Test Results** Components **Species** 

VM&P NAPHTHA (CAS 64742-89-8)

**Aquatic** 

Crustacea EC50 Water flea (Daphnia pulex) >= 2.7 - <= 5.1 mg/l, 48 hours

LC50 Fish Rainbow trout, donaldson trout 8.8 mg/l, 96 hours

(Oncorhynchus mykiss)

8.8 mg/l, 96 hours

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

Partition coefficient n-octanol / water (log Kow)

DIMETHYL ETHER 0.1

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the

waste disposal company.

Waste from residues /

unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container

is emptied.

Not assigned.

## 14. Transport information

DOT

**UN number** UN1950

**UN proper shipping name** Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 **Subsidiary hazard** 2.1 Label(s) **Packing group Environmental hazards** 

Marine pollutant No.

Special precautions for

user

N82 **Special provisions** Packaging exceptions 306 Packaging non bulk None Packaging bulk None

**IATA** 

UN1950 **UN number** 

**UN proper shipping name** Aerosols, flammable

Transport hazard class(es)

Class 2.1 **Subsidiary hazard Packing group Environmental hazards** No. **ERG Code** 10L Not assigned.

Special precautions for

user

Other information

Passenger and cargo Allowed with restrictions.

aircraft

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Cargo aircraft only** Allowed with restrictions.

**IMDG** 

UN number UN1950

**UN proper shipping name** Aerosols, flammable

Transport hazard class(es)

Class 2.1
Subsidiary hazard Packing group Environmental hazards

Marine pollutantNo.EmSF-D, S-USpecial precautions forNot assigned.

use

Transport in bulk according to Not available.

**IMO** instruments

**DOT** 



IATA; IMDG



### 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

**Toxic Substances Control Act** (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

**SARA 304 Emergency release notification** 

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

**SARA 302 Extremely hazardous substance** 

Not listed.

**SARA 311/312** Yes

**Hazardous chemical** 

**Classified hazard** categories

Flammable (gases, aerosols, liquids, or solids) Serious eye damage or eye irritation

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

#### SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

DIMETHYL ETHER (CAS 115-10-6)

Safe Drinking Water Act Not regulated.

(SDWA)

#### **US state regulations**

#### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

VM&P NAPHTHA (CAS 64742-89-8)

#### **California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

#### **International Inventories**

Country(s) or region	Inventory name On inventory (yes/	no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe European Inventory of Existing Commercial Chemical Substances (EINECS)		Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the		

governing country(s).

### 16. Other information, including date of preparation or last revision

04-25-2022 **Issue date Revision date** 07-23-2025

Version # 03

NFPA ratings Health: 2

Flammability: 4 Instability: 0

The information provided in this Safety Data Sheet is correct to the best of our knowledge, Disclaimer

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any

other materials or in any process, unless specified in the text.

Material name: R-17-A-73 ASPHALT COATING/PRIMER

6369 Version #: 03 Revision date: 07-23-2025 Issue date: 04-25-2022