

1. Identification

Product identifier	BLACKHAWK™ 5103 SP ASPHALT PRIMER
Other means of identification	None.
Recommended use	Not available.
Recommended restrictions	None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name	Armor Limited, Inc.
Address	2410 US-15 South, Sumter, SC 29150

After hours telephone number	1-877-982-7667
Normal work hours telephone number	1-877-982-7667
Website	www.armor-inc.com
E-mail	customerservice@armor-inc.com
Emergency 24-hour telephone number	CHEMTREC North America: +1-800-424-9300, International: +1-703-527-3887
Information on operation hours	8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Skin corrosion/irritation	Category 2
	Germ cell mutagenicity	Category 1
	Carcinogenicity	Category 1
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement May cause genetic defects. May cause cancer. Flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Ground/bond container and receiving equipment. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response

IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. Specific treatment see Section 4 of this SDS. In case of fire: Use appropriate media for extinction. If skin irritation occurs, seek medical advice/attention. Take off contaminated clothing and wash before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF ON SKIN: Wash with plenty of soap and water.

Storage	Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations. See section 13 of this SDS for disposal instructions.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT, OXIDIZED		64742-93-4	50 - 55
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY		64742-48-9	40 - 50
Nonexempt Mineral Spirits		8052-41-3	28.16
BENZENE		71-43-2	<1

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing difficulties, oxygen may be necessary. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if needed.

Skin contact For hot product, immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. For minor skin contact, avoid spreading material on unaffected skin. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth thoroughly. Call a POISON CENTER or doctor/physician. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed Not available.

Indication of immediate medical attention and special treatment needed In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Foam. Carbon dioxide (CO₂). Water fog. Dry chemical powder.

Unsuitable extinguishing media Do not use water jet.

Specific hazards arising from the chemical Fire may produce irritating, corrosive and/or toxic gases.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Do not get water inside container. Some of these materials, if spilled, may evaporate leaving a flammable residue.

Specific methods In the event of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

7. Handling and storage

Precautions for safe handling

Avoid heat, sparks, open flames and other ignition sources. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Do not use in areas without adequate ventilation. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container closed. Keep container dry. Keep away from food, drink and animal feedingstuffs. Keep out of reach of children. Use care in handling/storage.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
BENZENE (CAS 71-43-2)	STEL	5 ppm
	TWA	1 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Nonexempt Mineral Spirits (CAS 8052-41-3)	PEL	2900 mg/m ³
		500 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
BENZENE (CAS 71-43-2)	Ceiling	25 ppm
	TWA	10 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
BENZENE (CAS 71-43-2)	STEL	2.5 ppm
	TWA	0.5 ppm
Nonexempt Mineral Spirits (CAS 8052-41-3)	TWA	100 ppm

U.S. - NIOSH

Components	Type	Value
ASPHALT, OXIDIZED (CAS 64742-93-4)	REL	5 mg/m ³

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
BENZENE (CAS 71-43-2)	STEL	1 ppm
	TWA	0.1 ppm
Nonexempt Mineral Spirits (CAS 8052-41-3)	Ceiling	1800 mg/m ³
	TWA	350 mg/m ³

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
BENZENE (CAS 71-43-2)	25 µg/g	S-Phenylmercap- turic acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

BENZENE (CAS 71-43-2) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

BENZENE (CAS 71-43-2) Danger of cutaneous absorption

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection

Hand protection

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

Other

It is a good industrial hygiene practice to minimize skin contact. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards

Not available.

General hygiene considerations

When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance

Viscous liquid

Physical state

Solid.

Form

Liquid.

Color

Brown to. Black

Odor

Mild Petroleum Odor

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

No Data

Initial boiling point and boiling range

300 °F (148.89 °C)

Flash point

105.0 °F (40.6 °C) Tag Closed Cup

Evaporation rate

70

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

< 50 psi

Vapor density

> 4.5

Relative density

Not available.

Solubility(ies)

Solubility (water)

Insoluble

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

No Data

Decomposition temperature

Not available.

Viscosity Not available.

Other information

VOC < 450 g/l

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable at normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Irritants. Carbon oxides. Sulphur oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact May be irritating to eyes.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

Acute toxicity Not classified.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Not available.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization Not a skin sensitizer.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT, OXIDIZED (CAS 64742-93-4)	2A Probably carcinogenic to humans.
BENZENE (CAS 71-43-2)	1 Carcinogenic to humans.
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS 64742-48-9)	3 Not classifiable as to carcinogenicity to humans.
Nonexempt Mineral Spirits (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

BENZENE (CAS 71-43-2)	Cancer
-----------------------	--------

US. National Toxicology Program (NTP) Report on Carcinogens

BENZENE (CAS 71-43-2)	Known To Be Human Carcinogen.
-----------------------	-------------------------------

Reproductive toxicity Not classified.

Specific target organ toxicity - single exposure Central nervous system. May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not classified.

Chronic effects Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Product	Species	Test Results
BLACKHAWK™ 5103 SP ASPHALT PRIMER		
Aquatic		
Crustacea	EC50	Daphnia
Fish	LC50	Fish
		6255.0151, 48 hours estimated
		25946.4688, 96 hours estimated

Components	Species	Test Results
BENZENE (CAS 71-43-2)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)
		>= 8.76 - <= 15.6 mg/l, 48 hours
		5.9, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability Not available.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

BENZENE 2.13

Mobility in soil Not available.

Other adverse effects Not available.

13. Disposal considerations

Disposal instructions Dispose of contents/container in accordance with local/regional/national/international regulations. If discarded, this product is considered a RCRA ignitable waste, D001.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Waste from residues / unused products Dispose of in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number UN1999

UN proper shipping name Tars, liquid

Transport hazard class(es)

Class Combustible Liquid

Subsidiary risk -

Label(s) 3

Packing group III

Special precautions for user If shipped by ground in individual containers that are less than 119 gallons (450 L): Not regulated as a hazardous material. (49 CFR 173.121)

Special provisions B1, B52, IB3, T4, TP1, TP29

Packaging exceptions 150

Packaging non bulk 203

Packaging bulk 242

IATA

UN number UN1999

UN proper shipping name Tars, liquid

Transport hazard class(es)

Class 3

Subsidiary risk -

Packing group III

Environmental hazards No.

ERG Code 3L

Special precautions for user Not available.

Other information

Passenger and cargo aircraft Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number	UN1999
UN proper shipping name	Tars, liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
CERCLA/SARA Hazardous Substances - Not applicable.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BENZENE (CAS 71-43-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

BENZENE (CAS 71-43-2) Cancer
Central nervous system
Blood
Aspiration
Skin
Eye
respiratory tract irritation
Flammability

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Yes

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Germ cell mutagenicity
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
BENZENE	71-43-2	<1

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

BENZENE (CAS 71-43-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**US state regulations**

WARNING: This product contains chemicals known to the State of California to cause cancer and reproductive harm.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

BENZENE (CAS 71-43-2)

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS 64742-48-9)

Nonexempt Mineral Spirits (CAS 8052-41-3)

California Proposition 65**California Proposition 65 - CRT: Listed date/Carcinogenic substance**

ASPHALT, OXIDIZED (CAS 64742-93-4)

Listed: January 1, 1990

BENZENE (CAS 71-43-2)

Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Developmental toxin

BENZENE (CAS 71-43-2)

Listed: December 26, 1997

California Proposition 65 - CRT: Listed date/Male reproductive toxin

BENZENE (CAS 71-43-2)

Listed: December 26, 1997

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	12-01-2020
Revision date	06-29-2023
Version #	03
NFPA ratings	Health: 2 Flammability: 2 Instability: 0

References

ACGIH
EPA: AQUIRE database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents
HSDB® - Hazardous Substances Data Bank
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

Product and Company Identification: Alternate Trade Names
Physical & Chemical Properties: Multiple Properties