SAFETY DATA SHEET



1. Identification

Product identifier PENNTROWEL™ Epoxy Primer Resin

Other means of identification None.

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

1-800-222-7122

Normal work hours

telephone number

1-877-982-7667

Website www.ergonarmor.com
E-mail sds@ergon.com

Emergency 24-hour

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

telephone number

Information on operation 8:00 a.m. to 5:00 p.m.

hours

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Sensitization, skin Category 1

Environmental hazards Not classified. **OSHA defined hazards** Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction.

Precautionary statement

Prevention Wear protective gloves/protective clothing. Wash hands thoroughly after handling. Contaminated

work clothing should not be allowed out of the workplace.

ResponseTake off contaminated clothing and wash before reuse. IF ON SKIN: Wash with plenty of soap and

water. If skin irritation or rash occurs: Get medical advice/attention.

Storage Store in a well-ventilated place. Keep container tightly closed.

Disposal Dispose of contents/container to an appropriate treatment and disposal facility in accordance with

applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Material name: PENNTROWEL™ Epoxy Primer Resin

Chemical name	Common name and synonyms	CAS number	%
BISPHENOL A-(EPICHLOROHYDRIN) EPOXY RESIN		25068-38-6	65 - 85
BUTYL GLYCIDYL ETHER		2426-08-6	20 - 35
Other components below reportable	levels		12.2

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

> Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician if you feel

unwell.

Skin contact Remove and isolate contaminated clothing and shoes. Wash off with soap and plenty of water. For

minor skin contact, avoid spreading material on unaffected skin. Get medical attention if irritation

develops and persists. Wash clothing separately before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Do not induce vomiting. Do not use mouth-to-mouth method if victim ingested the substance. IF Ingestion

SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. If vomiting occurs,

Upper respiratory tract irritation. Irritation of nose and throat. Irritation of eyes and mucous

membranes. Prolonged exposure may cause chronic effects. May cause allergic skin reaction.

keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delaved

Indication of immediate medical attention and special treatment needed

In case of shortness of breath, give oxygen. Symptoms may be delayed.

General information If you feel unwell, seek medical advice (show the label where possible). Wash contaminated

clothing before reuse.

Irritant effects.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water spray. Water fog. Foam. Carbon dioxide (CO2). Powder.

Not available.

Specific hazards arising from

the chemical

No unusual fire or explosion hazards noted.

Special protective equipment and precautions for

firefighters Fire fighting

equipment/instructions

Specific methods

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Water runoff can cause environmental

damage.

In the event of fire, cool tanks with water spray. Move container from fire area if it can be done

without risk.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Avoid inhalation of vapors or mists. Avoid skin contact and inhalation of vapors during disposal of spills.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth or absorbent material then place into containers. Prevent product from entering drains.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Do not breathe dust/fume/gas/mist/vapors/spray. Do not get this material in contact with eyes. Do

not get this material in contact with skin. Do not get this material on clothing. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Avoid prolonged exposure. Wash hands thoroughly after handling. Avoid release to the environment.

Conditions for safe storage,

including any incompatibilities Store in a well-ventilated place. Store in original tightly closed container. Store in a closed container away from incompatible materials. Store in accordance with local/regional/national/international regulation.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants	(29 CFR 1910.1000)
---	--------------------

Components	Туре	Value	
BUTYL GLYCIDYL ETHER (CAS 2426-08-6)	PEL	270 mg/m3	
		50 ppm	
US. ACGIH Threshold Limit Val	ues		
Components	Туре	Value	
BUTYL GLYCIDYL ETHER (CAS 2426-08-6)	TWA	3 ppm	
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	
BUTYL GLYCIDYL ETHER (CAS 2426-08-6)	Ceiling	30 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

BUTYL GLYCIDYL ETHER (CAS 2426-08-6) Can be absorbed through the skin.

Appropriate engineering

controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

5.6 ppm

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical goggles are recommended.

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Wear appropriate chemical resistant clothing. Chemical resistant gloves.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Not available.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes. Avoid contact with eyes. Avoid contact with skin. Avoid contact with clothing. Wash hands after handling. Wash hands before breaks and immediately after handling the product. Wash hands after handling and before eating. Keep away from food and drink. Contaminated work clothing should not be allowed out of the workplace.

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Liquid. **Appearance Physical state** Liquid. **Form** Liauid.

> Color Colourless to light yellow.

Odor Mild. Sweet. **Odor threshold** Not available. Not available.

Material name: PENNTROWEL™ Epoxy Primer Resin 5277 Version #: 03 Revision date: 06-02-2021 Issue date: 05-17-2021

Melting point/freezing point Not available.

Initial boiling point and Not available.

boiling range Flash point

> 230.0 °F (> 110.0 °C) Pensky-Martens Closed Cup

Evaporation rateNot available. **Flammability (solid, gas)**Not available. **Upper/lower flammability or explosive limits**

Flammability limit - lower

(%)

Not available.

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure Nil

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Specific gravity 1.11 @25C

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

This product will autopolymerize at very high temperatures. (>200 deg C)

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point.

Incompatible materials Strong acids, alkalies and oxidizing agents. Amines.

Hazardous decomposition

products

Toxic gas. Irritants.

11. Toxicological information

Information on likely routes of exposure

Inhalation Inhalation of vapors/fumes generated by heating this product may cause respiratory irritation with

throat discomfort, coughing or difficulty breathing.

Skin contact May cause sensitization by skin contact. Causes skin irritation.

Eye contact Causes eye irritation.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Upper respiratory tract irritation. Irritation of nose and throat. Irritant effects.

Information on toxicological effects

Acute toxicity Not applicable.

Material name: PENNTROWEL™ Epoxy Primer Resin

Components Species Test Results

BUTYL GLYCIDYL ETHER (CAS 2426-08-6)

<u>Acute</u> Dermal

LD50 Rabbit 0.788 g/kg

Inhalation

LC50 Rat > 670 mg/l, 8 Hours

Oral

LD50 Rat 2.05 g/kg

Skin corrosion/irritation
Serious eye damage/eye

Causes skin irritation.

May be irritating to eyes.

irritation

Respiratory or skin sensitization

ACGIH sensitization

N-BUTYL GLYCIDYL ETHER (BGE) (CAS 2426-08-6) Dermal sensitization

Respiratory sensitization Not available.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Not classified. **Carcinogenicity** Not assigned.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Not available. Not classified.

Specific target organ toxicity

Specific target organ toxicity

single evnosure

single exposure

Not applicable.

Not classified.

- repeated exposure

Aspiration hazard Not classified.

Chronic effects Hazardous by OSHA criteria. Prolonged exposure may cause chronic effects.

Further information Symptoms may be delayed.

12. Ecological information

Ecotoxicity Accumulation in aquatic organisms is expected. Contains a substance which causes risk of

hazardous effects to the environment. Harmful to aquatic life with long lasting effects. The product

contains a substance which is harmful to aquatic organisms.

Product	Species Test Results		Test Results
PENNTROWEL™ Epox	y Primer Resin		
Aquatic			
Crustacea	EC50	Daphnia	3.5156 mg/l, 48 hours estimated
Fish	LC50	Fish	1.9529 mg/l, 96 hours estimated

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

BUTYL GLYCIDYL ETHER 0.63

Mobility in soilNot available.Other adverse effectsNot available.

^{*} Estimates for product may be based on additional component data not shown.

13. Disposal considerations

Disposal instructions Do not discharge into drains, water courses or onto the ground. This product, in its present state,

when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the

time of disposal, whether the product meets RCRA criteria for hazardous waste.

Hazardous waste code Not applicable.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions). Avoid discharge into water courses or onto the ground.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

UN number UN3082

UN proper shipping name Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A-(EPICHLOROHYDRIN) EPOXY

RESIN)

Transport hazard class(es)

9 Class **Subsidiary risk** Packing group III**Environmental hazards** No. **ERG Code** 91 Not available.

Special precautions for

user

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

9

IMDG

UN number UN3082

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., MARINE POLLUTANT

Transport hazard class(es) Class

Subsidiary risk Packing group TTT

Environmental hazards


Marine pollutant Yes F-A, S-F Special precautions for Not available.

user

Transport in bulk according to Not available.

Annex II of MARPOL 73/78 and the IBC Code

IATA; IMDG



Material name: PENNTROWEL™ Epoxy Primer Resin

5277 Version #: 03 Revision date: 06-02-2021 Issue date: 05-17-2021

Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

Classified hazard Skin corrosion or irritation **categories** Respiratory or skin sensitization

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer and

birth defects or other reproductive harm.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Country(s) or region Inventory name On inventory (yes/no)*

Taiwan Chemical Substance Inventory (TCSI)

Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 05-17-2021

 Revision date
 06-02-2021

Version # 03

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Health: 2 Flammability: 0 Instability: 0

References ACGIH

EPA: AQUIRE database

NLM: Hazardous Substances Data Base HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

US. IARC Monographs on Occupational Exposures to Chemical Agents

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Physical & Chemical Properties: Multiple Properties

Transport Information: Proper Shipping Name/Packing Group

GHS: Classification

Material name: PENNTROWEL™ Epoxy Primer Resin

Yes